
Index

Italicized page numbers represent sources of data in tables, figures, and appendices.

- A**
ABET (*see* Accreditation Board for Engineering and Technology)
Ablation, 34-2 (ftn)
Abrasive, 45-19
 cleaning, 63-13
 machining, 63-5
 type, 63-5 (tbl)
Abscissa, 7-2
Absolute
 convergence, 3-12
 English system, 1-4
 position, 55-9
 pressure, 14-2
 temperature, 24-4, 24-5
Absorbent, 33-7
Absorber, 31-2, 33-7
Absorptance, 31-2
Absorption
 coefficient, 21-7, *A-135*
 coefficient, sound, 68-8
 cycle, 33-6
 dry, 66-37
 dynamometer, 62-12
 factor, 66-40
 process, 66-21
ABS pipe, 16-10
Abundance, relative, 21-2
Accelerated
 Cost Recovery System, 69-21
 depreciation, 69-23
Acceleration
 centripetal, 15-19 (ftn)
 Coriolis, 55-8
 head, 18-2, *18-3*
 linear, 55-4
 normal, 55-8
 of fluid mass, 15-19
 of gravity, 1-2
 resultant, 55-8
 second, 57-10
 tangential, 55-7
 uniform, 55-3, *55-3*
Accelerometer, 58-21
Acceptance, 61-25, 70-3
 plan, 61-25
 quality level, 61-25
Accounting, 69-36
Accreditation Board for Engineering and Technology, 71-1 (ftn)
Accrual system, 69-34
Accumulation, 8-7
Accumulator, 17-32, 19-5
 exponents, 19-6
Accuracy, 11-13, 61-16 (ftn), 62-1
Acetylene gas, 63-11
Acid, 21-8
 carbonic, 21-13, 21-15, 66-41 (ftn)
 gas, 66-4
 rain, 66-5
 -test ratio, 69-35
Acidity, 21-13
AC machine, *67-14*
Acme thread, 52-22
Acoustic
 absorber, 68-8
 barrier, 68-9
 emission testing, 46-11
 holography, 46-11
Acoustical velocity, 14-14, *68-5*
Across-variable, 59-3
Actinide, 21-2
Actinon, 21-2
Action
 capillary, 14-11
 chimney, 22-16
 error in, 52-14
 galvanic, 21-11
 limit, 61-22
 line of, 5-1, 43-2, 52-11
Activated carbon, 66-23
Active
 base, isolation, 58-14
 coil, 52-5
 element, 59-2
 solar system, 31-2
 system, 60-11
 wire length, 52-5
Activity, 61-3
 -on-branch, 61-5
 -on-node, 61-3
Actuator, 19-6, 42-1
Acute angle, 6-1
Addendum, 52-10
Addition
 of vectors, 5-3
 polymerization, 45-15
Adhesion, 14-11 (ftn)
Adhesive bonding, 63-13
Adiabatic
 compressibility, 14-13
 compression, 15-13
 compression efficiency, 32-3
 efficiency, 27-8
 flame temperature, 22-15
 flow with friction, 26-15
 head, 32-5
 process, 25-2
 saturation process, 38-7, 38-10
 tip, 34-17
Adjacent
 angle, 6-2
 side, 6-2
Adjoint, classical, 4-5
Admiralty bronze, 45-12
Admittance, 67-5
Adsorbent, 38-11, 38-12 (ftn), 66-23
Adsorption, 66-23, 66-24
Advanced
 flue gas cleanup, 66-24
 flywheel, 57-3
 oxidation, 66-24
 reactor, 30-2
 scrubbing, 22-5
 turbine system, 29-14 (ftn), 29-17
Advantage
 mechanical, 43-10
 pulley, 43-11
 pulley block, *43-11*
Aeroderivative turbine, 29-14
Aero horsepower, 17-34
Affinity
 law, 18-17
 law, fan, 20-8
Afterburner, 66-34
Aftercooler, 29-10, 32-7
Age hardening, 45-8 (ftn), 45-11, 47-9
Agency, 70-2
Agent, 66-38 (ftn), 70-2
Agglomeration, 64-6
AGMA gear design, 52-14
Agreement, letter of, 70-3
Air
 -and-water system, 42-1
 atmospheric, 22-8, *A-99*
 bypass, recirculating, 41-3
 change method, 39-1
 classification, 64-10
 composition, *22-8*
 conditioner, 33-2
 conditioning load, 41-1
 conditioning process, 38-6
 -cooled exchanger, 36-12
 density ratio, 20-2 (ftn)
 excess, 22-12
 film coefficient, 35-4, *35-5*, *40-3*
 filter, 39-5
 -fuel ratio, 22-9, 22-12, 29-3
 handling unit, 39-6, 42-2
 heater, 27-15
 heater ash, 22-3
 horsepower, 20-4
 moist, 38-2, 38-3
 pollutant, 66-3
 preheater, 27-15
 primary, 27-3
 properties, *A-14*, *A-54*, *A-73*
 refrigeration cycle, 33-6
 resistance, 56-20

Italicized page numbers represent sources of data in tables, figures, and appendices.

- sample, whole, 66-20
- saturated, 38-2
- space, 35-7, 40-3
 - standard Carnot cycle, 29-4
 - standard cycle, 29-2
 - standard diesel cycle, 29-10
 - standard dual cycle, 29-11
 - standard Otto cycle, 29-5
- stripping, 66-38
- table, 24-10
- thermal conductance, *40-3*
- to-cloth ratio, 66-24
- toxic, 66-3
- unsaturated, 38-2
- volume control, 42-1
- washer, 38-2 (ftn), 38-10, 38-11
- Aircraft cable, 64-2
- Airflow, cooling, 36-24
- Airfoil, 17-33
- Alclad, 45-11 (ftn)
- Alcohol, 22-7
- Algebra, 3-1, 4-3
- Algebraic equation, 3-2
- Alias component, 9-7 (ftn)
- Alkali metal, 21-2
- Alkaline
 - earth metal, 21-2
 - fuel cell, 31-8
- Alkalinity, 21-13, *21-14*
 - methyl orange, 21-14
 - phenolphthalein, 21-14
- Alkane, 22-1
- Alkyne, 22-1
- All-air system, 42-1
- Allergen, 66-5
- Allotrope, 47-4
- Allowable stress, 50-1
 - bolt, *53-15*
 - effective, of pressure vessel, 53-9
 - gear, 52-13
 - pressure vessel, 53-4
 - spring, 52-3, *52-4*
 - working pressure, 19-3
- Allowable stress vs. temperature, steel, *53-5*
- Allowance
 - clash, 52-5
 - exposure, 40-1
 - time, 61-16
- Alloy
 - aluminum, 45-11
 - binary, 47-1
 - copper, 45-12
 - miscible, 47-1
 - SAP, 45-19
 - unified numbering system, 45-1
- Alloying ingredients, 47-1
 - cast iron, *45-10*
 - steel, *45-6*
- All-volatile treatment, 21-16
- Alnico, 45-13
- Alphabet, Greek, 3-1, *3-1*
- Alpha-iron, 47-4
- Alternating
 - combined stress, 50-8
 - current, 67-2, 67-4
 - stress, 50-6
- Alternator, 67-10 (ftn)
- Altitude
 - effect on power, 29-13
 - pressure at, 20-2, *20-2*
 - properties at, *A-88*
- Alumina, 45-11
- Aluminum
 - alloy, 45-11
 - bronze, 45-12
 - designations, 45-11, *45-11*
 - hardening of, 47-9
 - heat treatment, *45-12*
 - production of, 45-11
 - properties of, 45-11
 - tempers, *47-9*, 47-10
- Amagat-Leduc's rule, 24-17
- Amagat's law, 24-17
- American Society of Civil Engineers, 71-1
- Amine, 21-15
- Ammonia slip, 66-37 (ftn)
- Amorphous film, 31-4
- Amortization, 69-24
- Ampere, 67-2
- Amperometric sensor, 62-3
- Amplifier, pressure, 32-2
- Amplitude, 58-3, 58-19
- Analogy, electrical/thermal, 34-5, 34-12
- Analysis
 - chemical, 21-6
 - fault-tree, 61-27
 - Fourier, 9-6
 - frequency, 9-7 (ftn)
 - gravimetric, 22-2
 - hazard, 61-27
 - proximate, 22-2
 - sensitivity, 69-43
 - signature, 9-7 (ftn)
 - time-series, 9-7 (ftn)
 - ultimate, 21-4, 21-5, 22-2
 - volumetric, 22-2
- Analytic function, 8-1
- Analyzer
 - FFT, 9-7
 - signal, 9-7
 - spectrum, 9-7
- Andrade's equation, 46-15
- Anechoic room, 68-6
- Anemometer, 17-21
- Angle, 6-2 (*see also type*)
 - between lines, 6-1
 - clearance, 63-2
 - contact, *14-12*
 - convergent, 26-5
 - deviation, 26-11
 - direction, 5-2, 7-5
 - factor, 37-2
 - function of, 6-2
 - helix, 52-12
 - helix thread, 51-13
 - lead, 52-22
 - lift valve, 16-12
 - Mach, 26-11 (ftn)
 - of contact, 14-12
 - of depression, 6-2
 - of elevation, 6-2
 - of internal friction, 46-7, 56-7, 64-4
 - of kinetic friction, 64-5
 - of natural friction, 64-4
 - of natural slope, 64-4
 - of nip, 64-6
 - of obliquity, 52-11
 - of repose, 56-6, 64-4
 - of rupture, 46-7
 - of static friction, 56-6
 - of twist, 46-7, 51-13
 - pitch, 52-14
 - plane, 6-1
 - power, 67-7
 - pressure, 52-11, 52-12, 57-11
 - rake, 63-2
 - relief, 63-2
 - semivertex, 26-11
 - shock, 26-11
 - shock, wedge, *26-11*
 - solid, 6-6
 - thread, 52-22
 - triangular, 6-5
 - valve, 16-11
 - wedge, 63-2
- Angle of repose, *64-4*
- Angles between figures, 7-8
- Angular
 - acceleration, 55-6
 - frequency, 58-3, 67-4
 - impulse, 56-12
 - momentum, 56-3
 - motion, 55-6
 - orientation, 5-1
 - perspective, 2-3
 - position, 55-6
 - velocity, 55-6
- Anisotropic material, 5-1, 34-2 (ftn), 45-19
- Annealing, 47-9
- Annual
 - amount, 69-7
 - cost, 69-7
 - cost method, 69-15
 - return method, 69-15
- Annuity, 69-7
- Annular flow, 36-8
- Annulus gear, 57-5
- Anode, sacrificial, 21-12
- Anodizing, 63-13
- ANSI piping symbols, *A-30*
- Anthracite, 22-4
- Anthropometric data, 61-29
- Anticipation control, 42-2
- Antiderivative, 9-1
- Antoine equation, 14-9 (ftn)
- Apex, 43-22
- Aphelion, 56-19
- API scale, 14-4
- Apogee, 56-19
- Apparatus
 - dew point, 38-8, 41-4
 - Orsat, 22-11
 - sensible heat ratio, 38-6
- Apparent modulus, 46-10

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Application
for exam, 72-2
point of, 5-1
- Approach, 27-14, 36-13, 38-12
point, 29-20
temperature, 36-13
velocity of, 16-4, 17-16
- Approximation
Dunkerley, 58-16
small angle, 6-3
- Approximations, series, 8-8
- Aquation, 21-7
- Aramid fiber, 66-5
- Arc, 61-3
furnace, 45-5
length (by integration), 9-5
welding, 63-12
- Archimedes' principle, 15-14
- Arching, 64-5
- Architect, 70-4
- Area, *A-117*
between two curves, 9-4
by integration, 9-4
centroid, 48-1
daylight, 20-24
density method, 65-6
first moment of, 44-5, 48-2
free, 20-24
irregular, 7-1
logarithmic mean, 34-8
moment of inertia, 48-3, *A-117*
reduction in, 46-6
second moment of, 48-3
sprinkler protection, 65-6
transformation method, 49-19
- Areas, *A-7*
- Areas, law of, 56-18
- Argon-oxygen-decarburization, 45-2 (ftn)
- Argument, 3-8
- Arithmetic
sequence, 3-11
series, 3-11
- Arm, 43-2, 57-5
- Aromatic liquid, 14-9 (ftn)
- Arrangement factor, 37-2, 37-3, 37-3
- Array, 4-1
- Arrest, thermal, 47-2
- Artificial
abrasive, 45-19
aging, 47-9
expense, 69-20
- Asbestos, 66-5
brake lining, 52-16
cement (pipe), 16-10
substitutes, 66-5, *66-6*
- Asbestosis, 66-5
- ASCE (*see* American Society of Civil Engineers)
- "As fired," 22-3
- Ash, 22-3, 66-6
- ASME long-radius nozzle, 17-26 (ftn)
- Aspect ratio, 17-33
duct, 20-14
ellipse, 7-11
- Assembly line balancing, 61-18
- Asset, 69-33, 69-34
- Assignment, 61-12, 70-3
- Associative law
matrix, 4-4
of addition, 3-3
of multiplication, 3-3
sets, 11-2
- Aston process, 45-10
- Asymmetrical function, 7-4
- Asymptote, 7-2
- Asymptotic, 7-2
- Atactic polymer, 45-16
- Atmosphere
composition, *22-8*
of earth, 15-12
standard, 24-5, *A-88*
- Atmospheric
air, 22-8
air properties, *A-14, A-99*
fluidized-bed combustion, 22-5
head, 18-5 (ftn)
pressure, *14-3*
- Atom, 21-1
- Atomic
fraction, 47-1 (ftn)
mass unit, 21-1
number, 21-2, *A-39*
percent, 47-1 (ftn)
structure, 21-1
weight, 21-1, *A-39*
- Attack, intergranular, 21-11
- Attenuator, 27-13
- Attenuation, sound, 68-9
- Attitude, bearing, 52-20
- Attribute chart, 61-22
- Augmented matrix, 4-1
- Austempering, 47-7
- Austenite, 47-5
- Austenitic stainless steel, 21-11 (ftn), 45-8
- Austenitizing, 47-7
- Autogenous
grinding, 64-7
waste, 66-28 (ftn)
- Autoignition temperature, 22-8
- Auxiliary
equation, 10-1
view, 2-2
- Availability, 25-11, 61-9
- Available
draft, 22-16
hydrogen, 22-3, 22-14
methods, 66-17
- Average
outgoing quality limit, 61-26
power, 67-7
pressure, 15-6
run length, 61-22
speed, 24-17
time-weighted, 39-5
value, 9-4, 67-5
velocity, 16-8
- Avogadro's
hypothesis, 21-4
law, 24-13
number, 21-4
- A-Weighting, octave band, 68-7
- Axial
-centrifugal compressor, 32-1
exhaust, 29-14
-flow compressor, 32-1
-flow fan, 20-3
-flow impeller, 18-4, 64-12
-flow turbine, 18-23
loading, 49-11
member, 43-11
pitch, 52-12
strain, 46-4
- Axis
conjugate, 7-11
neutral, 49-10
oblique, 2-2
parabolic, 7-10
principal, 48-7, 54-2
rotation, 48-7
- Axonometric view, 2-3
- B**
- Babcock formula, 17-9
- Backfitting, 27-16
- Backflush, thermal, 27-12
- Background noise, 68-3
- Backing strip, 53-7
- Back
pressure, 27-11
pressure critical ratio, 26-12, 26-13
work ratio, 29-17
- Backlash, 52-11
- Backpressure turbine, 27-8
- Backward-curved fan, 20-4
- Baffle, 36-13
- Baghouse, 66-24
- Bainite, 47-7
- Bakelite, 45-15 (ftn)
- Balance
delay, 61-18
sheet, 69-34
- Balanced
draft, 22-16
draft point, 66-28
electrical load, 67-9
- Balancing, 54-2, 58-18
chemical equations, 21-6
duct, 20-18
line, 61-18
- Ballast circuit, 40-4, 62-9
- Balling scale, 14-4 (ftn)
- Ballistic pendulum, 56-3
- Balloon payment, 69-41
- Ball valve, 16-11
- Band
brake, 52-18
dead, 42-5
octave, *68-7*
sound, 68-6, 68-7
- Bandwidth, 60-10
classification, 64-11
of frequency analysis, 9-8
- Banking, roadway, 56-21
- Barlow formula, 19-3
- Barometer, 15-2, 15-5

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Barometric
 height relationship, 15-12
 pressure, 14-3
- Barrel finishing, 63-14
- Barrier, sound, 68-9
- Barth speed factor, 52-13
- Base, 12-1, 21-8
 -8 system, 12-2
 -10 number, 12-1
 -16 system, 12-2
 -*b* number, 12-1
 circle, 52-10, 57-11
 exchange, 21-14
 metal, 47-1
 of riser, 65-14
 pitch, 52-10
 unit, 1-5
 units, SI, *1-5*
 wage, 61-20
- Baseline rate, 67-7
- Base-load unit, 27-16
- Basic Motion Time Study, 61-16 (ftn)
- Basis, depreciation, 69-20
- Bathtub distribution, 11-7
- Battery, 31-10 (*see also type*)
- Baumé scale, 14-5
- Bauxite, 45-11
- Bayer process, 45-11
- BDC (*see* Bottom-dead-center)
- Beam
 -column, 49-11
 conjugate, 49-15
 continuous, 44-5
 curved, 49-19, *49-19*
 deflection, 49-13 to 49-16, *A-118-A-120*
 fixed-end, 44-1, 44-6
 indeterminate, 44-1
 shear stress, 49-9
 vibration, *58-19*
 wide, 49-16, 52-9
- Bearing, 51-10
 characteristic number, 52-22
 journal, 52-20, *52-21*
 journal correlation, *A-124*
 stiffener, 49-18
- Bed
 chemically active, 66-29
 moisture level, 22-3
 packed, 36-10
 residence time, 66-25
- Behavior science, 61-27
- Bell-shaped curve, 11-6
- Belt
 conveyor, 64-7
 elevator, 64-9
 feeder, 64-6
 flat, 52-15
 friction, 56-7
 tension, effective, 64-8
 V-, 52-16
- Beltline, reactor, 30-2
- Bending
 moment diagram, 49-8
 stress, beam, 49-10
 stress number, 52-14
- Benefit-cost ratio, 69-16
- Bent-tube boiler, 27-4
- Benzoyl peroxide, 45-15 (ftn)
- Bernoulli equation, 16-2, 17-14
- Beryllium, 45-12
- Bessel equation, 10-5
- Bessemer process, 45-3
- Best available technology, 66-21
- Beta
 distribution, 61-5
 -iron, 47-4
 ratio, 17-23
- Betz coefficient, 31-5
- Bevel gear, 52-14, 57-9
- Bias, 11-13, 62-2
- Biaxial stress, 49-5, 50-1
- Bidding, competitive, 71-3
- Bifunctionality, 45-15
- Billet, 45-10 (ftn), 63-13
- Billion, 1-7 (tbl)
- Bin, 27-3, 64-5 (*see also type*)
- Binary
 alloy, 47-1
 cycle, 28-7, 31-7
 digit, 12-1
 number system, 12-1
- Binder, 64-7
- Binding, 27-14
- Bingham
 fluid, 14-7
 plastic model, 17-11
- Binomial
 coefficient, 11-2
 distribution, 11-4
 theorem, 3-3
- Biocide, 27-12, 66-40 (ftn)
- Biofilter, 66-25
- Bioreactor, 66-25
- Bioremediation, 66-25
- Biosolid, 66-3 (ftn)
- Biostat, 66-40 (ftn)
- Biot number, *1-9*, 34-4, 34-13
- Bioventing, 66-25
- Birmingham water gage tubing, *A-28*
- Birmingham wire gage tubing, *A-103*
- Bisection method, 3-4, 13-1
- Bit, 12-1, 12-4
- Bituminous coal, 22-4
- Black body, 37-1
- Black steel pipe, 16-10
- Blade
 jet force on, 17-29
 pitch control, 20-3
- Blanking, 63-7
- Blasius
 equation, 17-5
 solution, 17-38, 36-4
- Blast
 furnace, 45-1
 gas, 22-7 (ftn)
 gate, 20-18
 governing, 27-16
- Bleed, 27-8
 fraction, 27-14
 -off, 38-13
 rate, 27-8
- Block
 and tackle, 43-11
- brake, 52-17
 diagram, 60-5, *60-6*
- Bloom, 45-10 (ftn)
- Blow, 20-24
 molding, 63-10
 -off, flame, 27-3
 -out, gasket, 53-14
 -tank system, 64-6
- Blowdown, 21-15, 27-5, 38-13, 66-9
- Blower, 32-1
- Blower power, 20-4
- Blowing the whistle, 71-3 (ftn)
- Blowoff, 27-5
- Blue
 center steel, 64-2
 embrittlement, 47-9
- Board
 hammer, 63-7
 of directors, 70-2
 of engineering licensing, 72-1
- Boardman formula, 19-3
- Bode plot, 60-11
- Body
 black, 37-1
 -centered tetragonal, 47-7 (ftn)
 gray, 37-2, 37-3
- Boiler, 27-4 (*see also type*)
 and Pressure Vessel Code, 53-1
 efficiency, 22-16, 27-4
 feedwater characteristics, 21-15
 feedwater quality, 21-11
 horsepower, 22-16, 27-4
 throttle valve, 27-16
 tubing, steel, *A-28*
 once-through, 27-1
 waste-heat, 29-20
- Boilerplate clause, 70-3
- Boiling, 14-9
 film, 35-10
 nucleate, 35-10
 -point margin, 66-10
 pool, 35-10
 water reactor, 30-2
- Bolt, 51-8
 allowable stress, *53-15*
 dimension, *51-10*
 family, 51-8
 grade, 51-8
 grade and type, *51-9*
 marking, 51-9
 preload, 51-11
 standards, 51-8
 strength, pressure vessel, 53-15
 stress concentration, 51-12
 torque, 51-12
- Boltzmann constant, 24-16
- Bomb calorimeter, 22-14
- Bond, 69-29
 fully amortized, 69-29 (ftn)
 yield, 69-30
- Bonded strain gage, 62-8
- Bonding, adhesive, 63-13
- Bonus, 61-20
- Bookkeeping, 69-33
- Book value, 69-23

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Boom, sonic, 14-14
 Booster, 32-2
 Booster humidification, 39-3
 Boost, fan, 22-16
 Bore, 29-2
 Bottleneck, 61-18
 Bottom
 ash, 22-3, 66-6
 -dead-center, 29-2, 32-3 (ftn)
 Bottoming cycle, 29-21
 Bound
 lower, 9-4
 upper, 9-4
 vector, 5-1 (ftn)
 Boundary
 irregular, 7-1
 layer, 16-8, 17-37, 36-2
 system, 25-1
 value, 10-2
 Bourdon pressure gauge, 15-2
 Box, closed, 51-14
 Boyle's law, 25-7
 Braced column, 51-2
 Brake, 52-16, 63-6
 band, 52-18
 block, 52-17
 dynamometer, 62-12
 energy dissipation, 52-16
 external shoe, 52-17
 lining, 52-16
 material, 52-17
 pad, 52-16
 power, 20-4, 29-3, 29-4, 56-20
 properties, 29-3
 pump power, 18-7
 specific fuel consumption, 29-3
 torque, 29-4
 prony, 29-3
 Braking torque, 52-18
 Brale indenter, 46-12
 Branch
 line, 65-2
 loss coefficient, 20-16, 20-16
 takeoff, 20-16
 Branching, 45-16
 Brass, 16-10, 45-12 (ftn)
 tubing, dimensions, A-27
 Brayton
 cooling cycle, 33-6
 cycle, 29-15, 29-18, 29-19
 Brazing, 63-12
 Breach of contract, 70-5
 Breakaway point, 60-12
 Break-even point, 69-37
 Breaking strength, 46-3
 Breakpoint, 66-23
 Breakthrough, 66-23
 Breeder reactor, 30-1 (ftn)
 Breeze, 22-5
 Brickwork, 27-4
 Bridge
 constant, 62-10
 truss, 43-12
 Wheatstone, 62-9
 Bridging, 64-5
 Brightness, 68-2, 68-3
 Brinell hardness, 46-12
 Briquetting, 64-6
 British thermal unit, 23-1, 24-5
 Brittle
 failure, 46-13
 material, 46-16, 50-1, 50-2
 Brix scale, 14-4 (ftn)
 Broad band measurements, 68-7
 Bromley equation, 35-11
 Bronze
 government, 45-12
 type, 45-12
 Btu (*see* British thermal unit)
 Bubbling fluidized-bed combustor, 66-27
 Bucket elevator, 64-9
 Buckingham equation, 52-14 (ftn)
 Buckling, 51-1
 beam, 49-18
 spring, 52-7, 52-8
 Buffer, 21-9
 Buffing, 63-14
 Building
 designer, 70-4
 material, properties, A-111
 -related illness, 66-5
 Built
 -in end beam, 44-6
 -up edge, 63-2 (ftn)
 Bulk
 material, 64-4
 modulus, 14-13, 46-8, 68-4
 modulus, solids, 46-8
 modulus, water, 14-13
 solid, 64-5
 storage pile, 64-4
 temperature, 34-4, 35-3, 36-2, 36-3
 velocity, 16-8
 Bundle, tube, 36-9
 Bunker C oil, 22-5
 Buoyancy, 15-14, 15-16
 Burden, 69-36
 Burning rate, municipal solid waste, 66-32
 Burnishing, 63-14
 Burnout velocity, 56-17
 Burst
 pressure, 19-3
 velocity, 57-3
 Bushing, 52-19
 Business property, 69-20 (ftn)
 Butterfly valve, 16-11
 BWG, tubing, A-103
 BWG tubing, dimensions, A-28
 Byers-Aston process, 45-10
 Bypass
 factor, 38-7, 41-4
 governing, 27-16
 recirculating air, 41-3
C
 Cabinet projection, 2-3
 Cable, 43-17 to 43-20
 catenary, 43-19
 hoisting, 64-1
 parabolic, 43-17
 tension, 56-11
 CaCO₃ equivalent, 21-13, A-41, A-42
 Calculus, fundamental theorem of, 9-4
 Calibration, 62-2
 Calorimeter, bomb, 22-14
 Calorizing, 63-14
 Cal sil, 34-9
 Cam, 57-10
 dynamics, 57-12
 Candlepower, 68-3
 Canon, 71-1
 Canonical form, row, 4-2
 Capacitance, 67-5
 fluid, 59-7
 thermal, 34-12
 Capacitive reactance, 67-5
 Capacitor, 67-5
 Capacity
 compressor, 32-2
 control, 20-3
 factor, 27-15
 heat, 24-7
 rate, thermal, 36-20
 refrigeration, 33-3
 specific, battery, 31-10
 turndown, 27-13
 Capillary
 action, 14-11
 -action heat pipe, 34-22
 Capitalized cost, 69-7, 69-15
 Capitalizing an asset, 69-20
 Capital recovery method, 69-15
 Carbide, 45-19, 47-5, 63-4
 Carbon
 dioxide buildup, 39-3
 dioxide emission, 66-6
 fixed, 22-4
 fraction, 66-7
 granular activated, 66-23
 monoxide emission, 66-8
 production, 66-14
 steel, 45-5
 temper, 45-10
 Carbonate
 fuel cell, 31-8
 hardness, 21-14
 Carbonic acid, 21-13, 21-15, 66-41 (ftn)
 Carborundum, 45-19
 Carburetor, 29-2
 Carburizing, 47-10, 63-12
 Carcinogen, 61-27
 Card, indicator, 29-8
 Carnot cycle, 25-10 (ftn), 25-11, 28-2
 air-standard, 29-4
 refrigeration, 33-3
 Carrier
 arm, 57-5
 equation, 38-2
 slurry, 17-11
 Cartesian
 coordinate system, 7-3
 equation form, 3-3 (ftn)
 triad, 5-2
 unit vector, 5-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Cash
 flow, 69-3, 69-6
 diagram, *A-137*
 system, 69-34
- Casing transducer, 58-21
- Casting
 die, 63-9
 type, 63-8, 63-9
- Cast iron, 45-9, *45-9*, *45-10*, 47-4, 47-5 (*see also type*)
 alloying ingredients, *45-10*
 heat treating, 47-8
 pipe, 16-10
- Catalytic
 converter, 29-2
 cracking, 22-3
 reduction, selective, 66-37
- Catenary cable, 43-19
- Cauchy
 equation, 10-5
 number, 1-9 (tbl)
 -Schwartz theorem, 5-3
- Caustic
 embrittlement, 21-11
 phosphate treatment, 21-16
- Cavalier projection, 2-3
- Caveat emptor, 70-6
- Cavitation, 18-13, 18-14
 coefficient, 18-14
 corrosion, 21-12
- c*-chart, 61-22, 61-24
- Ceiling
 heat transfer, 40-2
 thermal coefficient, *40-2*
- Cell
 fuel, 31-7
 landfill, 66-12
 photovoltaic, 31-4
 solar, 31-4
- Cellular fill, 38-11 (ftn)
- Cement, asbestos (pipe), 16-10
- Cementation, 47-10
- Cemented carbide, 45-19
- Cementite, 47-5
- Center, 7-2
 distance, 52-11
 instant, 55-12, 55-13
 of buoyancy, 15-16
 of force, 56-17
 of gravity, 9-6, 54-1
 of mass, 54-1
 of pressure, 15-4, 15-9, 15-10 (fig), 43-5
 of vision, 2-3
 -radius form, 7-9
- Centerless grinding, 63-5
- Centerline velocity, 16-8
- Centigrade, 24-5 (ftn)
- Centipoise, 14-7
- Centistoke, 14-8
- Central
 force field, 56-17
 impact, 56-16
 limit theorem, 11-11
 receiver system, 31-3
 system, 27-3
 tendency, 11-10
 view, 2-2
- Centrifugal
 casting, 63-9
 fan, 20-3
 force, 56-5
 pump, 18-2, 18-4
- Centripetal
 acceleration, 15-19 (ftn)
 force, 56-5
- Centroid, 9-6, *A-117*
 area, 48-1
 line, 48-2
 of volume, 54-1
- Centroidal
 mass moment of inertia, 54-2
 moment of inertia, 48-3
- Ceramic, 45-17, *45-18*, *45-19*
 adhesive, 63-13 (ftn)
 tool, 63-4
 toughened, 45-19
- Cermet, 45-19
- Cetane number, 22-7
- CFC replacement, *66-8*
- cgs system, 1-4
- Challenger, 69-18
- Chamber
 checker, 45-4
 property, 26-2
- Change, allotropic, 47-4
- Channeling, 66-39
- Chaos theory, 62-2 (ftn)
- Chaotic error, 62-2
- Char, 22-5
- Characteristic
 curve
 compressor, 32-8
 fan, 20-5
 system, 20-7
 dimension, 16-6, 34-3
 equation, 4-7, 10-1, 60-4, 60-12
 exhaust velocity, 26-9
 length, 26-9, 34-3, 35-2, 36-8
 log, 3-5
 number, bearing, 52-22
 polynomial, 4-7
 specific feed, 66-29
- Characteristics
 of metals, 45-1
 phase, 60-11
 polyphase motor, *A-133*
- Charcoal, activated, 66-23
- Charge
 electric, 67-2
 number, *21-3*
- Charles' law, 25-7
- Charpy test, 46-13
- Chart (*see also type*)
 control, 11-13, 61-22
 Cox, 14-9
 Heisler, 34-13, *A-95-A-97*
 Mollier, *A-53*, *A-72*
 pressure-enthalpy, 24-11
 psychrometric, 38-3
 time-temperature, 34-13
- Checker chamber, 45-4
- Check valve, 16-12
- Chelant, 21-16, 66-38 (ftn)
- Chelate, 66-38 (ftn)
- Chelating agent, 66-38 (ftn)
- Chemical
 dehumidification, 38-11
 dehydration, 38-11
 equations, balancing, 21-6
 loading, 66-41
 milling, 63-6
 reaction, 21-5
 scrubbing, 66-37
- Chemically active bed, 66-29
- Chiller, 33-2, 33-9
- Chimney, 22-16
- Chip
 -breaker groove, 63-2
 forming, 63-1
 temperature, 63-4
 thickness ratio, 63-2
 type, 63-1
 velocity, 63-2
- Chloride stress corrosion, 45-9
- Chlorination, 66-9
- Chlorine, 27-12, 66-26
- Chlorofluorocarbon, 66-8
- Choked flow, 26-4
- Choke point, 32-8
- Chord, 17-33, 43-12
- Chrysotile-asbestos brake lining, 52-16
- Churn head, pump, 18-15, 65-3
- Circle, 7-9
 base, 52-10
 clearance, 52-10
 Mohr's, 48-7, 49-6
 pitch, 52-10
 unit, 6-1
- Circular
 fin, 34-18
 mil, 67-2
 motion, 55-6
 permutation, 5-5
 pipe, *A-21*
 pitch, 52-10
 shaft, design, 51-13
 transcendental function, 6-2
- Circulating
 closed-loop system, 65-2
 fluidized-bed boiler, 66-28
- Circulation, 8-7 (ftn), 17-33, 29-20
- Circumferential
 strain, 51-5
 stress, 51-3, 51-4
- Cis form, 3-8
- Civil
 complaint, 70-5
 tort, 70-5 (ftn)
- Cladding, 63-11
- Clash allowance, 52-5
- Class
 limits, 11-9
 property, bolt, 51-9
 sound transmission, 68-9
- Classical adjoint, 4-5

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Claude cycle, 31-6 (ftn)
 Clausius-Clapeyron equation, 14-9 (ftn)
 Clay, vitrified (pipe), 16-10
 Cleanliness factor, 27-11
 Clean room, 39-5
 Clearance, 52-10
 angle, 63-2
 circle, 52-10
 diametral, 52-20
 percent, 32-3
 radial, 52-20
 volume, 29-2, 32-3
 Client (dealing with), 71-2
 Clinker, 22-3
 Clinographic projection, 2-3
 Clock spring, 52-9 (ftn)
 Closed
 box, 51-14
 combustor, 29-16
 -cycle OTEC, 31-6
 die forging, 63-7
 feedwater heater, 27-14, 36-14 (ftn)
 -loop gain, 60-4
 -loop recovery, 66-23
 system, 25-1
 turbine cycle, 29-15
 Closely held corporation, 70-2
 Cloud point, 22-7
 Clutch, 52-16, 52-19
 material, 52-17
 CO₂ fraction, 66-7
 CO₂ production, 66-14
 Coal, 22-4
 ash, 22-3
 blending, 66-18
 cleaning, 22-5
 dry ultrafine, 66-10
 -fueled turbine, 29-15
 micronized, 22-5, 27-3 (ftn)
 properties, 22-5
 substitution, 66-18
 upgrading, 22-5
 -water mixture, 29-15
 Coalescence, 63-9
 Coarsening temperature, 47-8
 Cocurrent
 -crossflow, 36-11
 flow, 36-10
 Code, 71-1
 Coefficient
 absorption, 21-7, *A-135*
 Betz, 31-5
 binomial, 11-2
 branch loss, 20-16, *20-16*
 cavitation, 18-14
 confidence, 61-16
 correlation, 11-13
 discharge, venturi, *17-24*
 drag, 17-34, 36-4 (ftn)
 end restraint, 51-2, *51-2*
 film, 34-6, 35-2
 air, *35-5, 40-3*
 evaporization, water, *35-11*
 fitting loss, air, *20-15*
 flow, 17-13, 17-24
 flow, orifice plate, *17-25*
 fluid resistance, 59-7
 friction, *56-7*
 Joule-Kelvin, 25-3
 Joule-Thompson, 25-3
 loss, 17-12, *17-12*, 20-14
 mass-transfer, 66-40
 matrix, 4-6
 noise reduction, 68-8, *A-135*
 nozzle, 26-8
 orifice, *17-17*
 of compressibility, 14-12
 of contraction, 17-16, 17-24
 of discharge, 17-17, 17-24
 of drag, *17-35, 17-36*
 of entry, 20-15
 of entry, air, *20-15*
 of expansion, thermal, 14-12 (ftn)
 of flow, 17-13, 17-24, 26-15
 of fluctuation, 57-2
 of forced convection, 36-2
 of friction, 15-12, 56-6
 of heat transfer, *36-15, 40-2*
 of lift, 17-32
 of linear expansion, 49-3
 of performance, 33-2
 of restitution, 56-15
 of rolling friction, 56-8
 of rolling resistance, 56-7, 56-19
 of the instrument, 17-22
 of thermal expansion, *49-4, 66-36*
 of thermal resistance, *62-6*
 of thrust, 26-8
 of transformation, 5-2
 of variation, 11-11, 61-16
 of velocity, 17-16, 17-23
 of viscosity, 14-6
 of viscous damping, 56-17, 58-9
 of volumetric expansion, 49-3
 overall heat transfer, 34-6, 36-15
 power, 31-5
 power, wind, *31-6*
 profile drag, 36-4 (ftn)
 radiant heat transfer, 37-4
 roughness, 17-7
 Seebeck, 31-9
 shading, 41-2
 skin friction, 17-38, 36-4
 slab edge, 40-3
 smoothing, 69-42
 sound absorption, 68-8
 static regain, 20-16
 strength, 46-5
 torque, 51-12
 transmission, 68-9
 valve flow, 17-13
 virial, 24-19
 Coefficients, method of undetermined, 10-4
 Cofactor
 matrix, 4-1
 of entry, 4-2
 Co-firing, 66-33
 Cogeneration cycle, 29-21
 Cogenerators, 21-2
 Coherent unit system, 1-2
 Cohesion, 14-11 (ftn), 46-7
 Coil, 36-6
 active, 52-5
 efficiency, 38-7
 of film coefficient, 35-7
 load, 41-1 (ftn)
 load line, 38-8
 pitch, 52-5
 sensible heat ratio, 38-6, 41-4
 Coining, 63-7
 Coke, 22-5, 22-7 (ftn), 45-2 (ftn)
 Colburn equation, 36-9
 Cold
 air-standard cycle, 29-2 (ftn)
 -end drive, 29-14
 flow, 46-15
 heading, 63-7
 reserve, 27-15
 -working, 47-9, 63-6 (tbl), *63-7*
 Colebrook equation, 17-5
 Collapse, duct, 20-18
 Collapsing pressure, 51-3 (ftn)
 Collector
 concentrating, 31-2
 dust, 39-5
 efficiency, 31-2
 evacuated tube, 31-2
 flat plate, 31-2
 focusing, 31-2
 solar, 31-2
 Collinear, 7-2, 43-6
 Collision, 56-15
 Colloid, 66-41
 Column
 braced, 51-2
 end coefficient, *51-2*
 intermediate, 51-3
 matrix, 4-1
 rank, 4-5 (ftn)
 slender, 51-1
 Combination, 11-2
 direct, 21-6
 method, 20-21
 Combined
 ash, 66-6
 cycle, 29-22
 diesel or gas turbine system, 29-10 (ftn)
 film coefficient, 34-17
 heat transfer coefficient, 37-4
 stress, 49-5, 51-13
 Combining weight, 21-5
 Combustible loss, 22-15
 Combustion
 complete, 22-12
 data, *22-10*
 efficiency, 22-16
 fluidized-bed, 22-5
 heat of, 22-14, *A-43*
 incomplete, 22-11
 loss, 22-15
 reaction, 22-8, *22-9*
 staged, 66-38
 stoichiometric, 22-9
 stratified charge, 29-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- temperature, 22-15
- turbine, 29-14
- Combustor, 29-12, 29-14, 29-16, 66-27
- Comfort range, 39-2
- Comity, 72-2
- Command, 60-13
- Commercial bronze, 45-12 (ftn)
- Comminution, 64-7
- Common
 - glass, 45-17
 - ratio, 3-11
- Commutative law
 - matrix, 4-4
 - of addition, 3-3
 - of multiplication, 3-3
 - sets of, 11-2
- Compaction, 64-6
- Comparative negligence, 70-5
- Comparator, 60-4
- Comparison test, 3-12
- Compatibility method, 44-2
- Compensatory
 - damages, 70-7
 - fraud, 70-6
- Competitive bidding, 71-3
- Complaint, 70-5
- Complement
 - nines, 12-3
 - number, 12-3
 - ones, 12-3
 - set, 11-1
 - tens, 12-3
 - twos, 12-3
- Complementary
 - angle, 6-2
 - equation, 10-1
 - probability, 11-4
 - solution, 10-4, 58-10
- Complete combustion, 22-12
- Completion time, 61-5
- Complex
 - conjugate, 3-8
 - matrix, 4-1
 - number, 3-1, 3-7
 - number operations, 3-8
 - plane, 3-7
 - power, 67-6
- Component
 - alias, 9-7 (ftn)
 - linear, 58-2
 - moment, 43-3
 - steady-state, 58-11
 - transient, 58-11
- Components of a vector, 5-2
- Composite
 - complex wall, 34-6, 34-7
 - cylinder, 34-8
 - material, 45-19, 45-20
 - material, flywheel, 57-4
 - spring constant, 52-2
 - structure, 49-19
- Composition, eutectic, 47-3
- Compound, 21-3
 - amount factor, 69-5
 - gear, 57-4
 - interest, 69-11
 - volatile organic, 66-25
- Compounding
 - factor, 69-7
 - period, 69-28
- Compressed
 - air energy storage, 31-9 (ftn)
 - air storage tank, 32-2
 - height, 52-5
 - water, properties, A-51, A-70
- Compressibility, 14-1, 14-12, 14-13, 24-9
 - adiabatic, 14-13
 - coefficient of, 14-12
 - factor, 14-12 (ftn), 24-19, A-83
 - isentropic, 14-13
 - isothermal, 14-13
- Compressible
 - flow through orifice, 26-15
 - fluid dynamics, 26-1
 - fluid, flow of, 17-26
- Compressions
 - adiabatic, 15-13
 - cycle, vapor, 33-3
 - efficiency, adiabatic, 32-3
 - ignition, 29-2
 - isothermal, 15-12
 - polytropic, 15-13
 - ratio, 29-3, 29-5, 29-11, 32-4 (ftn)
 - ratio, isentropic, 29-4
 - spring, helical, 52-4, 52-6
 - stage, 32-1
 - stroke, 29-2
 - wave, 68-4
- Compressive strength, 46-7
- Compressor, 32-1 (*see also type*)
 - air/gas, 32-1
 - capacity, 32-2
 - characteristic curve, 32-8
 - control, 32-2
 - scroll, 33-7
 - work, 32-4
- Concave, 7-2
- Concavity, 7-2
- Concentrated force, 43-2
- Concentrating collector, 31-2
- Concentration
 - cell corrosion, 21-11
 - factor, stress, A-121
 - ionic, 21-8
 - stress, 49-4, 51-7
 - tower buildup, 38-13
- Concentric
 - cylinder viscometer, 14-6 (ftn)
 - flywheel system, 57-4
 - loading, 49-11
- Concrete
 - density, 15-11 (ftn)
 - pipe, 16-10
- Concurrent force, 43-6
- Condensate
 - depression, 27-11
 - polishing, 21-16
 - well, 27-11
- Condensation
 - dropwise, 35-8
 - filmwise, 35-8
 - polymerization, 45-15
 - Reynolds number, 35-9
 - vapor, 35-7 to 35-9
- Condenser, 27-11, 33-1 (*see also type*)
 - cooling water, 66-9
 - duty, 27-11
 - hot well subcooling, 27-11
- Condensing
 - cycle, 28-2
 - vapor, film, 35-7
- Condition
 - initial, 58-4
 - line, turbine, 27-8
 - standard, 22-2
- Conditional
 - convergence, 3-12
 - probability, 11-4
 - probability of failure, 11-7
- Conditioner, sludge, 21-16
- Conditions of equilibrium, 43-6
- Conditions, standard, 14-4
- Conductance, 34-2, 67-2, 67-5
 - overall, 36-15
 - thermal, 40-2
 - thermal, air space, 40-3
- Conduction, 34-2
- Conductive, unit, 34-6
- Conductivity, 67-2
 - overall, 34-6
 - thermal, 34-2, 34-3, 36-16, A-89
- Cone
 - clutch, 52-19
 - pitch, 52-14
- Confidence
 - coefficient, 61-16
 - interval, 61-16 (ftn)
 - level, 11-11, 61-16
 - level z -values, 11-12
 - limit, 11-11
- Configuration factor, 37-2
- Congruency, 7-3
- Conical pile, 64-4
- Conic section, 7-8, 7-9
- Conjugate
 - axis, 7-11
 - beam, 49-15
 - complex, 3-8
- Connection
 - bolt, 51-10
 - eccentric, 51-16, 51-17
- Consequential damages, 70-7
- Conservation
 - law, radiation, 37-1
 - methods, heat, 40-6
 - of energy, 58-5
 - of momentum, 17-27, 56-3
- Consideration, 70-3
- Consistent
 - deformation method, 44-2, 49-19
 - system, 3-7
 - unit system, 1-2
- Constant
 - Boltzmann, 24-16
 - bridge, 62-10

Italicized page numbers represent sources of data in tables, figures, and appendices.

- coefficients, 10-1 to 10-3
 elastic relationships, 46-8
 Euler's, 9-8 (ftn)
 gravitational, 1-2, *56-18*
 Hazen-Williams, *A-31*
 sprinkler, *65-7*
 Henry's law, 21-7, *66-39*
 Joule's, 23-1, 24-6
 matrix, 4-6
 Newton's gravitation, 56-18
 of integration, 9-1, 10-1
 outlet, 20-25
 percentage method, 69-21 (ftn)
 pressure process, 25-2, 25-7
 reaction rate, 66-25
 room, 68-8
 solar, 31-1, 37-7
 -speed control, 60-13
 spring, 49-2, 52-2
 sprinkler orifice, 65-5
 Stefan-Boltzmann, 37-2
 temperature process, 25-2, 25-8
 thermoelectric, 62-7, *A-130*
 time, 34-12
 torsional spring, 58-5
 universal gas, *24-14*
 volume process, 25-2, 25-8
- Constants
 elastic, *46-8*
 fundamental, inside front cover
- Constrained motion, 56-9
- Constraint, 61-2, 61-12
- Construction contract, 70-3 (ftn)
- Construction manager, 70-4
- Consulting engineer, 72-1
- Contact
 angle, 14-12, *14-12*
 factor, 38-8
 ratio, 52-11
 resistance, 34-6 (ftn)
- Content, moisture, 24-9
- Continuity equation, 17-2
- Continuous
 beam, 44-1, 44-5
 bucket elevator, 64-9
 compounding, 69-28
 distribution function, 11-5
 duty rating, 29-4
 emissions monitoring, 66-21
- Contract, 70-2
 breach of, 70-5
 documents, 70-3 (ftn)
 discharge of, 70-5
 privity, 70-6
 requirement for, 70-2
 standard, 70-4
- Contraction, 17-12, 17-13, 17-16, 17-24
- Contractor, 70-4
- Contraflexure, point of, 7-2, 8-2, 49-16
- Control (*see also type*)
 blade pitch, 20-3
 capacity, 20-3
 chart, 11-13, 61-22
 chart factor, quality, *61-23*, *61-24*
 compressor, 32-2
 differential, 42-2
 element, 60-13
 limit, 61-22, 61-23
 mass, 25-1
 mechanism, 60-14
 of heat exchange operations, 36-23
 of turbine, 27-16
 point, 42-2, 61-25
 ratio, 60-4
 surface, 25-1
 system, 60-13
 tachometer, 60-13
 valve, hydraulic, 19-2
 velocity, 39-4
 velocity, hood, *39-4*
 volume, 25-1
- Controllability, 60-14
- Controllable pitch, 20-3
- Controlled
 -circulation boiler, 27-4
 -cooling transformation curve, 47-6
- Controller, 60-13
- Convection
 forced, 36-2
 natural/free, 35-2
 Newton's law of, 36-2
 preheater, 27-15
 superheater, 27-12
- Convective heat transfer coefficient, 34-6
- Convention
 half-year, 69-3
 sign, thermal, 25-4
 year-end, 69-3
- Conventional duct system, 20-17
- Convergence, 3-11, 3-12
- Convergent
 angle, 26-5
 -divergent nozzle, 26-5
 sequence, 3-10
 series, 3-11
- Converging-diverging nozzle, 17-23
- Conversion
 base, 12-3
 factors, *A-1-A-6*, inside front cover
 power, 23-5 (tbl)
 viscosity, *14-8*, *A-19*
- Converter, 29-2, 45-3
- Convex, 7-2
 hull, 7-2, 7-3
 polygon, 61-12
- Convexity, 7-3
- Conveyor
 belt, 64-7
 pneumatic, 64-6
 screw, 64-5
 submerged scraper, 66-6
- Convolution integral, 10-7
- Cooler, 33-9
- Cooling
 coil, 33-8
 compressor, 32-7
 degree day, 41-2
 duty, 38-12
 efficiency, tower, 38-12
 electronic enclosures, 36-23
 evaporative, 38-7, 38-10
 load, 41-1
 load factor, 41-2
 Newton's law of, 10-10
 sensible, 38-8
 tower, 38-11, 38-13
 tower blowdown, 66-9
 water, 36-14
 with dehumidification, 38-8
 with humidification, 38-8
- Coordinate
 holonomic, 55-2
 system, 7-3
- Coordinates of fluid steam, 17-17
- Coplanar, 7-2, 43-6
- Copolymer, 45-13
- Copper
 alloy, 45-12
 -beryllium, 45-12
 loss, 67-15
 pipe, 16-10
 production, 45-12
 tubing, 16-10
 tubing, dimensions, *A-26*, *A-27*
- Core, 49-12, 62-4 (ftn), 63-8
 loss, 67-15
 wire rope, 64-2
- Coriolis acceleration, 55-8
- Corner frequency, 60-10
- Corona wire, 66-27
- Corporation, 70-2
- Corrected fin length, 34-18
- Correction factor, LMTD, 36-14, *A-101*
- Correlation
 coefficient, 11-13
 film, 35-3
 hardness, *46-14*
 journal bearing, *A-124*
 Othmer, 14-11
 Seider-Tate, 36-5, 36-6
 tube-wire, *35-7*
- Corresponding state, 24-19
- Corrosion, 21-10
 cavitation, 21-12
 chloride, 45-9
 concentration cell, 21-11
 cracking, intergranular stress, 30-2
 cracking, stress, 45-9
 crevice, 21-11
 erosion, 21-11
 fatigue, 21-12
 fretting, 21-12
 galvanic, 21-11
 intergranular, 21-10
 microbiologically influenced, 27-12
 pressure vessel, 53-7
 -resistant steel, 45-5
 stress, 21-12
 two-metal, 21-11
- Corrosive substance, 66-3
- Cosine
 direction, 5-2, 7-5, 43-2
 function, integral, 9-8
- Cosines, law of, 6-5, 6-6

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Cost, 61-2 (ftn), 69-31 (*see also type*)
 accounting, 69-36
 capitalized, 69-7
 electricity, 18-8
 of goods sold, 69-37
 opportunity, 69-18
 plus fee, 70-4
 standard, 61-15
 sunk, 69-3
- Couette flow, 36-3 (ftn)
- Coulomb, 67-2
 friction, 56-5
 -Mohr theory, 50-2
- Counterblow forging, 63-8
- Counter-crossflow, 36-11
- Countercurrent flow, 36-10
- Counterflow, 36-10
- Couple, 43-4, 43-9
- Coupon rate, 69-30
- Cox chart, 14-9
- CPM (*see* Critical path method)
- Crack
 coefficient, 39-2
 length method, 39-2
 stress corrosion, 45-9
 weld bead, 45-9
- Cracking, hydrocarbon, 22-2
- Cramer's rule, 3-7, 4-6
- Crankcase oil, 52-19
- Crank end, 29-2
- Crank-slider, 55-13
- Credit, 69-33
 investment, 69-25
 tax, 69-25
- Creed, 71-1
- Creep, 46-10, 46-15
- Crest (dam), 15-11
- Crevice, 21-11
- Cristobalite, 45-18
- Criteria pollutant, 66-3
- Critical
 back-pressure ratio, 26-12, 26-13
 damping, 58-9
 damping coefficient, 58-9
 fastener, 51-16
 flow, 16-8
 gas constant, 26-4
 height, pressure vessel, 53-5 (ftn)
 insulation thickness, 34-10
 isobar, 24-3
 line, 47-4
 load, column, 51-1
 path method, 61-3, 61-4
 point, 8-2, 24-3, 24-8, *24-8*, 26-4, 47-4
 pressure ratio, 26-4
 property, 24-8, 26-5
 radius, 34-10
 ratio, 26-4
 Reynolds number, 36-3
 slenderness ratio, 51-2
 speed, shaft, 58-15, 58-17
 temperature, 47-4, 47-7
 zone, 16-8
- Cross
 -drum boiler, 27-4
 -linking, 45-13, 45-16
 main, 65-2, 65-12
 product, 43-2
 product, vector, 5-4
 temperature, 36-14
- Crossed drive, 52-15
- Crossflow
 cylinder, 36-8
 heat exchanger, 36-11
 tube, *36-9*
- Crossover
 frequency, 60-11
 gain, 60-11
 point, 60-10
- Crud, 21-16
- Crushing, 64-7
- Crusting agent, 66-10
- Cryogen, 24-2 (ftn)
- Cryogenic fluids, 24-2 (ftn)
- Cryolite, 45-11
- Crystallinity, polymer, 45-16
- Crystallization, water of, 21-4
- Cube, conduction, 34-11
- Culvert, 17-19
 entrance loss, *17-19*
- Cumulative
 fatigue, 50-7
 frequency, 11-9
 probability, *A-129*
 usage factor rule, 50-7
- Cunife, 45-13
- Cup
 -and-bob viscometer, 14-6 (ftn)
 -and-cone failure, 46-4
- Cupola, 45-10 (ftn)
- Curl, 8-7
- Current
 asset, 69-34
 divider, 67-4
 electrical, 67-2
 electric motor, *19-5*
 liability, 69-34
 meter, 17-21
 ratio, 69-34
- Curve, 7-3
 bell-shaped, 11-6
 degree, 7-3
 Euler's, 51-2
 fan characteristic, 20-5
 flow, 46-5
 inversion, 25-3
 learning, 69-42, *69-42*
 load, 27-15
 load-elongation, 46-1
 mortality, 61-11
 normal, *A-12*
 operating characteristic, 61-25
 performance, 18-15
 reloading, 46-6
 resistance, 56-19
 stress-strain, 46-1, 46-3
 symmetry, 7-4
 system, 18-15, 20-7
 time-temperature-transformation, 47-6
 unloading, 46-6
- Curved beam, 49-19, *49-19*
- Cut-and-sum method, 43-15
- Cut-in/out pressure, 32-2
- Cut
 -off
 frequency, 60-10
 governing, 27-16
 rate, 60-10
 ratio, 29-11
 volume, 29-11
 -point, 64-10, 64-11
 size, 66-26
- Cutting, 64-7
 energy, 63-3
 force, 63-2
 hardness, 46-12
 oil, 63-4
 power, 63-3
 speed, 63-2, 63-3 (tbl)
 tool material, 63-4
 torch, 63-12 (ftn)
- Cyaniding, 47-10
- Cycle, 25-10, 28-1 (*see also type*)
 absorption, 33-6
 air refrigeration, 33-6
 air-standard, 29-2
 air-standard diesel, 29-10
 air-standard dual, 29-11
 air-standard Otto, 29-5
 binary, 28-7, 31-7
 bottoming, 29-21
 Brayton, 29-15, 29-18, 29-19, 33-6
 Carnot, 25-10 (ftn), 25-11, 28-2, 29-4, 33-3
 Claude, 31-6 (ftn)
 cogeneration, 29-21
 combined, 29-22
 direct fuel reforming, 31-8
 dual-flash, 31-7
 Ericsson, 29-13
 flash steam, 31-7
 four-stroke, 29-2
 internal fuel reforming, 31-8
 Joule, 29-15
 nuclear power, 30-1
 power, 25-10
 Rankine, 28-3 to 28-5
 redesign, 27-16
 regenerative, 28-7
 solar power, 31-3
 Stirling, 29-12
 supercritical, 28-7
 time, 61-18
 topping, 29-21
 two-stroke, 29-2
 vapor compression, 33-3
- Cycles of concentration, 38-13
- Cyclic
 strain, 46-9 (ftn)
 stress, 46-9 (ftn)
- Cycloid, 7-3
- Cycloidal cam profile, 57-10
- Cyclone, 66-26
- Cyclone separator, 64-10
- Cylinder
 composite, 34-8

Italicized page numbers represent sources of data in tables, figures, and appendices.

- conduction through, 34-8
 crossflow, 36-8
 hydraulic, 19-6
 -operated pump, 18-2
 pressure, peak, 29-8 (ftn)
 thick-walled, 51-4, *51-5*
- Cylindrical coordinate system, 7-3 (tbl), 7-4 (fig)
- D**
- D'Alembert's
 paradox, 17-2 (ftn)
 principle, 56-5
- Dalton's law, 22-13, 24-17, 66-4 (ftn)
- Dam, 15-11
- Damage
 hydrogen, 21-11
 punitive, 70-5
- Damages, 70-7
- Damped
 forced vibration, 58-11
 free vibration, 58-9
 frequency, 58-9, 60-2
- Damper, 59-4
 control, face-and-bypass, 42-1
 duct, 20-18
 face, 42-2 (ftn)
 fire, 20-18
 pulsation (pump), 18-2
 smoke, 20-18
- Damping
 coefficient, critical, 58-9
 critical, 58-9
 factor, 58-9, *58-13*
 heavy, 58-9
 light, 58-5
 linear, 58-9
 ratio, 58-9
 viscous, 58-9
- Dangerous section, 49-11
- Darcy
 chart, *17-6*
 equation, 17-7
 friction factor, 17-5, *A-32-A-35*
 -Weisbach equation, 17-7
- Darrieus rotor, 31-4
- Dashpot, 58-9, 59-4
- Davit, 53-11 (ftn)
- Davonius rotor, 31-4 (ftn)
- Daylight area, 20-24
- DC machine, *67-14*
- Dead
 band, 42-5
 -beat motion, 58-9
 load, 43-4
- Deaerating heater, 27-14
- Deaerator, 27-14
- Debit, 69-33
- Decade, 60-10
- Decay
 exponential, 10-9
 weld, 21-10, 45-9
- Dechlorination, 66-26
- Decibel, 58-12
- Decile, 11-10
- Decimal number, 12-1
- Declining balance method, 69-21, 69-26
- Decomposition, 21-6
- Decrement, logarithmic, 58-9
- Dedendum, 52-10
- Defect, 6-6, 61-24
- Defendant, 70-5
- Defender, 69-18
- Definite integral, 9-1 (ftn), 9-4
- Deflection, *49-3*, 58-2 (ftn)
 beam, 49-13 to 49-16, *A-118-A-120*
 bridge, 62-9
 dynamic, 58-20
 pseudo-static, 58-10
 static, 58-2
 temperature, 46-10
 truss, 49-17
- Deformation, 58-2 (ftn)
 consistent, method of, 49-19
 elastic, 44-1, 49-2
 thermal, 49-3
- Degenerate
 circle, 7-10
 ellipse, 7-11
- Degree, 6-1
 day, 40-5, 41-2
 of a curve, 7-3
 of a polynomial, 3-3
 of damage, 61-27
 of freedom, 27-11, 47-3, 55-2, 58-2, 58-19, 60-14
 of indeterminacy, 43-7, 44-1
 of isolation, 58-12
 of redundancy, 44-1
 of saturation, 38-2
- Dehalogenation agent, 27-12
- Deionized water, 21-16
- Delay, 61-18
- Del operator, 8-5
- Delta
 -connection, 67-9
 -iron, 47-4
 rosette, 62-12
- Demand
 electrical, 67-7
 factor, 27-15
- Demineralized water, 21-16
- de Moivre's theorem, 3-8
- de Morgan's law, sets, 11-2
- Density, 24-5
 concrete, 15-11 (ftn)
 factor, fan, 20-20
 fin, 29-20
 fluid, *14-3*
 function, 11-4
 mass, 1-3
 of a fluid, 14-3
 optical, 66-17
 ratio, air, 20-2 (ftn)
 sprinkler discharge, 65-6
 watt, 40-4 (ftn)
 weight, 1-3
- Denting, 21-16 (ftn)
- Deoxidizer, 45-4
- Dependent
 event, 11-3
 motion, 55-11
 variable, 3-2
- Depletion, 69-24
- Depreciation, 69-20, 69-21
 accelerated, 69-23
- basis, 69-20
 calculation, *69-27*
 rate, 69-21
 recovery, 69-26
- Depression (*see also type*)
 angle of, 6-2
 wet-bulb, 38-2
- Depress of polymerization, 45-14
- Depth, 2-2, 52-10
- Derivative, 8-1
 directional, 8-6
 Laplace transform of, 10-6
 of motion, 57-10
- Derived
 from rule, 66-4
 unit, 1-5, 1-6 (tbl)
 units, SI, *1-5, 1-6*
- Descartes' rule of signs, 3-4
- Design
 condition, indoor, 39-2
 condition, outside, 40-2
 factor, 19-3
 for manufacture and assembly, 61-27
 power, 56-7 (ftn)
 pressure, 26-5, 26-13
 professional, 70-6
 temperature, inside, 41-1
- Designations
 aluminum, 45-11
 TEMA, *36-11*
- Desorption
 gas, 66-22 (ftn)
 thermal, 66-40
- Destruction removal efficiency, 66-30
- Destructive test, 46-13
- Desulfurization, flue gas, 22-5, 66-22
- Desuperheater, 27-13
- Detector-transducer, 62-3
- Deterioration model, 61-11
- Determinacy, 43-7
- Determinant, 4-3
- Deterministic model, 61-2
- Deuterium, 21-2
- Developer, 70-4
- Deviation
 angle, 26-11
 standard, 11-10
- Device, pressure measurement, 15-2
- Dew point
 apparatus, 38-8, 41-3
 flue gas, 22-13
 stack, 66-4
 temperature, 38-2
- Dezincification, 21-11, 45-12
- Diabatic flow, frictionless, 26-19
- Diagonal matrix, 4-1
- Diagram
 block, 60-5, *60-6*
 cash flow, 69-3
 equilibrium, 24-3, 47-1
 fatigue, 50-7 (ftn)
 free-body, 43-8
 iron-carbon, 47-4
 isothermal transformation, 47-6
 Mollier, 24-9, *A-53, A-72*

Italicized page numbers represent sources of data in tables, figures, and appendices.

- moment, 49-8
 - Nelson, 53-4
 - phase, 47-1
 - pole-zero, 60-8, 60-9
 - pressure-enthalpy, 24-11
 - root-locus, 60-12
 - shear, 49-8
 - time-temperature, 47-2
- Diameter
- equivalent, 16-6, *16-7*, 17-9, 17-36, 20-14
 - hydraulic, 16-6, 17-9, 20-14 (ftn), 36-8
- Diametral
- clearance, 52-20
 - interference, 51-5
 - pitch, 52-10
 - strain, 51-5
- Diamond, 63-4
- Diaphragm
- gauge, 15-2
 - pump, 18-3
 - vibration, 58-17
- Die
- casting, 63-9
 - types, 63-6
- Diesel
- cycle, air-standard, 29-10
 - engine, 29-10
 - fuel, 22-7
- Difference
- divided, 13-3
 - R*th-order, 3-10
 - table, divided, 13-3 (ftn)
- Differential
- automotive, 57-9
 - control, 42-2
 - equation, 10-1, 10-8
 - gear ratio, 56-20
 - manometer, 15-3
 - term, 9-1
 - transformer, 62-4
- Differentiation, 8-4
- Diffuser, 20-3, 20-24
- Diffusion-controlled cell, 62-3
- Diffusivity, thermal, 34-4, *34-4*
- Digit, 3-1, 12-1
- Digital
- control, 42-5
 - to-analog, 42-5
 - to-proportional, 42-5
- Dilatant fluid, 14-6, 14-7
- Dilation, 49-2
- Diluent gas, 66-21
- Dilution
- exhaust gas, 29-2
 - extraction, 66-21
 - toxicity, 39-5
 - ventilation, 39-5
- Dimension
- bolt, *51-10*
 - characteristic, 16-6, 34-3
 - nominal, 16-10
 - primary, 1-7
- Dimensionless
- group, 1-7, 1-9 (tbl)
 - number, 1-7, 1-9 (tbl)
- Dimensions
- brass tubing, *A-27*
 - BWG, tubing, *A-103*
 - copper tubing, *A-26*, *A-27*
 - of variables, 1-8 (tbl)
 - PVC pipe, *A-29*
 - steel boiler tubing, *A-28*
 - steel pipe, *16-11*, *A-22-A-25*
- Dimetric view, 2-3
- Dioxin, 66-9
- Direct
- acting pump, 18-2
 - coal-fueled turbine, 29-15
 - combination, 21-6
 - condensing tower, 38-13
 - contact heater, 27-13
 - current, 67-2
 - digital control, 42-5
 - firing system, 27-3
 - fuel reforming cycle, 31-8
 - impact, 56-16
 - injection, 29-3
 - iron-making process, 45-7
 - labor, 69-32
 - transfer function, 60-4
- Directed graph, 61-3
- Direction
- angle, 5-2, 7-4
 - cosine, 5-2, 7-5, 43-2
 - helix, 52-5
 - number, 7-5
- Directional derivative, 8-6
- Directivity, sound, 68-7
- Directrix, 7-10
- Disbenefit, 69-16
- Disbursement, 69-3
- Discharge, 18-4
- coefficient, 17-17, 17-24
 - coefficient, nozzle, 26-8
 - coefficient, sprinkler, 65-5
 - coefficient, venturi, *17-24*
 - density, 65-6
 - from tank, 17-16, 17-17
 - of contract, 70-5
 - side, 18-4
 - sprinkler, *65-5*
- Discounting, 69-5
- factor, *A-138-A-156*
- Discriminant, 3-3, 7-9
- Dish
- engine system, 31-3
 - Stirling system, 31-3
- Disjoint set, 11-1
- Disk
- clutch, 52-19
 - rotating, 57-2
- Dispatch interval, 64-4
- Dispersant, 21-16
- Dispersion, 11-10, 45-19
- Dispersoid, 45-19
- Displacement, 21-6, 55-2
- meter, 17-21
 - piston, 32-3
- Displacer, 29-12
- Dissatisfier, 61-28
- Dissolved oxygen process, 45-3
- Distance, 55-2
- between figures, 7-7
 - skidding, 56-21
 - squared law, 68-3
 - stopping, 56-21
- Distillate oil, 22-6
- Distillation temperature, 66-10
- Distortion energy theory, 46-8, 50-5
- Distributed
- collector system, 31-3
 - load, 43-4, 43-6
- Distribution (*see also type*)
- bathub, 11-7
 - beta, 61-5
 - binomial, 11-4
 - continuous, 11-6
 - discrete, 11-4
 - exponential, 11-6, 61-9
 - frequency, 11-9
 - Gaussian, 11-6
 - hypergeometric, 11-5
 - multiple hypergeometric, 11-5
 - normal, 11-6
 - point, 20-24
 - Poisson, 11-5
 - Student's *t*-, 61-16 (ftn), *A-127*
 - velocity, 16-8
 - Weibull, 61-9
- Distributive law, 3-3
- matrix, 4-4
 - sets, 11-2
- District heating, 29-21
- Dittus-Boelter equation, 36-6
- Divergence, 8-7
- Divergent sequence, 3-10
- Divided
- difference, 13-3 (ftn)
 - flow fitting, 20-16, *20-17*
- Division (matrix), 4-4
- Dodge-Romig plan, 61-25
- Domestic heat source, 40-4 (ftn)
- Dominant load, 49-18
- Doppler effect, 68-4
- Dosimeter, sound, 68-9
- Dot product, 5-3
- Double
- acceptance plan, 61-26
 - acting engine, 29-2
 - acting pump, 18-2
 - angle formula, 6-4
 - butt, 51-10 (ftn)
 - dabble method, 12-1 (ftn)
 - declining balance, 69-21, 69-26
 - entry bookkeeping, 69-33
 - integral, 9-3
 - integration method, 49-13
 - rivet, 51-10 (ftn)
 - root, 3-3
 - seal, 66-35
 - shear, 51-10
 - suction pump, 18-4
 - tempered steel, 45-7 (ftn)
- Doubling time, 69-8, *69-8*
- Downcomer, 27-4

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Downcycling, 66-16
Downtime, 61-9, 61-10
Downturn, 36-23
Draft, 22-16, 63-8
 balanced, 22-16
 cooling tower, 38-11
 forced, 22-16
 gauge, 15-3 (ftn)
 induced, 22-16
 loss, 22-16
 natural, 22-16
 tube, 18-20
Drag, 17-34 (*see also type*)
 coefficient, 17-34, 17-35, 17-36, 36-4 (ftn)
 disk, 17-34
 sphere, 17-34
 vehicular, 56-20
Draught, 22-16 (ftn)
Drawing, 2-2 (ftn), 47-9, 63-7
Drift, 38-13, 66-27
Drip, 27-14
Drive
 belt, 52-15
 flat belt, 52-15
 train efficiency, 56-20
 worm, 52-14
Driving dynamometer, 62-12
Droop, compressor, 32-9
Drop
 forging, 63-7
 spherical, 10-10
 test, 58-21
Dropwise condensation, 35-8
Drum
 mud, 27-4 (ftn)
 steam, 27-4
Dry
 absorption, 66-37
 air, composition, 22-8
 -bulb temperature, 38-1
 bulk solid, 64-5
 combustor, 29-14
 compression, 33-4
 cooling tower, 38-13
 flue gas loss, 22-15
 sand, 63-8
 scrubbing, 66-37
 ultrafine coal, 66-10
Dual
 cycle, air-standard, 29-11
 -duct system, 42-1
 -flash cycle, 31-7
Duct, 36-8 (ftn)
 collapse, 20-18
 exhaust, 20-18, 20-25
 fan, 20-3
 friction loss, 20-11, 20-12, 20-13
 heat gain to, 41-2
 leakage, 20-18
 rectangular, 20-14
 specific roughness, 20-11, 20-11 (ftn)
 supply, 20-18
 velocity, 20-19
Ductile
 cast iron, 16-10, 45-9
 material, 46-5, 50-3, 50-4
 transition temperature, 46-14
Ductility, 46-5
Ductility transition temperature, 46-14
Dulong and Petit law, 24-7
Dulong's formula, 22-14
Dummy
 activity, 61-5
 node, 61-3
 unit load, 44-6
Dump, 27-11 (ftn), 66-12
Dunkerley approximation, 58-16
Du Nouy torsion balance, 14-11 (fig)
Duplex
 pump, 18-2
 stainless steel, 45-9
Duplexed steel, 45-4
Duralumin, 45-12 (ftn)
Dust, 66-9
 coal, 66-10
 collector, 39-5
 control, 66-9
Duty, 29-21
 condenser, 27-11
 cooling, 38-12
 cycle, 67-12
 heat, 36-14
 point, fan, 20-7 (ftn)
 rating, continuous, 29-4
Dwell, 57-11
Dynamic
 analysis, 49-7
 balance, 54-2, 58-18
 compressor, 32-1, 32-2, 32-8
 deflection, 58-20
 energy, 16-2 (ftn)
 equilibrium, 56-5
 friction, 56-6
 head, total, 18-6
 programming, 61-12
 reaction, 56-5 (ftn)
 response, 49-7
 response, spring, 52-8
 similarity, 17-38, 18-19, 20-9
 unit, 60-4
 viscosity, 14-6 (ftn)
Dynamics, 26-1, 55-1
 cam lobe, 57-12
Dynamometer, 29-3, 62-12
Dyne, 1-4
E
Earnings, relative, 61-20
Earth's atmosphere, 15-12, 15-13
Earths, rare, 21-2
Eastern coal, 22-4
Eccentric
 impact, 56-16
 load, column, 51-3
 load, connection, 51-16, 51-17
 loading, 49-11
Eccentricity, 7-8, 7-11, 7-12, 49-11, 51-3
 dam, 15-12
 orbit, 56-19, 56-19
 ratio, bearing, 52-20
EC grade aluminum, 45-11 (ftn)
Echelon form, row-reduced, 4-2
Echelon matrix, 4-1
Eckert number, 1-9 (tbl)
Economic
 analysis factor, A-138-A-156
 indicator, 69-39
 insulation thickness, 34-10
 life, 69-19
 order quantity, 61-2 (ftn), 69-42
Economizer, 22-3, 27-15
Eddy current testing, 46-11
Eductor, 27-3 (ftn)
Effect
 Doppler, 68-5
 evaporator, 27-14
 flywheel, 57-1
 greenhouse, 31-2
 Hall, 31-8 (ftn)
 isotope, 21-2 (ftn)
 Magnus, 17-34
 Peltier, 62-6 (ftn)
 photoelectric, 62-4
 piezoelectric, 15-2, 62-4
 refrigeration, 33-3
 Seebeck, 62-6
 stack, 22-16
 system, 20-7
 Thompson, 62-6 (ftn)
Effective
 allowable stress, pressure vessel, 53-9
 exhaust velocity, 2-8
 force, 56-5 (ftn)
 head, 17-16, 18-5
 interest rate, 69-5, 69-28
 length, column, 51-2
 length, V-belt, 52-16
 period, 69-2
 pressure, 29-3, 29-8
 sensible heat ratio, 38-7
 tension, belt, 64-8
 time, 26-9
 value, 67-5
 weld throat, 51-13
 wind velocity, 39-2
Effectiveness
 fin, 34-16
 heat exchanger, 36-20, A-104, A-105
 lever, 15-14
 method, 36-20
 regenerator, 29-19
Efficacy, luminous, 68-2
Efficiency, 23-6
 adiabatic, 27-8
 adiabatic compression, 32-3
 boiler, 22-16, 27-4
 coil, 38-7
 collector, 31-2
 combustion, 22-16
 cooling tower, 38-12
 destruction removal, 66-30
 drive train, 56-20
 factor, heat removal, 31-2
 fan, 20-4
 fin, 34-16, 34-17

Italicized page numbers represent sources of data in tables, figures, and appendices.

- furnace, 22-16
 - gear train, 52-12
 - humidification, 38-7
 - isentropic, turbine, 27-8
 - isolation, 58-12
 - joint, 16-10, 51-11, 53-8
 - lever, 15-14
 - luminous, 68-2
 - mechanical, 29-3
 - mesh, 52-12
 - method, 36-20
 - motor, 67-15
 - nozzle, 26-8
 - overall, pump, 18-8
 - polytropic, 32-5
 - production, 61-20
 - pulley, 43-11
 - pump, 18-8
 - pumping (temperature), 18-19
 - pump isentropic, 27-6
 - radiator, 34-16
 - regenerator, 29-19
 - relative, 29-3
 - removal, 66-25
 - saturation, 38-7, 38-11
 - static, 20-4
 - thermal, 22-16, 25-10, 28-1, 29-3
 - total, fan, 20-4
 - volumetric, 29-3, 32-4
 - weld, joint, 53-9
 - Efflux, speed of, 17-16
 - Effort, 43-10
 - Eigenvalue, 4-7, 60-8 (ftn)
 - Eigenvector, 4-7
 - Ejector pump, 18-2
 - Elastic
 - analysis, 51-16
 - constants, 46-8
 - constants, relationships, 46-8
 - deflection, beam, A-118-A-120
 - deformation, 44-1, 49-2
 - failure, 49-18
 - impact, 56-15
 - limit, 46-2
 - line, 49-14
 - region, 46-2
 - strain, 46-2
 - toughness, 46-6
 - Elasticity, modulus of, 46-2, 46-2, 49-2
 - Elastomer, 45-13, 45-15
 - Electric
 - arc furnace, 45-5
 - charge, 67-2
 - machine, 67-14
 - motor formulas, 19-5
 - motor, hydraulic power, 19-5
 - motor size, 18-9
 - vehicle, 31-10
 - Electrical
 - discharge machining, 63-6
 - generator, 27-15
 - output, 27-1
 - rating, power, 27-1
 - thermal analogy, 34-5, 34-12
 - Electricity, cost, 18-8
 - Electrochemical
 - grinding, 63-6
 - machining, 63-6
 - Electrolytic grinding, 63-6
 - Electromotive force, 67-2
 - Electronic enclosures, 36-23
 - Electroplating, 63-14
 - Electropneumatic switch, 42-1
 - Electrospark machining, 63-6
 - Electrostatic precipitator, 66-26, 66-27
 - Electrostatic unit, 67-2
 - Elementary row operation, 4-2
 - Elements, A-39, A-40
 - types, 21-2
 - Element, transition, 21-2
 - Elevation
 - angle of, 6-2
 - drawing, 2-2
 - Elevator, 64-3, 64-9
 - Elimination, Gauss-Jordan, 4-2
 - Elinvar, 45-13
 - Ellipse, 7-11, 7-11
 - Elliptic integral function, 9-8 (ftn)
 - Elongation at failure, 46-5
 - Elutriation, 64-11
 - Embossing, 63-7
 - Embrittlement
 - blue, 47-9
 - caustic, 21-11
 - hydrogen, 21-11, 53-4
 - neutron, 30-2
 - Emery, 45-19
 - Emission, fugitive, 66-10
 - Emissions
 - monitoring, 66-21
 - sampling, 66-20
 - Emissive power, 37-1
 - Emissivity, 37-1, 37-3, A-106
 - Emulsion, 19-2 (ftn), 21-7 (ftn)
 - Enclosed air space, 35-7
 - Enclosure hood, 39-4
 - Enclosures, cooling electronic, 36-23
 - End
 - around carry, 12-4
 - post, 43-12
 - quench test, 47-7
 - restraint coefficient, 51-2, 51-2
 - Endoergic impact, 56-15
 - Endothermic reaction, 21-9
 - Endpoint, pressure-drop, 21-16
 - End treatment, spring, 52-6
 - Endurance
 - limit, 46-9
 - ratio, 46-9
 - strength, 46-9
 - Energy, 23-1
 - conservation, 58-5
 - conservation law, 23-1
 - content of moist air, 38-3
 - cutting, 63-3
 - dynamic, 16-2 (ftn)
 - efficiency ratio, 23-6 (ftn), 33-2
 - falling mass, 23-3 (ex)
 - flow, 16-2, 23-3, 24-6, 25-6
 - flywheel, 57-1
 - grade line, 16-9, 17-15
 - gravitational, 23-2
 - impact, 16-4
 - internal, 23-4, 24-5
 - kinetic, 16-2, 23-3
 - line, 16-9
 - potential, 16-2, 23-2
 - pressure, 16-2, 23-3
 - production efficiency, 23-6
 - sink, 17-15, 25-10
 - solar, 31-1
 - source, 17-15, 25-10, 31-1
 - specific, 16-1, 16-9, 23-1
 - specific, battery, 31-10
 - spring, 23-3
 - stagnation, 16-4
 - static, 16-2, 23-3
 - storage, 31-9
 - strain, 46-6, 49-2, 49-11
 - strain, torsion, 51-13
 - total, 16-2, 16-4
 - use efficiency, 23-6
 - velocity, 16-2 (ftn)
 - work principle, 23-3, 23-4
- Engine
 - diesel, 29-10
 - gas-diesel, 29-10
 - oil, 52-19
 - Stirling, 29-12
 - Engineering
 - dimensional system, 1-7
 - economy factor, A-138-A-156
 - intern, 72-1 (ftn)
 - registration, 72-1
 - strain, 46-2
 - stress, 46-2
 - Engineer-In-Training exam, 72-1
 - Engineers' Creed, 71-1
 - English
 - engineering system, 1-2
 - gravitational system, 1-3
 - Enlargement, 17-12, 17-13
 - Enthalpy, 24-5
 - of formation, 21-9, 21-10
 - of moist air, 38-3
 - of reaction, 21-9
 - Entrance
 - loss, culvert, 17-19
 - region, 36-5
 - Entropy, 24-6
 - function, 24-11
 - production, 24-6
 - Entry, coefficient of, 20-15
 - air, 20-13
 - Entry length, thermal, 36-5
 - Environment, 25-1, 66-3
 - Environmental engineering, 66-4
 - Eötvös number, 17-38
 - Epicyclic gears, 57-6, 57-9, A-126
 - Epicycloid, 7-3
 - Epidemic, 10-10
 - Equal
 - friction method, 20-19
 - vectors, 5-1
 - Equality of matrices, 4-3

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Equation, 3-2
 Andrade's, 46-15
 Antoine, 14-9 (ftn)
 auxiliary, 10-1
 Bernoulli, 16-2, 17-14
 Bessel, 10-5
 Blasius, 17-5
 Bromley, 35-11
 Buckingham, 52-14 (ftn)
 Cauchy, 10-5
 characteristic, 10-1
 Clausius-Clapeyron, 14-9 (ftn)
 Colebrook, 17-5
 complementary, 10-1
 Darcy, 17-7
 Darcy-Weisbach, 17-7
 differential, 10-1
 Euler's, 3-8, 10-5
 Gauss' hypergeometric, 10-5
 general flow, 26-2
 Hagen-Poiseuille, 17-7
 Hazen-Williams, 17-7, 65-7
 Legendre, 10-5
 Nikuradse, 17-5
 nonparametric, 3-3
 Nusselt, 35-3, 36-5
 of state, 24-12, 24-13
 real gas, 24-19
 van der Waals', 24-19
 virial, 24-19
 parametric, 3-2
 Petroff, 52-21
 quadratic, 3-3
 reduced, 10-1
 Rohsenow, 14-10
 steady-flow energy, 26-2
 Taylor's, 63-5
 three-moment, 44-5
 tool life, 63-5
 Torricelli's, 17-16
 Weisbach, 17-7
 Weymouth, 26-17
 Zuber, 14-10
- Equations
 of motion, Euler's, 56-8
 simultaneous linear, 3-7
- Equiangular rosette, 62-12
- Equilateral hyperbola, 7-12
- Equilibrium, 43-20, 56-2
 conditions, 43-6
 conditions, static, 43-6
 diagram, 24-3, 47-1
 diagram, iron-carbon, 47-5
 dynamic, 56-5
 isopiestic, 14-9
 moisture content, 45-17
 phase, 56-6
 position, 58-2
 solid, 24-3
 static, 15-16
 thermal, 24-4, 25-5, 37-1, 37-6
- Equipment
 high-side, 33-7
 low-side, 33-8
- Equipotential line, 17-3
- Equity, 69-34
- Equivalence, economic, 69-5
- Equivalent
 CaCO₃, 21-13
 chemical, 21-4
 diameter, 16-7, 16-7, 17-9, 17-36
 diameter, duct, 20-14
 evaporization, 27-5
 fluid height, 15-5 (tbl)
 Joule, 23-1
 length, 17-11, 17-12, A-131
 air, 20-13
 fitting, A-37, A-131
 length method, duct, 20-15
 resultant, 43-4
 spring constant, 52-2
 stress, 50-6
 temperature difference, 41-2
 uniform annual cost, 69-7
 vector, 5-1 (ftn)
 weight, 21-4
 weight, milligram, 21-8
- Erf, 9-8
- Ergonomics, 61-29
- Ericsson cycle, 29-13
- Erosion corrosion, 21-11
- Error, 11-13, 60-4, 60-14, 61-9, 62-2 (*see also type*)
 function, 9-8, 11-6
 gain, 60-4
 in action, 52-14
 magnitude, 62-3
 ratio, 60-4
 signal, 60-4
 terms, 62-3
 transfer function, 60-4
 type VII, 61-25
- Errors and omission insurance, 70-7
- Escape velocity, 56-19
- Estimator, unbiased, 11-10
- Etching radius, 63-6
- Ethanol, 22-7
- Ethic, 71-1
- Ethical priority, 71-2
- Ethyl alcohol, 22-7
- Euler
 constant, 9-8 (ftn)
 curve, 51-2
 equation, 3-8
 equations of motion, 56-8
 load, 51-1
 number, 1-9 (tbl)
- Eutectic
 alloy, 47-3
 cast iron, 47-5
 composition, 47-3
 line, 47-3
 reaction, 47-3
 temperature, 47-3
- Eutectoid
 reaction, 47-3
 steel, 47-5
 temperature, 47-4
- Evacuated-tube collector, 31-2
- Evaluation, nondestructive, 46-11
- Evaporation, 10-10, 38-13
- Evaporative cooling, 38-7, 38-10
- Evaporative pan humidification, 39-3
- Evaporator, 27-14 (ftn), 33-1, 33-8
- Evaporization, 35-10, 35-11
 equivalent, 27-5
 factor of, 27-4
 film coefficient, water, 35-11
- Evase, 20-3
- Even symmetry, 7-4, 9-7 (tbl)
- Event, 11-2, 61-3
- Exact equations, first-order, 10-3
- Exams, licensing, 72-1, 72-2
- Exam date, 72-2
- Excess air, 22-12
- Exchange, ion, 21-14
- Exchanger, heat, 36-10
- Excitation, motor, 67-13
- Exciter, 58-21
- Exemplary damages, 70-7
- Exfoliation, 21-11
- Exhaust,
 duct, 20-18, 20-25
 gas dilution, 29-2
 hood, fume, 39-4
 stroke, 29-2
 velocity, characteristic, 26-9
 velocity, effective, 26-8
- Exit property, 26-5
- Exoergic impact, 56-15 (ftn)
- Exothermic reaction, 21-9
- Expanded-flow bin, 64-5
- Expander, 29-14
- Expansion
 by cofactor, 4-3
 coefficient of, 14-12 (ftn)
 factor, 17-26, 17-26
 linear, coefficient, 49-3
 over-, 26-13
 series, 8-8
 thermal, 49-3
 thermal, coefficient of, 49-4, 66-36
 two-stage, 27-8
 under-, 26-13
 valve, 33-1
 volumetric, coefficient, 49-3
- Expected value, 69-30
- Expense, 69-32
- Expensing an asset, 69-20
- Explosive
 forming, 63-11
 limit, lower, 39-5
- Exponent, 3-5
 polytropic, 15-13, 25-2
 rules, 3-5
 strain-hardening, 46-5
- Exponential
 decay, 10-9, 60-9
 distribution, 11-6, 11-7, 61-9
 form, 3-8
 function, integral, 9-8
 gradient cash flow, 69-4
 growth, 10-9, 69-4
 growth factor, A-138-A-156

Italicized page numbers represent sources of data in tables, figures, and appendices.

- reliability, 11-7
- weighted forecast, 69-42
- Exposed fraction, 15-15
- Exposure
 - allowance, 40-1
 - limit, short-term, 39-5
- Extended surfaces, 34-16
- Extension spring, 52-8
- Extensive property, 24-4
- External
 - force, 43-2, 56-2
 - gear, 57-4
 - pressure, 15-14
 - rate of return, 69-12
 - shoe brake, 52-17
 - work, 23-1
- Externality, nuclear 30-2
- Externally fired combined cycle, 29-15
- Extraction
 - cycle, 28-2
 - rate, 27-8
 - turbine, 27-8, 27-13
- Extractive metallurgy, 45-1
- Extreme
 - fiber, 49-11
 - point, 8-2
 - stress, 49-5
 - temperature difference, 36-13
- Extrinsic waste, 66-3
- Extrusion, 63-10
- F**
- Face
 - and-bypass damper control, 42-1
 - damper, 42-2 (ftn)
 - value, 69-29
 - velocity, 66-24
 - width, tooth, 52-10
- Facilities layout, 61-14
- Factor (*see also type*)
 - absorption, 66-40
 - arrangement, 37-3
 - Barth speed, 52-13
 - bolt torque, 51-12
 - bonus, 61-20
 - bypass, 41-4
 - capacity, 27-15
 - cleanliness, 27-11
 - coil, 38-7
 - compounding, 69-7
 - compressibility, 14-12 (ftn), 24-19, A-83
 - contact, 38-8
 - cooling load, 41-2
 - correction, LMTD, A-100
 - damping, 58-9, 58-13
 - Darcy friction, 17-5
 - demand, 27-15
 - density, fan, 20-2
 - design, 19-3
 - directivity, 68-7
 - discounting, A-138-A-156
 - economic analysis, A-138-A-156
 - emissivity, 37-3, 37-3
 - expansion, 17-26, 17-26
 - Fanning friction, 17-5 (ftn), 26-15, 26-18
 - fatigue notch, 46-10
 - fatigue stress concentration, 46-9, 46-10
 - form, gear, 52-13
 - fouling, 36-17, 36-17
 - friction, Darcy, A-32-A-35
 - gage, 62-8, 62-8
 - heat removal efficiency, 31-2
 - heat transfer, 36-22
 - impact, 16-4
 - integrating, 10-2
 - interference, 31-5
 - joint quality, 16-10
 - LMTD, 36-14
 - load, 27-15
 - loading, 31-9
 - magnification, 58-10, 58-12
 - normal shock, 26-9
 - nut, 51-12
 - of evaporation, 27-4
 - of safety, 15-11, 15-12, 50-1
 - output, 27-16
 - performance, 38-10
 - performance rating, 61-16
 - phase, 67-7
 - piping geometry, 17-13
 - plant, 27-15
 - power, 67-7, 67-8
 - reheat, 28-6
 - sensible heat, 38-6
 - service, 40-4, 56-7 (ftn), 67-11
 - service, gear drive, 52-11
 - service, V-belt, 52-16
 - shading, 31-2
 - shape, 34-20, 34-21, 37-2, 37-2, 37-4
 - side friction, 56-21
 - stress concentration, 49-4, A-121
 - press fit, 51-8
 - stripping, 66-40
 - surface finish, 46-10
 - transmission, 26-18
 - transverse sensitivity, 62-8
 - use, 27-16
 - utilization, queue, 61-7
 - velocity of approach, 17-23
 - Wahl, 52-5
 - water hammer, 19-3
- Factorial, 3-2, 32-2 (ftn)
- Factors, conversion, A-1-A-6, inside front cover
- Factors versus strength, 46-16
- Factory
 - cost, 69-32, 69-36
 - loading, 61-15
- Failure, 11-3
 - brittle, 46-13
 - cup-and-cone, 46-4
 - line, 50-6
 - mean time to, 11-7, 61-9
 - mode and effect analysis, 61-27
 - sudden, 61-11
 - theory, 50-1
- Failures, mean time between, 61-9
- Faith of an engineer, 71-1
- Falling mass energy, 23-3 (ex)
- Family, chemical, 21-2
- Fan
 - axial flow, 20-3
 - boost, 22-16
 - centrifugal, 20-3
 - curve, 20-5
 - duct, 20-3
 - efficiency, total, 20-4
 - homologous, 20-9
 - law, 20-8
 - non-overloading, 20-4
 - paddle wheel, 20-4
 - power, 20-4
 - propeller, 20-3
 - radial, 20-4
 - radial tip, 20-4
 - rating table, 20-5
 - shaving wheel, 20-4
 - similarity, 20-9
 - specific speed, 20-4
 - squirrel cage, 20-3
 - straight-blade, 20-4
 - tubeaxial, 20-3
 - vaneaxial, 20-3
- Fanning friction factor, 17-5 (ftn), 26-15, 26-18, 36-4 (ftn)
- Fanno flow, 26-15, A-86
- Fan similarity equations, 20-9
- Faraday, 67-2
- Far-field, 68-6
- Fastener, 51-8, 51-16
- Fast Fourier transform, 9-7
- Fatigue
 - corrosion, 21-12
 - cumulative, 50-7
 - diagram, 50-7 (ftn)
 - failure, 46-8
 - interaction formula, 50-7
 - life, 46-9
 - loading, spring, 52-4
 - notch factor, 46-10
 - notch sensitivity, 46-10
 - ratio, 46-9
 - strength, 46-9
 - stress concentration, 49-5
 - stress concentration factor, 46-10
 - test, 46-8
- Fault, 61-9
 - tolerant system, 61-9
 - tree analysis, 61-27
- Feasible region, 61-12
- Feedback, 60-4
 - gain, 60-4
 - negative, 60-4
 - positive, 60-4
 - ratio, 60-4
 - transfer function, 60-4
- Feeder, dry bulk solid, 64-5, 64-6
- Feed main, 65-2
- Feedwater
 - boiler, 21-15, 21-16
 - heater, 27-13
 - heater, closed, 36-14 (ftn)
- Fee structure, 70-4
- Fenestration, 41-2 (ftn)
- Ferrimagnetic material, 45-18

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Ferrispinel, 45-18
 Ferrite, 45-18, 47-4, 47-6
 Ferritic stainless steel, 21-11 (ftn), 45-8
 Ferroelectric, 45-18
 FFT (*see* Fast Fourier transform)
 Fiber
 -nickel-cadmium battery, 31-10
 -strengthened, 45-19, 45-20
 Fiber core, wire rope, 64-2
 Fiberglass, 45-19, 66-5
 Fictive temperature, 45-17
 Fiduciary responsibility, 70-2
 Figure of merit, 31-9
 File hardness, 46-13
 Filler, 45-13
 Fillet weld, 51-13
 Fill, tower, 38-11
 Film
 amorphous, 31-4
 boiling, 35-10
 coefficient, 34-6, 35-2
 air, 35-5, 40-3
 combined, 34-17
 evaporization, water, 35-11
 natural, 35-2
 total, 35-11
 Reynolds number, 35-9
 temperature, 35-3, 36-3
 Filming amine, 21-15
 Filmwise condensation, 35-8
 Filter, 60-10
 air, 39-5
 hydraulic, 19-5
 ratio, 66-24
 Filtering velocity, 66-24
 Fin, 34-16 to 34-18 (*see also type*)
 density, 29-20
 effectiveness, 34-16
 efficiency, 34-16, 34-17
 length, corrected, 34-18
 -tube exchanger, 36-13
 Final value, 60-7
 Fines (coal), 22-4
 Finish, surface, 2-4, 2-4, 46-9
 factor, 46-10
 Finite series, 3-11
 Fire
 damper, 20-18
 protection system, 65-1
 -resistant fluid, 19-2
 -tube boiler, 27-4 (ftn)
 Firm capacity, 27-15
 First
 critical back-pressure ratio, 26-13
 derivative, 8-1
 -in, first-out, 69-37
 law of thermodynamics, 23-2 (ftn), 25-4, 25-5
 moment of a function, 9-6
 moment of area, 44-5, 48-2
 -order, 10-3
 -order, linear, 10-2
 Fit
 interference, 51-5
 press, 51-5
 shrink, 51-5
 Fitting
 divided flow, 20-16
 equivalent length, A-37, A-131
 friction loss, duct, 20-14
 screwed, 17-12 (ftn)
 threaded, 17-12 (ftn)
 Fixed
 asset, 69-34
 carbon, 22-4
 -charge problem, 61-13
 cost, 69-31
 -end beam, 44-1, 44-6
 -end moment, 44-6
 -orifice desuperheater, 27-13
 -point iteration, 13-2
 pulley, 43-11
 vector, 5-1 (ftn)
 Flame
 blow-off, 27-3
 hardening, 47-10
 temperature, 22-15, 66-13
 welding, 63-12
 Flange, 48-4
 stiffener, 49-18
 straight, 53-4
 Flanged
 hood, 39-4
 joint, 53-14
 Flank, tooth, 52-10
 Flap, 17-33
 Flare, 66-11, 66-34
 Flash, 63-8
 -back, 27-3
 evaporator, 27-14 (ftn)
 point, 22-5 (ftn)
 steam cycle, 31-7
 tank, 27-14 (ftn), 31-7
 Flashing, 27-13, 27-14 (ftn)
 Flat
 belt drive, 52-15
 coil spring, 52-9 (ftn)
 -faced follower, 57-10
 friction, 56-6
 plate, 51-17
 collector, 31-2
 evaporation, 35-11
 film coefficient, 35-6
 flow over, 36-3, 36-4
 uniform pressure, 51-18
 spring, 52-10
 Flexible hydraulic hose, 19-3
 Flexural stress, 49-10
 Float, 61-3
 Floating
 action control, 42-5
 -head heat exchanger, 36-11
 object, 15-15, 15-16
 Flocculation, 66-41
 Floodable material, 64-5
 Flooding, 66-22, 66-40
 velocity, 66-22
 Flow
 adiabatic, with friction, 26-15
 annular, 36-8
 around cylinder, 17-36
 choked, 26-4
 coefficient of, 17-13, 17-24
 coefficient, orifice plate, 17-25
 coefficient, valve, 17-13
 Couette, 36-3 (ftn)
 critical, 16-8
 curve, 46-5
 diagram, cash, A-137
 energy, 16-2, 23-3, 24-6, 25-6
 equalization, 66-41
 Fanno, 26-15
 frictionless diabatic, 26-19
 isentropic, 26-3
 isothermal, with friction, 26-17
 laminar, 16-7
 measurement, 17-20
 nozzle, 17-25
 number, 64-12
 of water through schedule-40 pipe, A-36
 over flat plate, 17-37
 rate, 20-3
 Rayleigh, 26-19
 shear, 51-15
 streamline, 16-7
 turbulent, 16-8, 17-5
 uniform, 16-9
 viscous, 16-7
 work, 23-3, 25-6
 Fluctuation, coefficient of, 57-2
 Flue gas, 22-11, 66-4 (ftn)
 calculations, 22-12
 cleanup, 66-24
 desulfurization, 22-5, 66-22
 dew point, 22-13
 recirculation, 66-27
 temperature, 22-13
 Fluid
 capacitance, 59-7
 compressible, 26-1
 cryogenic, 24-2 (ftn)
 density, 14-3
 heat transfer, 31-2, 36-22
 height equivalent, 15-5 (tbl)
 hydraulic, 19-2
 hydraulic fire-resistant, 19-2
 ideal, 14-2
 inductance, 59-7
 inertance, 59-7
 mass, 15-19
 Newtonian, 14-2, 14-6
 power, 19-1
 pump, 19-4
 symbols, 19-1, A-38
 pressure, 14-2, 15-14
 real, 14-2
 resistance coefficient, 59-7
 rotating, 57-3
 shear stress, 14-6
 system, modeling, 59-7
 transfer, 31-3
 type, 14-2
 velocity, maximum, 17-3
 viscosity type, 14-6

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Fluidized-bed
 boiler, 66-28
 combustion, 22-5, 27-3, 27-4
 combustor, 66-27
- Fluorinated hydrocarbon, 33-4
- Fluoroplastic, 45-15
- Fluoropolymer, 45-15, *45-16*
- Flux
 geometric, 37-4
 heat, 35-3, 36-5
 luminous, 68-1
 welding, 63-12
- Fly ash, 22-3
- Flywheel, 57-1, 57-3
 advanced, material, *57-4*
 effect, 57-1
 effect, thermal, 40-5
 rotor, 57-3
- F-method, 36-20
- Focus, 7-10
- Focusing collector, 31-2
- Follower, 57-10
 offset, 57-11
- Footcandle, 61-30 (ftn)
- Foot pulley, 64-9
- Force, 56-2 (*see also type*)
 amplification, 43-10
 central field, 56-17
 centrifugal, 56-5
 centripetal, 56-5
 concentrated, 43-2
 -couple system, 43-4
 cutting, 63-2
 external, 43-2
 gear, 52-12, 52-13
 inertial, 56-5
 internal, 43-2
 majeure, 70-3
 normal, 56-6
 ormal, on a dam, 15-12
 number, 64-12
 on a dam, 15-11
 on a blade, jet, 17-29
 on a pipe bend, 17-30
 on-plate, jet, 17-28
 tractive, 56-20
 van der Waals', 24-19
 velocity-dependent, 56-17
 work performed by, 9-4
- Forced
 convection, 36-2
 draft, 22-16
 draft tower, 38-11
 outages, mean time between, 61-9
 response, 60-2
 vibration, 58-2, 58-10
- Forcing
 frequency, 58-10
 function, 10-1, 10-4, 58-10, 59-2
- Forebay, 18-20
- Forecasting, 69-41
- Forging, 63-7
 temperature, *63-7*
- Form
 cis, 3-8
 drag, 17-34
 exponential, 3-8
 factor, gear, 52-13
 Newton, 13-3 (ftn)
 operational (log), 3-5
 phasor, 3-8
 polar, 3-8
 rectangular, 3-7
 trigonometric, 3-7
- Formality, 21-7
- Formation
 enthalpy of, 21-9, *21-10*
 heat of, 21-9
- Forming, explosive, 63-11
- Formula
 Babcock, 17-9
 Barlow, 19-3
 Boardman, 19-3
 double-angle, 6-4
 Dulong's, 22-14
 half-angle, 6-4
 J. B. Johnson, 51-3
 Lamé, 19-3
 Maney, 51-12
 Panhandle, 17-9
 parabolic column, 51-3
 PLAN, 29-8
 secant, 51-3
 Spitzglass, 17-9
 two-angle, 6-4
 weight, 21-4
 Weymouth, 27-9
- Forward
 -curved fan, 20-3
 gain, 60-4
 transfer function, 60-4
- Fouling, 17-12, 36-17
 factor, *36-17*
- Fourier
 analysis, 9-6
 inversion, 9-6
 number, 1-9 (tbl), 34-4
 series, 9-6
 transform, fast, 9-7
 waveforms, *9-7*
- Fourier's
 law, 34-5
 theorem, 9-6
- Four-stroke
 cycle, 29-2
 diesel, 29-10
- Fraction
 bleed, 27-14
 gravimetric, 21-5, 22-2, 24-17
 mass, 24-17
 mole, 14-6, 22-2, 24-17
 partial, 3-6, 9-2
 partial pressure, 22-2
 submerged, 15-15
 volumetric, 22-2, 24-17
- Fracture
 appearance transition temperature, 46-14
 strength, 46-3
 transition plastic temperature, 46-14
- Frame, 43-12
- Frame, inertial reference, 55-9
- Francis turbine, 18-22
- Fraud, 70-2 (ftn), 70-6
- Fraudulent act, 70-6
- Free
 area, 20-24
 -body diagram, 43-8, 43-20
 convection, 35-2
 field, 68-5
 -machining steel, 45-5, 63-4
 moment, 43-4, 43-9
 -piston Stirling engine, 29-12
 protection, 42-2
 pulley, 43-11
 rotation, 58-5
 -stream temperature, 36-2
 surface, 16-6
 vibration, 58-2
- Freedom, degree of, 47-3, 55-2, 58-19
- Freeze stat, 42-2
- Freezing point, 47-1 (ftn), 47-2
- Freon, 66-8
 replacement, *66-8*
- Frequency
 analysis, 9-7 (ftn), 60-11
 angular, 58-3
 crossover, 60-11
 cut-off, 60-10
 damped, 58-9, 60-2
 distribution, 11-9
 electrical, 67-4
 forcing, 58-10
 fundamental, spring, 52-8
 linear, 58-3
 natural, 9-6, 57-12, 58-3, 60-9
 polygon, 11-9
 response, 60-2 (ftn), 60-10, 60-11
- Fresnel integral function, 9-8 (ftn)
- Fretting corrosion, 21-12
- Friction, 56-6 (*see also type*)
 belt, 56-7
 brake, 62-12
 coefficient of, 15-12, 56-6, *56-7*
 factor
 chart, Moody, 17-6, *17-6*
 chart, Darcy, 17-5, *A-32-A-35*
 Fanning, 17-5 (ftn), 26-15, 26-18, 36-4 (ftn)
 flat, 56-6
 head, 18-5
 head loss, 17-4
 internal, angle, 46-7
 loss
 air duct, *20-12, 20-13*
 duct, 20-11, 20-14
 gas, 17-9
 hydraulic power, 19-4
 slurry, 17-11
 sprinkler, 65-7
 stack, 22-18
 steam, 17-9
 water, schedule-40 pipe, *A-36*
 power, 18-8, 29-3
 power, fan, 20-5
 pressure, 20-11

Italicized page numbers represent sources of data in tables, figures, and appendices.

- sideways, 56-21
- turbulent flow, 17-7
- Frictionless
 - adiabatic flow, 26-19
 - surface, 43-7
- Fried heat transfer efficiency factor, 36-22
- Froude number, 1-9 (tbl), 17-40
- Fuel
 - air ratio, 29-3
 - bound NO_x, 66-13
 - cell, 31-7 (*see also type*)
 - consumption
 - furnace, 40-6
 - specific, 29-3
 - vehicular, 56-20
 - diesel, 22-7
 - economy, 56-21
 - heat of combustion, *A-43*
 - injection, 29-2, 29-3
 - oil, 22-5, 22-6
 - oxygenated, 66-8
 - properties, 22-6
 - refuse-derived, 66-32
 - switching, 66-18
 - utilization, 29-22
 - waste, 22-4
- Fugitive
 - dust, 66-9
 - emission, 66-10, 66-35
- Full
 - arc admission, 27-16
 - bridge, 62-11
 - load value, motor, 67-11
 - wave symmetry, 9-7 (tbl)
 - wrap, 64-3
- Fully
 - amortized bond, 69-29 (ftn)
 - developed, 36-5, 36-7 (ftn)
 - turbulent flow, 16-8
- Fume exhaust hood, 39-4
- Function
 - circular transcendental, 6-2
 - error, 9-8, 11-6
 - first moment of, 9-6
 - forcing, 10-1, 58-10
 - hazard, 11-7
 - holomorphic, 8-1
 - hyperbolic, 6-4
 - integral, 9-8
 - cosine, 9-8
 - elliptic, 9-8 (ftn)
 - exponential, 9-8
 - Fresnel, 9-8 (ftn)
 - gamma, 9-8 (ftn)
 - sine, 9-8
 - objective, 61-12
 - of an angle, 6-2
 - of related angles, 6-3
 - path, 25-4
 - performance, 11-8
 - point, 25-4, 25-7
 - regular, 8-1
 - response, 59-1
 - second moment of a, 9-6
 - singularity, 59-3
 - symmetrical, 7-4
 - transfer, 60-3
 - trigonometric, 6-2
 - unit impulse, 10-6
 - unit step, 10-6
 - vector, 5-5
- Functionality, 45-15
- Functions
 - integral of combination, 9-2
 - of related angles, 6-3
- Fundamental
 - constants, inside front cover
 - frequency, spring, 52-8
 - speed, shaft, 58-15
 - theorem of calculus, 9-4
- Fundamentals of Engineering exam, 72-1, 72-3
- Funnel-flow bin, 64-5
- Furnace, 27-3, 40-5, 40-6
 - arc, 45-5
 - blast, 45-2
 - efficiency, 22-16
 - fluidized-bed, 27-3
 - induction, 45-5
 - pulverized-coal, 27-3
 - sorbent-injection, 22-5
 - reverberatory, 45-10
- Fusion
 - heat of, 47-2
 - metals, 63-11
- Future worth, 69-5
- F-waste, 66-3
- G**
- Gage
 - factor, 62-8, 62-8
 - pressure, 14-2, 15-2, 15-6 (ftn)
 - strain, 62-8, 62-9, 62-13
- Gain
 - characteristic, 60-10
 - crossover, 60-11
 - crossover point, 60-10
 - feedback, 60-4
 - forward, 60-4
 - heat, 41-1
 - margin, 60-11
 - overall, 60-4
 - sharing plan, 61-20
- Galvanic
 - action, 21-11
 - series, 21-11, 21-12
- Galvanizing, 63-14
- Gamma
 - integral function, 9-8 (ftn)
 - iron, 47-4
- Gangue, 45-2
- Garbage, 22-4, 66-12
- Gas
 - absorption, 66-21, 66-22
 - compressor, 32-1
 - constant, specific, 24-14
 - constant, universal, 24-13, 24-14
 - desorption, 66-22 (ftn)
 - diesel engine, 29-10
 - dynamics, 26-1
 - friction loss, 17-9
 - greenhouse, 66-11
 - high velocity, 26-1
 - ideal, 24-2
 - incompressible, 16-3 (ftn)
 - landfill, 66-11
 - liquefied petroleum, 22-7
 - manufactured, 22-7 (ftn)
 - mixture, 24-2, 24-17
 - natural, 22-11
 - noble, 21-2
 - noncondensing, 27-11
 - perfect, 24-15, 25-7
 - process, metal arc welding, 63-12
 - properties, 24-15 (tbl)
 - real, 24-2
 - specific heat, 22-2, 24-20
 - synthetic, 22-5, 22-8
 - table, 24-10
 - turbine, 29-14
 - welding, 63-11
- Gasification process, 29-15, 66-16
- Gasifier, 29-14
- Gasket blow-out, 53-14
- Gasohol, 22-7
- Gasoline, 22-6, 66-10, 66-10
- Gate, 63-8
 - blast, 20-18
 - valve, 16-11
- Gauge
 - diaphragm, 15-2
 - draft, 15-3 (ftn)
 - pressure, 15-2 (*see also Gage pressure*)
 - sheet metal, *A-123*
 - strain, 15-2
 - wire, *A-123*
- Gauss' hypergeometric equation, 10-5
- Gaussian distribution, 11-6
- Gauss-Jordan elimination, 4-2
- Gear (*see also type*)
 - bevel, 52-14
 - epicyclic, 57-6, *A-126*
 - helical, 52-12
 - hypoid, 52-14
 - involute, 52-11
 - motor, 18-10, 67-12 (ftn)
 - oil, 52-19
 - ratio, 57-5
 - set, 52-11, 57-4
 - spur, 52-10
 - train, 57-4
 - versus pinion, 52-11
 - worm, 52-14
- gees, 56-4 (ftn)
- General
 - contractor, 70-4
 - damages, 70-7
 - expense, 69-32
 - flow equation, 26-2
 - ledger, 69-33
 - partner, 70-1
 - term, 3-10
 - triangle, 6-5
- Generating line, 52-11
- Generation, internal heat, 34-14

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Generator, 67-10 (ftn), *67-14*
-absorber-heat-exchanger cycle, 33-7
electrical, 27-15
magnetohydrodynamics, 31-8
pollution, 66-4
steam, 27-4
thermionic, 31-9
thermoelectric, 31-9
- Genotoxin, 61-27
- Geometric
factor, 37-2
flux, 37-4
jerk, 57-10
mean, 11-10
mean radius, 57-3
sequence, 3-11
series, 3-11
similarity, 17-38
- Geopressured source, 31-7 (ftn)
- Geostationary orbit, 56-18
- Geothermal energy, 31-7
- Gerber line, 50-6
- Geysers, 31-7
- g*-force, 56-4 (ftn)
- Gibbs
phase rule, 47-3
theorem, 24-18
- Girth seam, 53-6 (ftn)
- Glass, 45-17, *45-18*
common, 45-17
fiber types 45-19
transition temperature, 45-17
- Glauconite, 21-14
- Global warming, 66-11
- Globe valve, 16-11
- Glow plug, 29-10 (ftn)
- Golf ball, 17-35
- Goodman line, 50-6
- Governing, 27-16
- Government bronze, 45-12
- Grade
bolt, 51-8
line, 16-9, 17-15
resistance, 56-19
roadway, 56-19
steel, 19-3 (ftn)
viscosity, 52-19
- Gradient
cash flow, 69-9
roadway, 56-19
search, 61-12
series cash flow, 69-4
temperature, 34-5
thermal, 34-5
vector, 8-5
velocity, 14-6
- Gratz number, 1-9 (tbl), 36-2
- Grain
growth stage, 47-9
properties, 47-8
size, 47-8
- Grand sensible heat ratio, 38-6, 41-4
- Granular activated carbon, 66-23
- Graphite fiber, 45-20
- Graphitization, 45-9
- Grashof number, 1-9 (tbl), 35-2
- Gravimetric
analysis, 22-2
fraction 21-5, 22-2, 24-17
- Gravitational
constant, 1-2, *56-18*
energy, 23-2
- Gravitation, Newton's law of, 56-18
- Gravity
acceleration of, 1-2
center of, 54-1
chimneys, 22-16 (ftn)
dam, 15-11 (ftn)
damper, 20-18
die casting, 63-9
drop hammers, 63-7
molding, 63-9
on earth, 1-2
specific, 14-4
- Gray
body, 37-3
cast iron, 45-9, 47-8
- Greek alphabet, *3-1*
- Greenhouse
effect, 31-2
gas, 66-11
- Green sand, 21-14, 63-8
- Gridded system, 65-1
- Grille, 20-18, 20-24
- Grinding, 63-5, 64-7
- Grip, 51-11
- Grit, 63-5 (tbl), 66-41
- Gross
electrical output, 27-1
heating value, 22-14
- Ground slab, 40-3
- Group
chemical, 21-2
dimensionless, 1-7, 1-9 (tbl)
X steel, 45-7
- Growth, exponential, 10-9
- Guard, 61-30
- Guide vane control, compressor, 32-2
- Gyration, radius of, 48-6, 54-2, *A-117*
- H**
- Hagen-Poiseuille equation, 17-7
- Half
-angle formula, 6-4
-bridge, 62-11
-power point, 60-10
-wave symmetry, 7-4, 9-7 (tbl)
-wrap, 64-3
-year convention, 69-3
- Hall effect, 31-8 (ftn)
- Hammer
forging, 63-7
water, 17-31
- Hard
material, 46-16
steel, 47-7
surfacing, 63-14
- Hardenability test, 47-7
- Hardening
age, 45-8 (ftn), 45-11, 47-9
aluminum, *45-12*
of non-allotropic alloys, 47-9
precipitation, 45-11, 47-9
strain, 46-4
surface, 47-10
- Hardness
carbonate, 21-14
correlations, *46-14*
noncarbonate, 21-14
number, 46-12
permanent, 21-14
red, 63-4
red/hot, 45-7 (ftn)
scale, Moh, *46-12*
steel, *47-7*
steel maximum, 47-7
temporary, 21-14
test, 46-12, *46-13*
total, 21-14
water, 21-13
- Hardwood, 45-16
- Hardy-Cross method, 17-20, 49-17
- Harmonic, 58-18
cam profile, 57-10
frequency, fundamental, 52-8
motion, simple, 58-2, *58-6*
sequence, 3-11
series, 3-11
terms, 9-6
test, vibration, 58-20
- Hastelloy, 45-13
- Haulage rope, 64-1
- Hazard
analysis, 61-27
assessment by risk analysis, 61-27 (ftn)
function, 11-7
- Hazardous
air pollutant, 66-3
material, 66-19
waste, 66-3, 66-20, 66-31
- Hazen-Williams
constant, *A-31*
constant, sprinkler, *65-7*
equation, 17-7, 65-7
- Hazmat, 66-19
- Head, 15-4 (ftn), 18-5
absorption (boiler), 27-4
acceleration, 18-2, *18-3*
added, 17-14
adiabatic, 32-5
atmospheric, 18-5 (ftn)
churn, 18-5
effective, 17-16, 18-5
end, 29-2
extracted, 17-14
friction, 18-5
impact, 16-5
loss, 17-4
effect of viscosity, 17-10
slurry, 17-11
overload, 18-15
polytropic, 32-5
pressure, 18-5 (ftn)
pressure vessel, 53-4
pulley, 64-9

Italicized page numbers represent sources of data in tables, figures, and appendices.

- rated, 18-15
 shutoff, 18-15
 stack effect, 22-17
 static discharge, 18-5
 static suction, 18-5
 total, 16-3
 total dynamic, 18-6
 vapor pressure, 18-5 (ftn)
 velocity, 18-5
- Header-type feedwater heater, 27-14
- Head-on machine, 31-4
- Health risk assessment, 61-27
- Heat
 capacity, 24-7
 content, 24-5
 -driven refrigeration cycle, 33-6
 duty, 36-14
 exchanger, 27-10, 36-10 (*see also type*)
 exchanger designations, TEMA, 36-11
 exchanger effectiveness, 36-20, A-104, A-105
 flow, transient, A-92-A-97
 flux, 35-3, 36-5
 gain, 40-4, 41-1
 generation, occupant, 39-3
 graphically finding, 25-4
 latent, 24-8, 24-9
 latent, water, 24-9
 load, 27-11, 36-14, 38-12
 metabolic, 39-3
 of combustion, 22-14, A-43
 of formation, 21-9
 of fusion, 47-2
 of steel, 45-4
 pipe, 34-20
 pump, 33-2
 rate, 27-5, 28-2
 ratio, sensible, 41-3
 recovery steam generator, 29-20
 rejector, 29-12
 release rate, 66-32
 removal efficiency factor, 31-2
 reservoir, 25-10
 sensible, 24-8
 specific, 24-7, 24-8, 34-3
 specific, gas, 24-20
 tape, 34-20
 total, 24-5
 tracing, 34-20
 transfer
 coefficient, 35-2, 36-15, 40-2
 coefficient, convective, 34-6
 coefficient, overall, 36-15
 coefficient, radiant, 37-4
 factor, 36-22
 fluid, 31-2, 36-22
 unit, 36-20 (ftn)
 transmittance, overall, 34-6
 treatment, aluminum, 45-12
 treatment, cast iron, 47-8
- Heater (*see also type*)
 air, 27-15
 feedwater, 27-13
- Heating
 district, 29-21
- load, 40-1
 sensible, 38-8
 space, 29-21, 33-2
 value, 22-14
 with dehumidification, 38-11
 with humidification, 38-10
- Heats, ratio of specific, 26-3
- Heavy
 damping, 58-9
 -duty coil, 36-13
 hydrogen, 21-2
 metal, 21-2
- Heel (dam), 15-11
- Height, 2-2
 compressed, 52-5
 critical, pressure vessel, 53-5 (ftn)
 of packing, 66-40
 of transfer unit, 66-40
 solid, 52-5
 waviness, 2-4
- Heisler chart, 34-13, A-95-A-97
- Helical
 compression spring, 52-4
 extension spring, 52-8
 gear, 52-12
 torsion spring, 52-9
- Heliostat, 31-3
- Helix, 7-12, 7-12
 angle, 52-12
 direction, 52-5
 pitch, 7-12
 thread angle, 51-13
- Hematite, 45-2
- Henry's law, 21-7, 66-39
 constant, 66-39
- HEPA (*see* High-efficiency particulate arrester)
- Hess' law, 21-9
- Hexadecimal system, 12-2
- HFC-134a, A-64, A-81
- Hideout, 21-11
- Hierarchy, need, 61-28
- High
 -alloy austenitic stainless steel, 45-9
 -alloy steel, 45-5
 -carbon steel, 45-5
 -efficiency particulate arrester, 39-6
 energy rate forming, 63-11
 -pass filter, 60-10
 -performance power system, 29-22
 -pressure turbine, 27-8
 -side equipment, 33-7
 -speed steel, 63-4
 -strength steel, 45-5
 -temperature advanced furnace, 29-22
 -temperature reservoir, 25-10
 velocity gas, 26-1
 -velocity system, 20-17
- Higher heating value, 22-14
- Hilbert-Morgan equation, 36-8
- Hinge, 43-10, 49-18
- Histogram, 11-8
- Hobby, 69-12 (ftn)
- Hoisting cable, 64-1
- Hole, tap, 15-2
- Holographic testing, 46-11
- Holomorphic function, 8-1
- Holonomic coordinate, 55-2
- Homogeneous
 circuits, law of, 62-7
 differential equation, 10-1, 10-2
 function, 59-2
 linear equation, 3-7
 unit system, 1-2
- Homologous
 fan, 20-9
 pump, 18-12, 18-18
- Honing, 63-5, 63-14
- Hood
 control velocity, 39-4
 fume exhaust, 39-4
- Hooke's law, 46-2, 49-2, 52-2
- Hoop stress, 51-3, 51-4
- Hopper, 64-5
- Horizon, 69-3
- Horizontal
 -axis machine, 31-4
 shear, 49-10
- Horsepower, 23-5
 aero, 17-34
 air, 20-4
 boiler, 22-16, 27-4
 conversions, 23-5
 flywheels, 57-2
 hydraulic, 17-14, 18-6, 18-7
 rotating members, 52-10
 shaft, 51-13
- Hose, hydraulic, 19-2
- Host ingredient, 47-1
- Hot
 dry rock source, 31-7 (ftn)
 -end drive, 29-14
 hardness, 45-7 (ftn)
 reserve, 27-15
 well, 27-11, 27-14
 windbox, 29-23
 -wire anemometer, 17-22
 working, 47-9, 63-6 (tbl), 63-7
- Hourglass failure, 46-7 (ftn)
- Hub, 51-6, 57-2
- Human
 error, 62-2
 factors, 61-29
- Humectant, 66-10 (ftn)
- Humidification, 38-8, 39-2
 efficiency, 38-7
 load, 38-8
 steam, 38-10
- Humidistat, 42-1
- Humidity, 38-2
- Hurwitz
 criterion, 60-12
 test, 60-12
- HVAC, 42-1
- Hybrid throttle pressure operation, 27-16 (ftn)
- Hydrashaker, 58-21
- Hydrated molecule, 21-4
- Hydration, 21-4, 21-7

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Hydraulic
 accumulator exponents, *19-6*
 brake, 52-16 (ftn)
 control valve, 19-2
 cyclone, 64-10
 cylinder, 19-6
 diameter, 16-6, 17-9, 20-14 (ftn), 36-8
 fluid, 19-2
 grade line, 16-9, 17-15
 horsepower, 17-14, *18-6*, *18-7*
 jack, 15-14
 line materials, 19-2
 loading, 66-41
 power, 18-6, 19-1
 press, 15-14
 pump, 19-4
 radius, 7-1, 16-6, *A-21*
 ram, 15-14, 19-6
- Hydraulics, 17-2
- Hydrocarbon, 22-1
 NPSHR, *18-20*
 specific gravity, *A-18*
 vapor pressure, *A-17*
- Hydrochloric acid, 66-4
- Hydroclone, 64-10
- Hydrocyclone, 64-10
- Hydrodynamics, 17-2
- Hydrogen
 available, 22-3
 damage, 21-11
 embrittlement, 21-11, 53-4
 heavy, 21-2
 peroxide, 45-13 (ftn)
- Hydrogenation, 66-16
- Hydrometer, 14-4
- Hydro-pneumatic accumulator, 19-5
- Hydrostatic
 head, 15-4
 moment, 15-11
 paradox, 15-4
 pressure (*see* Pressure)
 pressure test, 53-17
 resultant, 15-6
 torque, 15-11
- Hydrostatics, 17-2
- Hydrothermal source, 31-7 (ftn)
- Hygroscopic, 39-2
- Hygrostat, 42-1
- Hyperbola, 7-11, *7-11*, 7-12
- Hyperbolic
 function, 6-4
 derivative, 8-2
 integral, 9-2
 identity, 6-5
 radian, 6-5
- Hypereutectoid steel, 47-5
- Hypergeometric
 distribution, 11-5
 equation, Gauss', 10-5
- Hypersonic, 14-14
- Hypocycloid, 7-3
- Hypoeutectic cast iron, 47-5
- Hypoeutectoid steel, 47-5
- Hypoid gear, 52-14
- Hypothesis, 21-4, 52-2
- Hypothesis test, 11-12
- Hysteresis, 62-5 (ftn)
- I**
- Ice point, 62-6
- Ideal
 combustion, 22-9
 fluid, 14-2
 gas, 24-2
 gas, property, 24-15
 machine, 23-6
 radiation, 37-1
 reaction, 21-6
 spring, 52-2
 yield, 21-7
- Idempotent law, 11-1
- Identity
 hyperbolic, 6-5
 laws, sets of, 11-1
 logarithm, 3-5
 matrix, 4-1
 trigonometric, *6-2-6-5*, 6-3
- Idler gear, 57-4
- Ignitable substance, 66-3
- Ignition, 29-2
- Ignition temperature, 22-8
- Illegitimate error, 62-2
- Illuminance, 68-2
 recommended, *68-3*
- Illumination, 68-2
- Imaginary number, 3-1
- Immiscible liquid, 15-12
- Impact, 56-15
 central, 56-16
 direct, 56-16
 eccentric, 56-16
 elastic, 56-15
 endoergic, 56-15
 energy, 16-4
 energy test, 46-13
 factor, 16-4
 head, 16-5
 inelastic, 56-15
 loading, 49-7
 noise, 68-3
 oblique, 56-16
 plastic, 56-15
 test, pressure vessel, 53-5, 53-6
 tube, 16-4
- Impactor forging, 63-8
- Impedance, 67-5
- Impeller, 18-4, 18-11, 64-12
- Impending motion, 56-6
- Implicit differentiation, 8-4
- Impulse, 56-12
 fluid, 17-27
 function, 10-6
 -momentum principle, 17-26, 56-13, 56-14
 noise, 68-3
 shock, 58-19
 specific, 26-8
 total, 26-8
 turbine, 17-29, 18-20, 18-21, 27-8
 unit, 59-2
- Impulsive force, 56-13
- Incentive plan, wage, 61-20
- Inches of water gage, 20-2
- Incineration, 22-4
 liquid, 66-31
 MSW, 66-31
 sludge, 66-34
 soil, 66-34
- Incinerator, 66-28 to 66-31
- Inclined plane, 56-9
- Income tax, 69-24
- Incomplete combustion, 22-11
- Incompressible gas, 16-3 (ftn)
- Inconel, 45-13
- Inconsistent system, 3-7
- Incremental
 analysis, 69-17
 cost, 69-31
- Indefinite integral, 9-1 (ftn), *9-1*, *9-2*, 9-4, *A-10*
- Independent
 event, 11-3
 variable, 3-2
- Indeterminacy, degree of, 44-1
- Indeterminate
 statics, 44-1
 truss, 44-6
- Index
 roughness height, 2-4
 spring, 52-2 (ftn), 52-4
 viscosity, 14-9, 19-2 (ftn), *A-20*
- Indicated
 power, 29-3
 properties, 29-3
 specific fuel consumption, 29-3
- Indicator
 card, 29-8
 drawing, 29-8
- "Indifference quality level," 61-25
- Indirect
 coal-fired turbine, 29-15
 -condensing tower, 38-13
 injection, 29-3
 manufacturing expense, 69-32
- Indoor design condition, 39-2
- Induced
 draft, 22-16
 drag, 17-34
- Inductance, 59-7, 67-6
- Induction
 furnace, 45-5
 hardening, 47-10
 motor, 18-9, 67-12
 ratio, 20-24
 reactance, 67-6
 transducer, 62-4
- Inductor, 67-6
- Industrial exemption, 72-1
- Inelastic
 impact, 56-15
 strain, 46-2
- Inertance, fluid, 59-7
- Inert gas welding, 63-12
- Inertia, 54-1
 area moment of, 48-3, *A-117*
 mass moment of, 54-2, *A-125*

Italicized page numbers represent sources of data in tables, figures, and appendices.

- polar moment of, 48-5, 51-13
 principal moment of, 48-7
 product of, 48-6, 54-2
 resistance, vehicle, 56-19
 thermal, 40-5
 vector, 54-1, 56-5 (ftn)
- Inertial
 force, 54-1, 56-5
 frame, 55-9
 resisting force, vehicle, 56-19
 separator, 66-26
- Infant mortality, 11-7, 61-11
- Infiltration, 39-1, 39-2
 energy to warm, 40-4
 loss, 40-1
- Infinite series, 3-11 (ftn)
- Inflation, 69-39
- Inflection point, 7-2, 8-2, 49-16
- Influence diagram, 43-10
- Infrared
 incineration, 66-31
 testing, 46-11
- Initial
 condition, 58-4
 tension, spring, 52-8
 value, 9-3, 10-1, 60-7
- Initiator, 45-15
- Injection
 molding, 63-10
 sorbent, 66-38
 steam, 29-14
 well, 66-28
- Injured party, 70-5
- Inlet
 pressure, net positive, 18-2 (ftn)
 vane, 20-3
- Inline sampling, 21-11
- Innovative method, 66-17
- Insensitivity, 11-13, 62-2
- Insertion loss, 68-9
- Inside design temperature, 41-1
- Insolation, 31-2
- Instability, 60-12, 62-2
- Instantaneous
 center, 55-12, 55-13
 cooling load, 41-2
 heat gain, 41-1
- Instrument, coefficient of, 17-22
- Insulated
 pipe, 34-8
 tip, 34-17
- Insulating properties, building materials,
A-111
- Insulation
 pipe, 34-9
 thermal properties, *34-10*
 thickness, critical, 34-10
- Insurance, 70-7
- Intake stroke, 29-2
- Intangible property, 69-20 (ftn)
- Integer programming, 61-12
- Integral
 convolution, 10-7
 cosine function, 9-8
 definite, 9-1 (ftn), 9-4
 double, 9-3
 elliptic function, 9-8 (ftn)
 exponential function, 9-8
 Fresnel function, 9-8 (ftn)
 gamma function, 9-8 (ftn)
 indefinite, 9-1, 9-4, *A-10*
 of combination of functions, 9-2
 of hyperbolic function, 9-2
 of transcendental function, 9-1
 reinforcement, 53-12
 sine function, 9-8
 triple, 9-3
- Integrand, 9-1
- Integrated cycle, 29-22
- Integrating factor, 10-2
- Integration, 9-1
 by parts, 9-2
 by separation of terms, 9-3
 constant of, 9-1, 10-1
- Intensifier, 32-2
- Intensity
 luminous, 68-2
 sound, 68-4
- Intensive property, 24-4
- Interaction factor, 37-2
- Intercept form, 7-5
- Intercooling, 29-19
- Intercooling, compressor, 32-7
- Interest
 compound, 69-11
 rate, effective, 69-5, 69-28
 rate, nominal, 69-28
 simple, 69-11
- Interfacial area, 66-40
- Interference, 51-5
 factor, 31-5
 fit, 51-5
- Intergranular, 21-12
 attack, 21-11
 corrosion, 21-10
 stress corrosion cracking, 30-2
- Intermediate
 column, 51-3
 gear, 57-4
 metals, law of, 62-7
 -pressure turbine, 27-8
 temperatures, law of, 62-7
- Internal
 energy, 23-4, 24-5
 force, 43-2, 43-13, 56-2
 friction, angle, 46-7, 56-7
 fuel reforming cycle, 31-8
 gear, 57-4
 heat gain, 40-4, 41-2
 heat generation, 34-14
 rate of return, 69-12
 work, 23-1, 46-6
- International standard atmosphere, *A-88*
- Intern engineer, 72-1 (ftn)
- Interpolating polynomial, Newton's, 13-3
- Interpolation, nonlinear, 13-2, 13-3
- Interpolymer, 45-13
- Intersecting lines, 2-1
- Intersection
 line, 7-6
 set, 11-1
- Interval
 confidence, 61-16 (ftn)
 elevator, 64-4
- Intrinsic waste, 66-3
- Invar, 45-13
- Inventory, 69-37
- Inverse
 function, 6-4
 Laplace transform, 10-6
 lever rule, 38-5
 matrix, 4-5
 -square field, 56-17
- Inversion
 curve, 25-3
 Fourier, 9-6
 point, 25-3
 temperature, 25-3, *25-3*
- Invert emulsion, 19-2 (ftn)
- Investment
 casting, 63-9
 credit, 69-25
 return on, 69-11, 69-14
- Involute gear, 52-11
- Ion exchange, 21-14, 21-15
- Ionic concentration, 21-8
- Iron
 allotropes of, 47-4
 alpha, 47-4
 beta, 47-4
 carbide, 47-5
 -carbon diagram, 47-4
 cast, *45-9, 45-10, 47-5*
 delta, 47-4
 gamma, 47-4
 loss, 67-15
 refining, *45-3*
 wrought, 45-10
- Irradiance, 68-2
- Irrational number, 3-1
- Irreducible factor, 69-2
- Irreversibility, 25-12
- Irreversible process, 25-3
- ISA nozzle, 17-26 (ftn)
- Isenthalpic curve, 25-3
- Isentropic
 compressibility, 14-13, 24-9
 compression ratio, 29-4
 compressor, 29-17, 32-3
 efficiency, pump, 27-6
 efficiency, turbine, 27-8
 flow, 26-3
 flow factor, *A-84, A-85*
 pressure, 26-13
 pressure ratio, 29-4
 process, 25-2, 25-8, 25-9
- Isobar, 24-3
- Isobaric
 compressibility, 24-9
 process, 25-2
- Isochoric process, 25-2
- Isokinetic test, 66-20
- Isolated system, 25-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Isolation
 degree of, 58-12
 efficiency, 58-12
 from active base, 58-14
 material, 58-13
 vibration, 58-12
- Isometric
 process, 25-2
 view, 2-3
- Isometry, 7-3
- Isopiestic equilibrium, 14-9
- Isoprene latex, 45-13
- Isostatic
 molding, 63-10
 polymer, 45-16
- Isotherm, 24-3
- Isothermal
 compressibility, 14-13, 24-9
 compression, 15-12
 flat plate, 36-3
 flow with friction, 26-17
 process, 25-2
 transformation diagram, 47-6
- Isotope, 21-2 (ftn)
- Iteration, fixed-point, 13-2
- Izod test, 46-15
- J**
- Jack
 hydraulic, 15-14
 power, 52-22
- Jacketed pipe heat exchanger, 36-10
- J. B. Johnson formula, 51-3
- Jerk, 57-10
- Jet
 condenser, 27-11 (ftn)
 force on blade, 17-29
 force on plate, 17-28
 propulsion, 17-27
 pump, 18-2
- Job
 cost accounting, 69-36
 enlargement, 61-28
 enrichment, 61-28
 flexibility, 61-28
- Jockey pump, 65-3
- Joint, 53-2 (ftn)
 efficiency, 16-10, 51-11, 53-8
 flanged, 53-14
 lap, bolted, 51-10
 probability, 11-3
 quality factor, 16-10
 weld, efficiency, 53-9
- Joints, method of, 43-14
- Jominy end-quench test, 47-7
- Joule, 1-5
 cycle, 29-15
 equivalent, 23-1
 -Kelvin coefficient, 25-3
 -Thompson coefficient, 25-3
- Joule's
 constant, 23-1, 24-6
 law, 23-4
- Journal, 52-20, 69-33
 bearing, 52-21
 bearing correlation, A-124
- Judgment factor, 69-2
- Jump, follower, 57-11
- K**
- Kalman's theorem, 60-14 (ftn)
- Kelvin
 day, 40-5
 -Planck statement, 25-11
 scale, 24-5
- Kepler's law, 56-18
- Kern, 49-12
- Kernal, 49-12
- Killed steel, 45-5
- Kinematic
 Stirling engine, 29-12
 viscosity, 14-8, 16-7
- Kinetic
 energy, 16-2, 23-3
 friction, angle of, 64-5
 gas theory, 24-15
 pump, 18-2
- Kinetics, 56-2
- Kirchhoff's
 radiation law, 37-1
 voltage law, 67-3
- K-monel metal, 45-13
- Knives, cutting, 64-7
- Knoop hardness, 46-12
- Knudsen number, 1-9 (tbl)
- Kutta-Joukowski theorem, 17-34
- kVA rating, 67-12
- K-waste, 66-3
- L**
- Labor
 direct, 69-32
 variance, 69-36
- Lagging circuit, 67-7
- Lagrange stream function, 17-3
- Lagrangian interpolating polynomial, 13-2
- Lag, thermal, 40-5
- Lamé formula, 19-3
- Lamé's solution, 51-4
- Laminae, 16-7
- Laminar flow, 16-7, 17-5, 36-5, 36-10
- Lance, oxygen, 45-3
- Land
 ban, 66-20
 tooth, 52-10
- Landfill, 66-12
 gas, 66-11
 liner, 66-34
- Lang lay, 64-2
- Langley, 31-2 (ftn)
- Lanthanide, 21-2
- Lanthanon, 21-2
- Lanthanum barium copper oxide, 45-18
- Lap
 joint, 63-13
 joint, bolted, 51-10
- Laplace transform, 10-5, 10-6, A-11
- Lapping, 63-5, 63-14
- Laser machining, 63-6
- Last-in, first-out, 69-37
- Latent heat, 39-3
 fusion, 24-9
 sublimation, 24-9
 vaporization, 24-9
 water, 24-9
- Lateral
 buckling, 49-18
 strain, 46-4
- Latex, isoprene, 45-13
- Latus rectum, 7-10, 7-11
- Law
 affinity, 18-17, 20-8
 Amagat's, 24-17
 Archimedes', 15-14
 associative, addition, 3-3
 associative, multiplication, 3-3
 Avogadro's, 24-13
 Boyle's, 25-7
 Charles', 25-7
 commutative, addition, 3-3
 commutative, multiplication, 3-3
 corresponding state, 24-19
 Dalton's, 22-13, 24-17
 distance-squared, 68-3
 distributive, 3-3
 Dulong and Petit, 24-7
 fan, 20-8
 Fourier's, 34-5
 Henry's, 21-7, 66-39
 Hess', 21-9
 Hooke's, 46-2, 49-2, 52-2
 Joule's, 23-4
 Kepler's, 56-18
 Kirchhoff's radiation, 37-1
 Newton's first, 56-4
 Newton's, of gravitation, 56-18
 Newton's second, 56-4
 Newton's third, 56-5
 of areas, 56-18
 of conservation of energy, 23-1
 of convection, Newton's, 36-2
 of cooling, Newton's, 10-10, 34-11
 of cosines, 6-5, 6-6
 of definite proportions, 21-3
 of homogeneous circuits, 62-7
 of intermediate metals, 62-7
 of intermediate temperatures, 62-7
 of multiple proportions, 21-3
 of orbits, 56-18
 of periods, 56-18
 of sines, 6-5, 6-6
 of tangents, 6-5
 of thermodynamics, first, closed system, 25-4
 of thermodynamics, first, open system, 25-5
 of thermodynamics, second, 25-11
 Pascal's, 15-4
 radiation conservation, 37-1
 second, thermodynamics, 24-7 (ftn)
 similarity, 18-18
 Stefan-Boltzmann, 37-2
 Stoke's, 17-35
 third, thermodynamics, 24-6
 zeroth, thermodynamics, 24-4
- Layer, boundary, 16-8 (ftn), 36-2
- Layout, facilities, 61-14

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Lay, wire rope, 64-2
 L-D process, 45-3
 Leachate, 66-12
 Leaching, selective, 21-11
 Lead, 66-12
 -acid battery, 31-10
 angle, 52-22
 ratio, 52-14
 screw, 52-22
 Leading circuit, 67-7
 Leaf, 52-10
 Leak
 detection, 66-10
 points, 27-11 (ftn)
 Leakage, duct, 20-18
 Lean-burn engine, 29-10
 Learning curve, 69-42, *69-42*
 Least
 radius of gyration, 48-6
 significant bit, 12-1, 12-4
 significant digit, 12-1
 squares method, 11-13
 Ledger account, 69-33
 Legendre equation, 10-5
 Legionnaire's disease, 66-5
 Length, 2-2
 arc, by integration, 9-5
 characteristic, 26-9, 34-3, 35-2, 36-8
 effective, column, 51-2
 equivalent, 17-11, *17-12, A-131*
 air, *20-13*
 fitting, *A-37, A-131*
 of the line of action, 52-11
 of tube, 36-15
 thermal entry, 36-5
 Lethal substance, 53-3
 Letter of agreement, 70-3
 Level
 acceptance quality, 61-25
 confidence, 11-11, 61-16
 indifference quality, 61-25
 sound power, 68-7
 sound pressure, 68-6
 Lever, 43-10, 59-5
 effectiveness, 15-14
 efficiency, 15-14
 ratio, 58-8
 rule, 38-5, 47-2
 Leverage, 69-34
 Lewis
 beam strength theory, 52-13
 form factor, 52-13 (ftn)
 number, 1-9 (tbl)
 L'Hôpital's Rule, 3-9
 Liability
 account, 69-33
 current, 69-34
 in tort, 70-5
 Licensing, 72-1
 Life
 -cycle analysis, 61-27
 -cycle cost, 69-20
 economic, 69-19
 extension, 29-23
 fatigue, 46-9
 pump, 19-5
 service, 69-20
 tool, 63-5
 Lifeline rate, 67-7 (ftn)
 Lifer, 57-10
 Lift, 17-32
 cam follower, 57-11
 coefficient of, 17-32
 landfill, 66-12
 rotating cylinders, 17-33
 valve, 16-12
 Light
 damping, 58-9
 heat gain from, 40-4
 metal, 21-2
 quantity of, 68-2
 -sensitive detector, 62-4
 -water reactor, 30-1
 Lignin, 45-16
 Lignite, 22-4
 Limit, 3-9 (*see also type*)
 average outgoing quality, 61-26
 confidence, 11-11
 control, 61-22
 elastic, 46-2
 endurance, 46-9
 lower explosive, 39-5
 of reinforcement, 53-12
 proportionality, 46-2
 simplifying, 3-9
 surge, 32-8
 value, threshold, 39-5
 viscosity, 52-20
 wear design of gears, 52-14
 Limited partner, 70-2
 Limiting
 current, sensor, 62-4
 reactant, 21-7
 value, 3-9
 Line, 6-1 (ftn), 7-3
 balancing, 61-18
 centroid, 48-2
 coil load, 38-8
 condition, turbine, 27-8
 critical, 47-4
 current, 67-9
 diagram, 59-3
 energy grade, 16-9, 17-15
 equipotential, 17-3
 eutectic, 47-3
 failure, 50-6
 generating, 52-11
 Gerber, 50-6
 Goodman, 50-6
 hydraulic grade, 16-9, 17-15
 intersection, 7-6
 liquidus, 47-1
 load, coil, 38-8
 normal vector, 8-6
 of action, 5-1, 43-2, 52-11
 pressure, 52-11
 Rayleigh, 26-19
 refrigerant, 33-9
 saturated, 24-3
 Smith, 50-7 (ftn)
 Soderberg, 50-6
 solidus, 47-1
 straight, 7-4
 voltage, 19-5 (ftn)
 Lineal distance, 40-4 (ftn)
 Linear
 acceleration, 55-4
 actuator, 19-6
 component, 58-2, 59-1
 damping, 58-9
 differential equation, 10-1
 equations, 3-7
 expansion, coefficient of, 49-3
 first-order, 10-2
 force system, 43-4
 frequency, 58-3, 67-4
 impulse, 56-12
 model, 61-2
 momentum, 56-2
 motion, 55-2
 motor, 19-6 (ftn)
 programming, 61-12
 regression, 11-13
 second-order, 10-3
 spring, 23-2, 23-3 (ftn)
 system, 55-2
 variable differential transformer, 62-4
 watt density, 40-4 (ftn)
 Linearity theorem, 10-6
 Liner, 45-20, 66-34
 Lines
 angle between, 6-1
 intersecting, 2-1
 perpendicular, 2-1
 Lining, brake, 52-16
 Linz-Donawitz process, 45-3
 Liquefied petroleum gas, 22-7
 Liquid
 aromatic, 14-9 (ftn)
 -dominated reservoir, 31-7
 fuel, 22-5
 immiscible, 15-12
 metal, 36-7
 metal fast breeder reactor, 30-1 (ftn)
 penetrant testing, 46-11
 properties, *A-15, A-16*
 saturated, 24-2
 subcooled, 24-2
 -vapor mixture, 24-2, 24-12
 volatile, 14-9, 21-7 (ftn)
 Liquidated damages, 70-7
 Liquidus line, 47-1
 Liter, 1-6
 LMTD
 correction factor, 36-14, *A-101, A-102*
 method, 36-20
 Load
 air conditioning, 41-1
 cell, 62-12
 coil, 41-1 (ftn)
 cooling, 41-1
 curve, 27-15
 dead, 43-4
 -deflection equation, 52-5
 distributed, 43-4, 43-6

Italicized page numbers represent sources of data in tables, figures, and appendices.

- dominant moving, 49-18
- duration curve, 27-15
- elongation curve, 46-1
- factor, 27-15
- heat, 27-11, 36-14, 38-12
- heating, 40-1
- humidification, 38-8
- line, coil, 38-8
- moving, 49-18
- number, bearing, 52-21
- overhung, 18-10
- pickup, 40-5
- proof, bolt, 51-8, 51-12
- refrigeration, 41-1 (ftn)
- tower, 38-12
- Loading
 - axial, 49-11
 - boot, 64-9
 - chemical, 66-41
 - concentric, 49-11
 - error, 62-2
 - factor, 31-9, 66-12
 - hydraulic, 66-41
 - impact, 49-7
 - pump shaft, 18-10
- Loan, 69-39
- Lobe, cam, dynamics, 57-12
- Local
 - buckling, 49-18
 - control computer, 42-5
 - losses, 17-11
- Locus of points, 7-2
- Logarithm, 3-5
 - identities, 3-5
- Logarithmic
 - decrement, 58-9
 - mean area, 34-8
 - mean temperature difference, 36-14
- Longitudinal
 - fin, 34-18
 - stress, 51-4
 - wave, 68-4
- Long stress, 51-4
- Long-term liability, 69-34
- Loop
 - gain, 60-4
 - pipe, 17-20
 - primary/secondary, 30-1
 - system, 65-1
 - transfer function, 60-4
- Loss
 - coefficient, 17-12, 17-12, 17-13, 20-14
 - air, 20-13
 - branch, 20-16
 - combustion, 22-15
 - duct friction, 20-11
 - electrical machine, 67-15
 - entrance, culvert, 17-19
 - factor, pulley, 43-11
 - friction, air duct, 20-12, 20-13
 - friction, sprinkler, 65-7
 - infiltration, 40-1
 - insertion, 68-9
 - journal bearing, 52-21
 - local, 17-11
 - method, 22-16
 - of coolant accident, 30-2
 - transmission, 40-1, 68-9, A-136
 - wax process, 63-9
 - zero-length, 20-15
- Lot
 - quality, 61-25
 - tolerance percent defective, 61-25
- Loudness, 68-4, 68-4, 68-8
- Low
 - alloy steel, 45-5
 - carbon steel, 45-5
 - excess-air burner, 66-34
 - NOx burner, 66-35
 - pass filter, 60-10
 - pressure turbine, 27-8
 - side equipment, 33-8
 - sulfur coal, 22-4
 - temperature reservoir, 25-10
 - velocity system, 20-17
- Lower
 - bound, 9-4
 - control limit, 61-23
 - critical point, 47-4
 - explosive limit, 39-5
 - heating value, 22-14
- Lubarsky-Kaufman correlation, 36-7
- Lubricant, 52-19
- Lubricating oil, 52-20
- Lumber, oven-dry, 45-17 (ftn)
- Lumen, 68-1
- Luminance, 68-3
- Luminous
 - efficacy, 68-2
 - efficiency, 68-2
 - emittance, 68-2
 - flux, 68-1
 - intensity, 68-2
- Lump coal, 22-4
- Lumped
 - mass, 59-4
 - parameter method, 34-12
- Lump-sum fee, 70-4
- Lux, 61-30 (ftn)
- M**
- Mach
 - angle, 26-11 (ftn)
 - number, 1-9 (tbl), 14-14
 - wave, 26-11 (ftn)
- Machine, 43-20
 - electric, 67-14
 - ideal, 23-6
 - real, 23-6
 - safeguard, 61-30
 - worker system, 61-29
- Maclaurin series, 8-7 (ftn)
- Macrofouling, 27-12
- Macroreticular synthetic resin, 21-15
- Magnaflux, 46-11
- Magnaglow, 46-11
- Magnesia, 22-3 (ftn), 34-9 (ftn)
- Magnetic
 - flowmeter, 17-22
 - particle testing, 46-11
 - pulse forming, 63-11
- Magnetite, 45-2
- Magnetohydrodynamics, 31-8
- Magnification factor, 58-10, 58-12
- Magnus effect, 17-34
- Maintenance
 - motivation factor, 61-28
 - preventative, 61-10
- Major
 - axis, 7-11
 - source, pollution, 66-4
- Make-up
 - pump, 65-3
 - water, 21-15
- Malleable cast iron, 45-10, 47-8
- Management
 - by-objectives, 61-29
 - science, 61-1
 - systems modeling, 61-1
- Maney formula, 51-12
- Manganese bronze, 45-12 (ftn)
- Man-machine system, 61-29
- Manometer, 15-2, 15-3
- Mantissa, 3-5
- Manufactured gas, 22-7 (ftn)
- Manufacturing cost, 69-32
- Manway, 53-11
- MAPP gas, 63-11
- Mapping function, 7-3
- Maraging steel, 45-5 (ftn)
- Margin
 - boiling-point, 66-10
 - gain, 60-11
 - of safety, 50-1
 - phase, 60-11
- Market value, 69-23
- Martempering, 47-7
- Martensite, 47-7
- Martensitic stainless steel, 21-11 (ftn), 45-8
- Masking, 66-37
- Masonry
 - density, 15-12
 - M-factor, 40-5
- Mass, 1-1, 24-4, 54-1
 - burn, 66-31
 - center of, 54-1
 - control, 25-1
 - flow bin, 64-5
 - fraction, 24-17
 - lumped, 59-4
 - moment of inertia, 54-2, A-125
 - transfer coefficient, 66-40
 - yield, 66-33
- Material
 - anisotropic, 5-1, 34-2
 - breach, 70-5
 - conditions monitoring, 61-27
 - handling, 64-1
 - pipe, 16-9
 - recovery facility, 66-32 (ftn)
 - refractory, 37-4
 - spring, 52-3, 52-3, 52-4, 52-4
 - variance, 69-36
- Mathematical programming, 61-12

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Matrix, 4-1, 4-2 (*see also type*)
 algebra, 4-3
 inverse, 4-5
 multiplication, 4-4
 order, 4-1
 transformation, 5-3
- Matter
 mineral, 22-3
 volatile, 22-4
- Maximum
 flame temperature, 22-15
 fluid velocity, 17-3
 normal stress theory, 50-1
 point, 8-2
 shear stress theory, 46-8, 50-3
 strain theory, 50-3
 value, sinusoid, 67-5
 velocity in pipe, 17-3
- Maxwell-Boltzmann distribution, 24-17
- MBh, 27-4 (ftn), 34-5 (ftn)
- Mean, 11-10
 area, logarithmic, 34-8
 arithmetic, 11-10
 bulk temperature, 36-3
 effective pressure, 29-8
 geometric, 11-10
 radius, geometric, 57-3
 stress, 50-6
 time between failures, 61-9
 time between forced outages, 61-9
 time to failure, 11-7, 61-9
 time to repair, 61-9
- Measurement
 far-field, 68-6
 flow, 17-20
 near-field, 68-6
- Mechanical
 advantage, 43-10
 advantage, pulley block, 43-11
 efficiency, 29-3
 properties, metal, A-113-A-115
 seal, 66-35
 similarity, 17-38
 system, modeling, 59-4
- Mechanism, 43-20
 crank/slider, 55-13
- Median, 11-10
- Media, packing, 66-39
- Medium-carbon steel, 45-5
- Melting point, 47-1 (ftn)
- Member
 axial, 43-11
 redundant, 43-7, 43-13
 three-force, 43-6
 two-force, 43-6
 zero-force, 43-14
- Meniscus, 14-11
- Mensuration, 7-1, A-7-A-9
- Mer, 45-13, 45-15
- Merit, figure of, 31-9
- Mesh, 52-11
 efficiency, 52-12
 ratio, 57-5
 separation, 64-10
- Metabolic, 39-3
- Metacenter, 15-16
- Metacentric height, 15-17
- Metal, 21-2
 alkali, 21-2
 alkaline earth, 21-2
 base, 47-1
 characteristics, 45-1
 heavy, 21-2
 light, 21-2
 properties, mechanical, A-113-A-115
 removal rate, 63-3
 spraying, 63-14
 transition, 21-3
- Metallic properties, 21-2
- Metallizing, 63-14
- Metalloid, 21-2
- Metallurgy, 45-1, 63-10
- Metal-metal system, 45-19
- Metals, properties, A-82, A-90
- Metastable structure, 45-9
- Metathesis, 21-6 (ftn)
- Meter
 current, 17-21
 displacement, 17-21
 obstruction, 17-21
 orifice, 17-24
 pressure, 14-3
 sound, 68-5
 turbine, 17-21
 variable-area, 17-21
 venturi, 17-23
- Metering pump, 18-4
- Methane
 landfill, 66-11
 series, 22-2
- Methanol, 22-7
- Method (*see also type*)
 area transformation, 49-19
 bisection, 3-4, 13-1
 combination, 20-21
 compatibility, 44-2
 consistent deformation, 44-2, 49-19
 cut-and-sum, 43-15
 double-dabble, 12-1 (ftn)
 engineering, 61-27
 equal-friction, 20-19
 equivalent length, duct, 20-15
 Hardy-Cross, 17-20
 loss, 22-16
 lumped parameter, 34-12
 M-factor, 40-5
 Newton's, 13-2, 34-11, 34-12 (ftn)
 NTU, 36-20
 numerical, 3-4, 13-1
 of joints, 43-14
 of least squares, 11-13
 of sections, 43-15
 of undetermined coefficients, 3-6, 10-4
 parallelogram, 5-3
 polygon, 5-3
 Rayleigh's, 58-5
 Raymondi and Boyd, 52-22
 regula falsi, 13-2 (ftn)
 remainder, 12-1
 simplex, 61-12
- static regain, 20-21
 superposition, 44-4
 -Time-Measurement, 61-16 (ftn)
 total pressure, 20-24
 transfer function, 41-2
 velocity reduction, 20-19
 Winfrey, 69-16 (ftn)
- Methyl
 alcohol, 22-7
 orange alkalinity, 21-14
- Metric system, 1-4
- Meyer hardness, 46-12
- M-factor
 masonry, 40-5
 method, 40-5
- Mho, 67-2 (ftn)
- Microbiologically influenced corrosion, 27-12
- Microfin, 33-9 (ftn)
- Microfouling, 27-12
- Micronized coal, 22-5 (ftn), 27-3 (ftn)
- Microstrain, 62-8
- MIG welding, 63-12
- Miles per gallon, 56-21
- Milligram
 equivalent weight, 21-8
 per liter, 21-8, 21-11 (ftn)
- Milling, 64-7
- Million, parts per, 21-8, 21-11 (ftn)
- Mineral matter, 22-3
- Miner's rule, 50-7
- Minimum
 attractive rate of return, 69-14, 69-16
 point, 8-2
- Minor
 axis, 7-11
 loss, 17-11
 loss, sprinkler, 65-7
 of entry, 4-2
- Miscible alloy, 47-1
- Mixed
 -bed unit, naked, 21-16
 flow pump, 18-4 (ftn)
 flow turbine, 18-23
 triple product, 5-4
- Mixer, 64-12
- Mixing
 heater, 27-13
 problem, 10-8
 Reynolds number, 64-12
 two air streams, 38-5
- Mixture, 47-3
 gas, 24-2, 24-17
 liquid-vapor, 24-2
 pattern, 61-22
 rule, 66-4
- mks system, 1-5
- MMBtu, 66-14
- Modal
 shape, 58-19
 vibration, 58-18
- MODAPS, 61-16 (ftn)
- Mode, 11-10, 58-18
- Model, 17-11, 17-38 (*see also type*)

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Modified
 Goodman line, 50-7
 Mohr theory, 50-2
- Modular ratio, 49-19
- Modulation, flow rate, 20-3
- Module, gear, 52-10
- Modulus, 3-8
 apparent, 46-10
 Biot, 34-4
 bulk, 14-13, 46-8, 68-4
 creep, plastics, 46-10
 of elasticity, 46-2, *46-2*, 49-2
 steel, *53-5*
 of elasticity, temperature effect on, 53-5
 of resilience, 46-6, 50-4
 of rigidity, 46-7
 of toughness, 46-6
 secant, 14-13, 46-4
 section, 49-11
 shear, 46-7, 49-2
 tangent bulk, 14-13
 Young's, 46-2, 49-2
- Mohr's
 circle, 48-7, 49-6
 theory, modified, 50-2
 theory of rupture, 46-7
- Moh hardness scale, *46-12*
- Mohs hardness test, 46-12
- Moist air, 38-2, 38-3
- Moisture
 bed, 22-3
 content, 24-9, 45-16
 separator, 30-1
- Molality, 21-7
- Molar
 properties, 24-4
 volume, 21-4
- Molarity, 21-8
- Molding, 63-8 to 63-10
- Mole, 21-4
 fraction, 14-6, 21-8, 22-2, 24-17
 percent, 14-6
- Molecular weight, 21-4
- Molecule, 21-1
 hydrated, 21-4
 spacing, 14-2
 speed, 24-17
- Mollier diagram, 24-9, *A-53*, *A-72*
- Molluscide, 27-12
- Molten carbonate fuel cell, 31-8
- Moment, 49-8
 about a line, 43-3
 about a point, 43-2
 arm, 43-2
 component, 43-3
 diagram, 49-8
 first, area, 48-2
 fixed-end, 44-6
 free, 43-4, 43-9
 hydrostatic, 15-11
 of a function, 9-6
 of area, first, 44-5
 of inertia, *A-117*
 area, 48-3, *A-117*
 mass, 54-2, *A-125*
 polar, 48-5, 51-13
 principal, 48-7
 of momentum, 56-3
 one-way, 49-8 (ftn)
 overturning (dam), 15-11
 righting, 15-16
 second, 48-3
 statical, 48-2, 49-10
- Moment area method, 49-14
- Momentum
 angular, 56-3
 conservation, 56-3
 fluid, 17-27
 linear, 56-2
- Monel metal, 45-13
- Monitoring, emissions, 66-21
- Monitor steel, 64-2
- Monomer, 45-13
- Monomial, 3-3
- Monotectic reaction, 47-3
- Montreal Protocol, 33-2, 66-8
- Moody friction factor chart, 17-6, *17-6*
- Mortality
 curve, 61-11
 infant, 11-7, 61-11
- Most
 probable speed, 24-17
 significant bit, 12-1, 12-4
 significant digit, 12-1
- Motion
 constrained, 56-9
 dependent, 55-11
 impending, 56-6
 linear, 55-2
 plane, 55-11
 projectile, 55-4
 relative, 55-9
 simple harmonic, 58-2, *58-6*
 uniform, 55-3
- Motivation-maintenance theory, 61-28
- Motivator, 61-28
- Motor, *67-14*
 electrical, 67-10
 electric, hydraulic power, 19-5
 formulas, *19-5*
 gear, 18-10
 induction, 67-12
 linear, 19-6 (ftn)
 octane number, 22-6
 polyphase, characteristics, *A-133*
 size, 18-8, *18-9*, *67-11*
 speed control, 67-15
 stepper, 60-13 (ftn)
 synchronous, 67-13
- Mottled cast iron, 45-10
- Movement, 61-15
- Moving average forecast, 69-41
- Moving load, beam, 49-18
- MSW (*see* Municipal solid waste)
- MTTF (*see* Mean time to failure)
- MTBE, 22-7
- Mud drum, 27-4 (ftn)
- Muller, 63-10
- Multicouple, 31-9
- Multiple
 degrees of freedom, 58-2, 58-19, 59-2
 hypergeometric distribution, 11-5
 -pass heat exchanger, 36-10
 pipe containment, 66-36
 reheat, 27-13
 -stage pump, 18-4
- Multiplication
 matrix, 4-4
 vector, 5-3
- Multirating table, 20-5
- Municipal solid waste, 66-12, 66-31, *66-33*, 66-34
- Mutagen, 61-27
- Muther nearness priority, 61-15 (ftn)
- N**
- Nacelle, 31-4
- Naked mixed-bed unit, 21-16
- Nameplate
 motor, 67-11
 rating, 18-9
 pressure vessel, 53-2
- Napierian logarithm, 3-5
- Napthalene series, 22-2
- National
 Council of Examiners for Engineering and Surveying, 72-1
 Society of Professional Engineers, 71-1, 71-3
- Native copper, 45-12
- Natural
 abrasive, 45-19
 -circulation boiler, 27-4
 convection, 35-2
 draft, 22-16
 frequency, 9-6, 57-12, 58-3, 60-9
 gas, *22-11*
 logarithm, 3-5
 response, 60-1, *60-2*
 vibration, 58-2
- Near-field, 68-6
- Nearness priority, 61-15
- Necking down, 46-4
- Neck, nozzle, 53-3, 53-11
- Need hierarchy, 61-28
- Needle valve, 16-11
- Negative
 exponential distribution, 11-7
 feedback, 60-4
 number (computer), 12-4
- Negligence, 70-5
- Nelson diagram, 53-4
- NEMA motor size, *18-9*
- Nernst theorem, 24-6
- Nested spring, 52-5
- Net
 electrical output, 27-1
 heating value, 22-14
 inlet pressure required, 18-13 (ftn)
 positive inlet pressure, 18-2 (ftn)
 positive suction head, 18-13
 radiation transfer, 37-4
 rating, 22-16
 stack temperature, 22-13
 transport theory, 34-2
- Network polymer, 45-15
- Neurotoxin, 61-27
- Neutral
 axis, 49-10
 equilibrium, 56-2
 flame, 63-11

Italicized page numbers represent sources of data in tables, figures, and appendices.

- position, 42-5
solution, 21-8
- Neutralization, 21-9, 66-41
- Neutralizing amine, 21-15
- Neutron
embrittlement, 30-2
gaging, 46-12
radiography, 46-12
- Newton form, 13-3 (ftn)
- Newtonian fluid, 14-2, 14-6
- Newtonian frame of reference, 55-9
- Newton's
first law, 56-4
gravitational constant, 56-18, 56-18
interpolating polynomial, 13-3
law of convection, 36-2
law of cooling, 10-10, 34-11
law of gravitation, 56-18
method, 13-2, 34-11, 34-12 (ftn)
second law, 56-4
third law, 56-5
- Nichrome, 45-13
- Nickel, 45-13
-metal hydride battery, 31-10
silver, 45-12 (ftn)
- Nikuradse equation, 17-5
- Nilvar, 45-13
- NIMBY, 66-12
- Nines complement, 12-3
- Nip, angle of, 64-6
- Nitric oxide, 66-13
- Nitriding, 47-10
- Nitrogen
dioxide, 66-13
oxides, 66-13
-oxygen ratio, 22-8
- Nitrous oxide, 66-13 (ftn)
- Noble gas, 21-2
- No-boiler incinerator, 66-31
- No choice exam, 72-3 (ftn)
- Nocturnal radiation, 37-7
- Node, 7-2, 58-19, 61-3
- Nodular cast iron, 45-9, 47-8
- Noise, 68-3
criteria curve, 68-8
dose, 68-9
meter, 68-5
reduction, 68-8 to 68-10
reduction coefficient, A-135
- Nominal
damages, 70-7
dimension (pipe), 16-10
interest rate, 69-28
system voltage, 67-5 (ftn)
- Nonattainment area, 66-3
- Noncarbonate hardness, 21-14
- Noncatalytic reduction, selective, 66-38
- Noncircular duct, 17-9
- Noncondensing cycle, 28-2
- Noncondensing gas, 27-11
- Nonconformance, 61-24
- Noncriteria pollutant, 66-3
- Nondestructive testing, 46-11, 46-13
- Nonenclosure hood, 39-4
- Nonhomogeneous differential equation,
10-1, 10-4
- Nonhomogeneous linear equation, 3-7
- Nonlinear
interpolation, 13-2, 13-3
regression curves, 11-14
- Nonmetals, 21-2
properties, A-82, A-91
- Non-overloading fan, 20-4
- Non-parametric equation, 3-3
- Non-quantifiable factor, 69-2
- Nonreverse-flow valve, 16-12
- Non-SI units, 1-6
- Nonsingular matrix, 4-5
- Normal
acceleration, 55-8
curve, A-12
distribution, 11-6
force, 15-12, 56-6
form, 7-5
line vector, 8-6
pitch, 52-10, 52-12
pressure angle, 52-12
pressure, sprinkler, 65-7, 65-8
shock, A-85
shock wave, 26-9
speed, 56-21
stress, 49-2
stress theory, maximum, 50-1
temperature and pressure, 22-3
vector, 7-6
view, 2-1
- Normality, 21-8
- Normalizing, 47-7, 47-9
- Notch
-brittle, 46-6 (ftn)
factor, fatigue, 46-10
sensitivity, 46-10
stress concentration, 49-5
toughness, 46-13, 47-9, 53-5
- NOx, 22-5, 66-13
- Nozzle, 17-23
ASME long radius, 17-26 (ftn)
coefficient, 18-21
control, 27-16
convergent-divergent, 26-5
discharge coefficient, 26-8
efficiency, 26-8
flow, 17-25
ISA, 17-26 (ftn)
loss, turbine, 18-21
pressure vessel, 53-3, 53-11
steam flow through, 26-20
velocity coefficient, 26-8
venturi, 26-5
- np*-chart, 61-24
- NPSHR, hydrocarbon, 18-20
- NSPE (*see* National Society of Professional Engineers)
- NTU method, 36-20
- Nuclear
power cycle, 30-1
sensing, 46-12
- Nucleate boiling, 35-10
- Nucleon, 21-1
- Null
event, 11-3
indicator, 62-9
matrix, 4-1
point, 39-4, 66-28
position, 62-4
region, 7-3
set, 11-1
- Number
AGMA bending stress, 52-14
atomic, 21-2, A-39
Avogadro's, 21-4
base-*b*, 12-1
bearing load, 52-21
binary, 12-1
Biot, 34-4
cavitation, 18-14
cetane, 22-7
complement, 12-3
complex, 3-1, 3-7
condensation Reynolds, 35-9
dimensionless, 1-7, 1-9 (tbl)
direction, 7-5
Eötvös, 17-38
film Reynolds, 35-9
flow, 64-12
force, 64-12
Fourier, 34-4
Froude, 17-40
Graetz, 36-2
Grashof, 35-2
imaginary, 3-1
irrational, 3-1
Mach, 14-14
mixing Reynolds, 64-12
negative (computer), 12-4
Nusselt, 35-2, 36-2
octane, 22-6
of transfer units, 36-20
oxidation, 21-3, 21-3
Peclet, 36-2
performance, 22-6
power, 64-12
Prandtl, 35-2, 36-2
rational, 3-1
Rayleigh, 35-3
real, 3-1
Reynolds, 16-7, 17-38, 35-3, 36-2
smoke spot, 22-13, 66-17
Sommerfeld, 52-22
Stanton, 36-2
system, 12-1
type, 3-1
Weber, similarity, 17-40
- Numbering system, 3-1
- Numerical method, 3-3, 13-1
- Nusselt
equation, 35-3, 36-5
equation parameters, 35-4
number, 1-9 (tbl), 35-2, 36-2, 36-5, 36-8, 36-10
-type correlation, 35-3 (ftn)

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Nut
 coal, 22-4
 factor, 51-12
Nyquist analysis, 60-13
- O**
- Objective function, 61-2, 61-12
Objectively scored problems, 72-3
Oblique
 axis, 2-2
 compression shock wave, 26-13
 impact, 56-16
 perspective, 2-3
 shock wave, 26-11
 triangle, 6-5
 view, 2-2
Obliquity, angle of, 52-11
Observability, 60-14
Obstruction meter, 17-21
Obtuse angle, 6-1
Occupant heat generation, 39-3
Ocean thermal energy conversion, 31-6
Octahedral shear-stress theory, 50-5
Octal number system, 12-2
Octane number, 22-6
Octave, 60-10, 68-7
 band, 68-7, 68-7
 rule, 58-19
Odd
 symmetrical, 7-4
 symmetry, 9-7 (tbl)
Odor, 66-15
Odor removal, 39-3
Offer, 70-3
Off-gas, 66-39
Offset, parallel, 46-3
Ohm's law, 67-3, 67-6
Oil
 Bunker C, 22-5
 crankcase, 52-19
 cutting, 63-4
 distillate, 22-6
 fuel, 22-5, 22-6
 lubricating, 52-20
 residual fuel, 22-6
 spill, 66-15
Olefin series, 22-2
Oligomer, 45-14
Once-through
 boiler, 27-1, 27-4
 cooling water, 66-9
One-for-one plan, 61-20
Ones complement, 12-3
One-tail limit, 11-12
One-way
 moment, 49-8 (ftn)
 shear, 49-7 (ftn)
Opacity, smoke, 66-17
Opaque material, 68-3
Open
 circuit, electrical, 67-2
 combustor, 29-16
 -cycle OTEC, 31-6
 die forging, 63-7
 drive, 52-15
 hearth process, 45-4
 heater, 27-13
 -loop recovery, 66-23
 manometer, 15-3
 system, 25-1
Operating
 characteristic curve, 61-25
 differential, 42-2
 expense, 69-32
 point
 compressor, 32-8
 fan, 20-7
 pump, 18-16
Operation
 factor, 27-16
 unit, 27-1
Operational form (log), 3-5
Operations
 on complex numbers, 3-8
 research, 61-1
Opportunity cost, 69-18
Opposite side, 6-2
Optical
 density, 66-17
 holography, 46-11
Optimum staging, 32-7
Orbit
 eccentricity, 56-19, 56-19
 geostationary, 56-18
 law of, 56-18
Order
 differential equation, 10-1
 matrix, 4-1
 of the system, 59-2, 60-4
Ordinate, 7-2
Organic
 peroxide, 45-15 (ftn)
 precursor, 66-18
 sulfur, 22-3
Orientation, angular, 5-1
Orifice, 17-16
 coefficient, 17-17
 compressible flow, 26-15
 constant, sprinkler, 65-5
 large, 17-18
 meter, 17-24
 plate, 17-24
 plate flow coefficient, 17-25
 pressure loss, 17-25 (ftn)
Orsat apparatus, 22-11
Orthogonal, 7-2
 vectors, 5-3
 view, 2-2
Orthographic
 oblique view, 2-3
 view, 2-2
Oscillation
 amplitude of, 58-3
 period of, 58-3
Oscillatory system, 58-6
OSHA, sound exposure limits, 68-10
Osmotic pressure, 14-9
Othmer correlation, 14-11
Otto cycle, air-standard, 29-5
Outlet
 constant, 20-25
 duct, 20-24
Output factor, 27-16
Outside design condition, 40-2
Overall
 coefficient of heat transfer, 34-6, 36-15, 40-2
 conductance, 36-15
 conductivity, 34-2, 34-6
 efficiency, pump, 18-8
 gain, 60-4
 heat transfer coefficient, 36-15
 transfer function, 60-4
Overautogenous waste, 66-28 (ftn)
Overdamped, 58-9
Overdrive gear, 56-20
Over-expansion, 26-13
Overfeed stoking, 27-3
Overflow, 64-10
Overflow bit, 12-4
Overhauling screw, 52-22
Overhead, 69-36
Overhung load, 18-10
Overload
 head, 18-15
 pump, 65-3
Overshoot, 42-2, 60-2
Overturning
 factor of safety, 15-11
 moment (dam), 15-11
Owner, 70-4
Owners' equity, 69-33
Ownership, 70-1
Oxidant, 66-15
Oxidation, 21-3
 number, 21-3
Oxides, nitrogen, 66-13
Oxidizing flame, 63-12
Oxyacetylene welding, 63-11
Oxygen
 -enriched incineration, 66-34
 metabolic, 39-3
 process, 45-3
 scavenging, 21-15
Oxygenate, 22-6, 22-7
Oxygenated
 fuel, 66-8
 gasoline, 22-6
Oxyhydrogen welding, 63-11
Ozonation, 66-36
Ozone, 66-8, 66-15
- P**
- Pace value, 30-2
Packed
 bed, 36-10
 tower, 66-22, 66-39
Packing
 height of, 66-40
 media, 66-39
 tower, 38-11
Pad, brake, 52-16

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Paddle
 impeller, 64-12
 wheel fan, 20-4
- Palmgren-Miner cycle ratio, 50-7
- Panel
 coil heat exchanger, 36-12
 truss, 43-12
- Panhandle formula, 17-9
- Pappus-Guldinus, theorem, 48-3
- Pappus' theorems, 9-5
- Parabola, 7-10, *7-10*
- Parabolic
 axis, 7-10
 cable, 43-17
 cam profile, 57-10
 column formula, 51-3
- Paradox, hydrostatic, 15-4
- Paraffin series, 22-2
- Parallel
 axis theorem, 48-4, 54-2
 circuit, electrical, 67-4
 flow, 36-10
 force, 43-6
 line, 7-8
 offset, 46-3
 perspective, 2-3
 pipe, 17-20
 pumps, 18-17
 reliability, 11-8
- Parallelogram method, 5-3
- Parameters
 catenary, 43-19
 variation of, 10-4
- Parametric
 equation, 3-2
 equation, derivative, 8-3
 equation, plane, 7-6
- Parent ingredient, 47-1
- Parkerizing, 63-14
- Partial
 -arc admission, 27-16
 differentiation, 8-4
 emission, forced vortex pump, 18-11 (ftn)
 fraction, 3-6, 9-2
 pressure, 24-17
 pressure fraction, 22-2
 similarity, 17-40
 solubility, 47-3
 volume, 24-17
- Partially filled pipe, *A-21*
- Particle
 arrester, 39-6
 -strengthened, 45-19
- Particular solution, 10-4 (tbl)
- Particulate matter, 66-15
- Parting line, 63-8
- Partner
 general, 70-1
 limited, 70-2
- Partnership, 70-1
- Parts, integration by, 9-2
- Parts per million, 21-8, 21-11 (ftn)
- Pascal's
 law, 15-4, 15-14 (ftn)
 triangle, 3-3
- Passivated steel, 45-8
- Passive
 element, 59-2
 solar system, 31-2 (ftn)
 system, 60-11
- Path
 critical, 61-3, 61-4
 function, 25-4
- Payback period, 69-38
- PCB (*see* Polychlorinated biphenyls)
- p*-chart, 61-22, 61-24
- Peak
 cylinder pressure, 29-8 (ftn)
 demand multiplier, 67-7
 flame temperature, 66-13
 gain, 60-2
 load service, elevator, 64-4
 time, 60-2
- Pea coal screening, 22-4
- Peaking unit, 27-16
- Pearlite, 47-6
- Peclet number, 1-9 (tbl), 36-2
- Peel strength, 63-13
- Peltier effect, 62-6 (ftn)
- Pendant sprinkler, 65-4
- Pendulum
 ballistic, 56-3
 torsional, 58-5
- Penstock, 18-20
- Percent
 clearance, 32-3
 isolation, 58-12
 mole, 14-6
- Percentage
 humidity, 38-2
 yield, 21-7
- Percentile rank, 11-10
- Per diem fee, 70-5
- Perfect
 gas, 24-15, 25-7
 reaction, 21-6
 spring, 52-2
- Performance
 coefficient of, 33-2
 curve, pump, 18-15
 factor, 38-10
 function, 11-8
 number, 22-6
 rating factor, 61-16
 standard, 61-20
- Perigee, 56-19
- Perihelion, 56-19
- Perimeter, wetted, 16-6
- Period, 69-2
 chemical, 21-2
 electrical, 67-4
 of oscillation, 58-3
 of waveform, 9-6
- Periodic
 table, 21-2, *A-40*
 time, 56-18
 waveform, 9-6
- Periods, law of, 56-18
- Peritectic reaction, 47-3
- Peritectoid reaction, 47-3
- Permalloy, 45-13
- Permanent
 hardness, 21-14
 molding, 63-9
 set, 46-2
- Permivar, 45-13
- Permutation, 5-5, 11-2
- Peroxide, organic, 45-15 (ftn)
- Perpendicular
 axis theorem, 48-5
 line, 7-8
 line principle, 2-1
 lines, 2-1
- Perpetual inventory system, 69-37
- Personal property, 69-20 (ftn)
- Perspective, 2-2, 2-3
- PERT (*see* Program evaluation and review technique)
- Petroff equation, 52-21
- pH, 21-8
- Phase, 47-1, 67-9
 angle, 67-4, 67-6
 characteristic, 60-10, 60-11
 crossover, 60-11
 current, 67-9
 diagram, 24-3, 47-1
 diagram, iron-carbon, *47-5*
 factor, 67-7
 margin, 60-11
 rule, Gibbs, 47-3
 voltage, 19-5 (ftn)
- Phasor form, 3-8, 67-5
- Phenolic plastic, 45-15
- Phenolphthalein alkalinity, 21-14
- Phon scale, 68-8
- Phosphoric acid fuel cell, 31-8
- Phosphorus bronze, 45-12
- Photochemical
 reaction, 66-15
 smog, 66-17
- Photoelectric effect, 62-4
- Photosensitive
 conductor, 62-5
 resist, 63-6
- Photovoltaic cell, 31-4, 62-4
- Physical
 constants, inside front cover
 inventory, 69-37
 strain, 46-5
 stress, 46-4
- Pickling, 63-8, 63-14
- Pickup, 62-3 (ftn)
- Pickup load, 40-5
- PI control, 42-5
- Pictorial drawing, 2-2 (ftn)
- PID control, 42-5
- Piece-rate, 61-20
- Piecework, 61-20
- Pier, 49-12, 51-1
- PIEV time, 56-21
- Piezoelectric, 45-18
 effect, 15-2, 62-4
 transducer, 62-4
- Piezometer, 15-2 (ftn)
- Fig, 45-3

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Pile
 bulk, *64-4*
 bulk storage, 64-4
- Pinch point, 29-20
- Pinion, 52-11
- Pinned support, 43-7
- Pipe
 bend, force on, 17-30
 black steel, 16-10
 circular, *A-21*
 entrance, 17-13
 exit, 17-12
 heat, 34-20
 hydraulic, 19-2
 insulated, 34-8
 insulation, 34-9
 manufacture, 63-13
 material, 16-9
 maximum velocity in, 17-3
 parallel, 17-20
 pressure vessel, 53-15
 PVC, dimensions, *A-29*
 schedule-40, flow of water through, *A-36*
 series, 17-19
 steel, dimensions, *A-22-A-25*
 temperature effect, *53-16*
 wall thickness, 19-3
- Piping, 64-5
 geometry factor, 17-13
 symbols, *A-30*
- Piston displacement, 32-3
- Pit, ash, 22-3
- Pitch, 36-9, 56-2
 angle, 52-14
 axial, 52-12
 base, 52-10
 circle, 52-10
 circle velocity, 52-10
 circular, 52-10
 coil, 52-5
 cone, 52-14
 control, blade, 20-3
 diametral, 52-10
 helix, 7-12
 length, V-belt, 52-16
 -limiting, 31-5
 normal, 52-10
 circular, 52-12
 diametral, 52-12
 point, 52-10
 spring, 52-5
 transverse circular, 52-12
- Pitot-static gage, 17-22
- Pitot tube, 16-4, 26-21
- Pitting, 21-11
- Pitting resistance, gear, 52-14
- Plain carbon steel, 45-5
- Plain end, 52-5
- Plaintiff, 70-5
- Plan, 61-20 (*see also type*)
- Planar view, 2-2
- Plane, 7-6
 angle, 6-1
 complex, 3-7
 motion, 55-11, 56-2
 sandwiched, 34-6
 tangent, 8-5
- Planet
 carrier, 57-5
 gear, 57-5
 pinion, 57-5
- Planetary gear, *57-5, 57-6, A-126*
- PLAN formula, 29-8
- Plan, single-sampling, *A-128*
- Plant, 60-13
 factor, 27-15
 layout, 61-14
 location problem, 61-13
- Plasma
 diode, 31-9
 incineration, 66-34
- Plastic, *66-16*
 behavior, 49-2 (ftn)
 hinge, 49-18
 impact, 56-15
 molding, 63-9
 pipe, 16-10
 strain, 46-2
 types, 66-16
 waste, 66-15
- Plastics, tests on, 46-10
- Plate
 absorber, 31-2
 -and-frame heat exchanger, 36-12
 cam, 57-10
 clutch, 52-19
 exchanger, 36-12
 flat, 36-3, 36-4, 51-17
 flat, uniform pressure, *51-18*
 heat exchanger, 36-12
 heat rate, 27-5
 jet force on, 17-28
 -type element, 53-3
 vibration, 58-17, *58-17*
- Plateau, 47-2
- Plow steel, 64-2
- Plug
 flow, 29-10 (ftn)
 valve, 16-11
- Plugging, 66-37
- Plume, 38-12
- Plunger pump, 18-2
- Pneumatic
 actuator, 42-1
 conveyor, 64-6
- pOH, 21-8
- Pohlhausen solution, 36-4
- Point (*see also type*)
 approach, 29-20
 breakaway, 60-12
 choke, 32-8
 cloud, 22-7
 contraflexure, 8-2
 critical, 8-2, 24-3, 24-8, *24-8*, 26-4
 distribution, 20-24
 extreme, 8-2
 force, 43-2
 freezing, 47-2
 function, 25-4, 25-7
 inflection, 7-2, 8-2, 49-16
 inversion, 25-3
 null, 39-4
 of application, 5-1
 of contraflexure, 7-2, 49-16
 of control, 61-25
 of duty, fan, 20-7 (ftn)
 of instability, 60-12
 of rating, fan, 20-7 (ftn)
 of sale, 69-37
 operating, 18-16
 operating, compressor, 32-8
 operating, fan, 20-7
 pinch, 29-20
 pitch, 52-10
 pour, 22-7, 52-20
 set, 21-16
 singular, 8-1, 8-3
 -slope form, 7-5
 stone wall, 32-8
 terminal, 5-1
 triple, 24-8, *24-8*, 47-4
 yield, 46-2
- Poise, 14-7
- Poisoning, 66-37
- Poisson distribution, 11-5
- Poisson's ratio, 46-4, *46-4*
- Polar
 amine, 21-15
 coordinate system, 7-3 (tbl), 7-4 (fig)
 form, 3-8, 7-5
 moment of inertia, 48-5, 51-13
- Pole, 60-8
- Pole-zero diagram, 60-8, 60-9
- Polishing, 21-16, 63-14
- Pollutant, 66-3
- Pollution, 66-2 to 66-4
- Polychlorinated biphenyls, 66-15
- Polygon method, 5-3
- Polymer, 45-13, *45-15-45-17*, *66-16*
 atactic, 45-16
 crystallinity, 45-16
 isotactic, 45-16
 network, 45-15
 syndiotactic, 45-16
 synthetic, 45-14
 thermoplastic, *45-17*
 thermosetting, *45-17*
- Polymerization
 addition, 45-15
 condensation, 45-15
 degree, 45-14
 step reaction, 45-15
- Polymorph, 45-18
- Polynomial, 3-3
 characteristic, 4-7
 degree, 3-3
 Lagrangian interpolating, 13-2
 Newton's interpolating, 13-3
 standard form, 3-3
- Polyphase motor, characteristics, *A-133*
- Polystyrene resin zeolite, 21-14
- Polytropic
 compression, 15-13
 efficiency, 32-5
 equation of state, 25-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- exponent, 15-13, 19-6, 25-2
 exponent, compression, 32-2
 head, 32-5
 process, 25-2, 25-9
 specific heat, 25-2
 Pool boiling, 35-10
 Poppet valve, 29-2
 Population, 11-3
 Position
 equilibrium, 58-2
 valve, 19-2
 Positional number system, 12-1
 Positive
 displacement pump, 18-2
 feedback, 60-4
 Potential
 energy, 16-2, 23-2
 stream, 17-3
 Potentiometer, 62-3, 67-2
 Potentiometric sensor, 62-3
 Poundal, 1-4
 Pour point, 22-7, 52-20
 Powder metallurgy, 63-10
 Power, 23-5
 angle, 67-7
 blower, 20-4
 boosting, 29-14
 brake, 29-3, 29-4
 brake, fan, 20-4
 coefficient, 31-5
 coefficient, wind, *31-6*
 conversions, *23-5*
 cycle, 25-10
 nuclear, 30-1
 solar, 31-3
 vapor, 28-1
 design, 56-7 (ftn)
 electrical, 27-1, 67-3, 67-6
 emissive, 37-1
 factor, 67-7, 67-8
 fan, 20-4
 fluid, 19-1
 friction, 18-8, 20-5, 29-3
 hydraulic, 18-6, 19-1
 indicated, 29-3
 law (viscosity), 17-11
 number, 64-12
 phase, 67-9
 propulsion, 56-20
 pump, 18-2, 18-6
 screw, 52-22
 screw jacks, 52-22
 spring, 52-9 (ftn)
 specific battery, 31-10
 specific flywheel, 57-2
 stroke, 29-2
 thermal, 27-1
 tidal/wave, 31-7
 -to-heat ratio, 29-22
 -tower system, 31-3
 turbine, 17-29, 18-21
 versus torque, 52-10
 water, 18-6
 wind, 31-4
 Powerhouse, 18-20

 ppm (*see* parts per million)
 Prandtl number, 1-9 (tbl), 35-2, 36-2
 Prandtl's layer theory, 17-37
 Precedence table, 61-3
 Prechamber, 29-3
 Precharge gas pressure, 19-6
 Precipitation, 21-7
 -hardened stainless steel, 45-8 (ftn)
 hardening, 45-11, 47-9
 softening, 21-14
 Precipitator, *66-27*
 electrostatic, 66-26
 Precision, 11-13, 61-16, 61-18, 62-2
 Precision casting, 63-9
 Precombustion chamber, 29-3
 Precursor
 smog, 66-17
 trihalomethane, 66-18
 Predetermined system, 61-15
 Prefixes, SI 1-7
 Preheater, 27-15
 Preload, 51-11
 Prerequisite of privity, 70-6 (ftn)
 Present worth, 69-5, 69-11, 69-14
 Press
 fit, 51-5
 stress concentration factor, *51-8*
 forging, 63-8
 hydraulic, 15-14
 Pressure, 14-2, 15-4, 24-5
 absolute, 14-3
 amplifier, 32-2
 angle, 52-11, 52-12, 57-11
 at a depth, 15-6 (ftn)
 at altitude, 20-2, *20-2*
 atmospheric, *14-3*
 average, 15-6
 back, 27-11
 barometric, 14-3
 booster, 32-2
 burst, 19-3
 center of, 15-4, 15-8, *15-10*, 43-5
 collapsing, 51-3 (ftn)
 cut-in/out, 32-2
 design, 26-13
 die casting, 63-9
 drag, 17-34
 -drop endpoint, 21-16
 drop
 friction, 17-4 (ftn)
 hydraulic power, 19-4
 tube bundle, 36-9
 energy, 16-2, 23-3
 -enthalpy diagram, 24-11
 external, 15-14
 flow, 16-6
 fluid, 14-2
 friction, 20-11
 from gas, 15-12
 gage, 14-3
 gauge, 15-2
 head, 18-5 (ftn)
 hydrostatic, 15-4
 isentropic, 26-13
 line, 52-11
 loss, orifice, 17-25 (ftn)
 -maintenance pump, 65-3
 maximum allowable, 53-6
 mean effective, 29-8
 measurement, 15-1
 measuring devices, *15-2*
 multiple liquid, 15-12
 on a dam, 15-11
 on curved surface, 15-10
 on plane surface, 15-6 to 15-8
 osmotic, 14-9
 partial, 24-17
 peak cylinder, 29-8
 pouring, 63-9 (ftn)
 rating, 19-3
 ratio, 24-10, 29-11, 32-1
 design, 26-5
 isentropic, 29-4
 reduction valve, 19-2
 -relief valve, 17-32
 saturation, 14-9
 static, 20-1
 test, hydrostatic, 53-17
 total, 16-3, 20-2, 24-17
 transverse, 17-22
 unit, 14-2
 vapor, 14-9, *14-9*, *A-17*
 velocity, 20-2
 vessel, 53-1, *53-3*, 53-4
 thickness, *53-9*, *53-10*
 weld, *53-8*
 working, pressure vessel, 53-6
 Pressurestat, 42-1
 Pressurized
 fluidized-bed combustion, 22-5
 liquid, 15-14, 27-7
 tank, 17-17
 water reactor, 30-1
 Presswork, 63-6
 Preventative maintenance, 61-10
 Price, 61-2 (ftn)
 Price-earnings ratio, 69-35
 Primary
 air, 27-3
 creep, 46-15
 dimension, 1-7
 loop, 30-1
 unit, 1-7
 Prime
 contractor, 70-4
 cost, 69-32
 gear set, 52-11
 mover, 18-8 (ftn)
 Principal
 axis, 48-7, 54-2
 moment of inertia, 48-7
 organic hazardous constituent, 66-30
 stress, 49-5
 view, 2-2
 Principle
 Archimedes', 15-14
 D'Alembert's, 56-5
 impulse-momentum, 17-26, 56-13, 56-14
 work-energy, 23-3, 23-4, 52-2
 Priority, ethical, 71-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Privity of contract, 70-6
Probabilistic model, 61-2
Probability, 11-2
 complementary, 11-4
 conditional, 11-4
 cumulative, *A-129*
 density function, 11-4
 joint, 11-3
 of acceptance, 61-25
Problem mixing, 10-8 (*see also type*)
Process
 adiabatic saturation, 38-7, 38-10
 air, 39-1 (ftn)
 air conditioning, 38-6
 annealing, 47-9
 Aston, 45-10
 base exchange, 21-14
 Bayer, 45-11
 Bessemer, 45-3
 cost accounting, 69-36
 dissolved oxygen, 45-3
 gasification, 29-15
 ion exchange, 21-14
 irreversibility, 25-12
 layout, 61-14
 L-D, 45-3
 open hearth, 45-4
 oxygen, 45-3
 puddling, 45-10
 reversible, 25-3
 steam, 29-21
 thermodynamic, 25-2 (*see also type*)
 waste, 66-3
 zeolite, 21-14
Producer gas, 22-7 (ftn)
Producer's risk, 61-25
Product, 21-5
 cross, 43-2
 layout, 61-14
 mixed triple, 5-4
 of inertia, 48-6, 54-2
 standard, 61-15
 triple scalar, 5-4
 vector, 5-4 to 5-5
Production
 rate, 61-18
 standard, 61-15
Productivity, 61-20
Professional
 engineer, 72-1
 engineering exam, 72-3
Profile
 auxiliary view, 2-2
 cam, 57-10
 drag, 17-34
 drag coefficient, 36-4 (ftn)
 temperature, 34-5
Profit, 69-37
Profit and loss statement, 69-34
Program evaluation and review technique,
 61-5
Programming
 dynamic, 61-12
 integer, 61-12
 linear, 61-12
 mathematical, 61-12
Progressive die, 63-6
Projectile, *55-5*
 motion, 55-4
Projection, 2-3
Projector, 2-2
Prony brake, 29-3, 62-12
Proof
 alcohol, 22-7
 load, bolt, 51-8, 51-12
 strength, 51-8, 51-12
 stress, 46-3 (ftn)
 test interval, 61-10
Propagation, 45-15
Propagation velocity, 68-4
Propeller
 fan, 20-3
 turbine, 18-23
Proper polynomial fraction, 3-6 (ftn)
Proper subset, 11-1
Properties
 air, *A-14, A-54, A-73*
 alloys, *A-82, A-90*
 atmospheric air, *A-99*
 cast iron, *45-9, 45-10*
 ceramic, *45-18*
 clutch/brake material, *52-17*
 coal, *22-5*
 composite material, *45-20*
 flywheel, advanced, *57-4*
 fuel, *22-6*
 fuel oil, *22-6*
 gases, 24-15 (tbl)
 gasoline, *66-10*
 glass, *45-18*
 insulating, building materials, *A-111*
 isolation material, *58-13*
 liquid, *A-15, A-16*
 mechanical, metal, *A-113-A-115*
 metallic, 21-2
 metals, *A-82, A-90*
 nonmetals, *A-82, A-91*
 oxygenates, *22-7*
 refrigerant-12, *A-56-A-60, A-75-A-77*
 refrigerant-22, *A-61-A-63, A-78-A-80*
 refrigerant HFC-134a, *A-64, A-81*
 saturated steam, *A-44, A-47, A-65, A-67*
 saturated water, *A-98*
 solids, *A-82*
 solutions, 14-15
 spring material, *52-3, 52-4*
 standard atmosphere, *A-88*
 steam, saturated, *A-100*
 superheated steam, *A-49, A-69*
 thermal, insulation, *34-10*
 thermoplastic, *A-116*
 transfer fluid, *31-3*
 water, *A-13, A-14*
 compressed, *A-51, A-70*
 weld group, *A-122*
 wire, *64-2*
 wire rope, *64-2*
 wood, *45-17*
Property
 business, 69-20 (ftn)
 chamber, 26-2
 class, bolt, 51-9
 critical, *24-8, 26-5*
 exit, 26-5
 extensive, 24-4
 intensive, 24-4
 stagnation, 26-2
 static, 26-3
 throat, 26-5
 total, 26-2
Property changes
 in ideal gases, 25-7
 in liquids, 25-10
 in solids, 25-10
Proportional
 action, 42-5
 plus integral and derivative control, 42-5
 plus integral control, 42-5
 region, 46-2
Proportionality limit, 46-2
Proportions, 21-3
Propped cantilever beam, 44-1
Proprietorship, sole, 70-1
Propulsion
 jet, 17-27
 power, 56-20
Protection area, sprinkler, 65-6
Protocol, Montreal, 33-2
Proton exchange membrane fuel cell, 31-8
Prototype, 17-38
Proximate analysis, 22-2
Proximity probe, 58-21
p-sequence, 3-11
p-series, 3-11
Pseudoplastic fluid, 14-7
Pseudo-static deflection, 58-10
Psychrometric chart, 38-3, *A-107-A-110*
Psychrometrics, 38-1
Public
 corporation, 70-2
 dealing with, 71-3
Puddling process, 45-10
Puffing, 66-28
Pulley, 43-11, 56-11
 advantage, 43-11
 block, mechanical advantage, *43-11*
 dependent, 55-11
 efficiency, 43-11
 foot, 64-9
 head, 64-9
 variable-pitch, 20-3
Pulsation
 damper, 18-2
 stabilizer, 18-2
Pulse, shock, 58-19
Pulverized-coal furnace, 27-3
Pulverizing, 64-7
Pump, 17-14, 18-2, 18-7 (*see also type*)
 boilerfeed, 27-6
 centrifugal, 18-2, 18-4
 drip, 27-14
 efficiency, *18-8*
 efficiency, isentropic, 27-6

Italicized page numbers represent sources of data in tables, figures, and appendices.

- fire fighting, 65-3
 fluid power, 19-4
 homologous, 18-12, 18-18
 jockey, 65-3
 life, 19-5
 metering, 18-4
 mixed flow, 18-4 (ftn)
 overall efficiency, 18-8
 performance curve, 18-15
 power, 18-6
 shaft loading, 18-10
 similarity, 18-8
 velocity ratio, 18-3
- Pumping
 hydrocarbons, 18-19
 other liquids, 18-19
- Punching, 63-7
 Punch press, 57-2
 Punitive damage, 70-5, 70-7
 Purchase order, 70-3
 PV cell, 31-4
 PVC pipe, 16-10
 dimensions, A-29
p-V work, 23-3, 25-6
 P-waste, 66-3
 Pyritic sulfur, 22-3
 Pyrolysis, 66-16
 Pythagorean theorem, 6-2
- Q**
- Quadrants, 6-3
 signs of functions, 6-3
 Quadratic equation, 3-3
 Quality, 24-9
 acceptance plan, 61-25
 circle, 61-29
 control, 61-22
 control chart, factor, 61-23, 61-24
 factor, 60-10
 lot, 61-25
 of boiler feedwater, 21-11
 Quantitative business analysis, 61-1
 Quantity, economic order, 69-42
 Quarter
 -bridge, 62-11
 -wave symmetry, 9-7 (tbl)
 Quartile, 11-10
 Quartz, 45-18
 Quartz-crystal transducer, 15-2
 Quasiequilibrium process, 25-2
 Quasistatic process, 25-2
 Quenching, 47-6
 Queue, 61-6
 utilization factor, 61-7
 Quick ratio, 69-35
- R**
- R-12, A-56-A-60, A-75-A-77
 R-22, A-61-A-63, A-78-A-80
 Rad, 6-1 (ftn)
 Radial
 camp, 57-10
 clearance, 52-20
 fan, 20-4
 -flow impeller, 18-4, 64-12
 -flow turbine, 18-23
 interference, 51-5
 strain, 51-5
 tip fan, 20-4
 velocity, 55-9
 Radian, 6-1, 6-5
 Radiant
 heat transfer coefficient, 37-4
 superheater, 27-12
 Radiation
 emissivity, A-106
 law, 37-1
 loss, 22-15
 nocturnal, 37-7
 solar, 37-7
 thermal, 37-1
 Radiator
 efficiency, 34-16
 ideal, 37-1
 Radical, 21-3
 Radiographic inspection, pressure vessel, 53-9
 Radiography, 46-12
 Radioisotope generator, 31-9
 Radius
 critical, 34-10
 geometric mean, 57-3
 hydraulic, 7-1, 16-6, A-21
 of gyration, 48-6, 48-6, 54-2
 Radix, 12-1
 Radon, 66-16
 Raimondi and Boyd method, 52-22
 Rainwater runoff, 66-16
 Rake angle, 63-2
 Ram, hydraulic, 15-14, 19-6
 Ramp, unit, 59-2
 Random error, 62-2
 Range, 11-10
 stress, 50-6
 water, 38-12
 Rankine
 cycle, 28-3, 28-4
 scale, 24-5
 Rank (matrix), 4-5
 Ranking alternatives, 69-17
 Rapper, 66-27
 Rare earths, 21-2
 Rate
 bleed, 27-8
 creep, 46-15
 heat, 27-5, 28-2
 heat release, 66-32
 metal removal, 63-3
 of change, 8-1
 of quench, 47-6
 of return, 69-11, 69-14, 69-16
 of shear formation, 14-6
 of strain, 14-6
 production, 61-18
 spring, 52-2
 station, 27-5, 28-2
 steam, 27-15
 thermal capacity, 36-20
 water, 27-15
 Rated
 capacity, pump, 65-3
 head, pump, 18-15, 65-3
 value, motor, 67-11
 Rat-holing, 64-5
 Rating
 continuous duty, 29-4
 factor, tower, 38-12
 net, 22-16
 point, fan, 20-7 (ftn)
 table, fan, 20-5
 Ratio
 air
 density, 20-2 (ftn)
 -fuel, 22-9, 22-12, 29-3
 -to-cloth, 66-24
 amplitude, 58-19
 aspect, 17-33, 20-14
 back work, 29-17
 beta, 17-23
 chip thickness, 63-2
 circulation, 29-20
 common, 3-11
 compression, 29-3, 29-5, 29-11, 32-4 (ftn)
 contact, 52-11
 critical, 26-4
 critical pressure, 26-4, 26-12, 26-13
 current, 69-34
 cut-off, 29-11
 damping, 58-9
 design pressure, 26-5
 eccentricity, bearing, 52-20
 endurance, 46-9
 energy-efficiency, 23-6 (ftn), 33-2
 error, 60-4
 fatigue, 46-9
 feedback, 60-4
 filter, 66-24
 fuel-air, 29-3
 gear, 57-5
 gear velocity, 52-11
 humidity, 38-2
 induction, 20-24
 isentropic, 29-4
 lead, 52-14
 lever, 58-8
 mesh, 57-5
 modular, 49-19
 nitrogen/oxygen, 22-8
 of concentration, 38-13
 of transformation, 67-6
 Palmgren-Miner cycle, 50-7
 Poisson's, 46-4, 46-4
 power-to-heat, 29-22
 pressure, 24-10, 29-11, 32-1
 price-earnings, 69-35
 saturation, 38-2
 sensible heat, 38-6, 41-3
 slenderness, 51-2
 specific heat, 15-13, 24-8, 26-3
 speed, 57-5
 spray, 38-11
 test, 3-12
 train, 57-5
 turndown, 27-3, 27-13

Italicized page numbers represent sources of data in tables, figures, and appendices.

- velocity, 52-11, 52-15, 57-5
- volume, 24-10
- Rational
 - function, 60-3
 - number, 3-1
- Rationalization, 3-8
- Ray, 6-1 (ftn)
- Rayleigh
 - equation, 58-15 (ftn)
 - flow, 26-19, *A-87*
 - line, 26-19
 - number, 35-3
 - Ritz equation, 58-15 (ftn)
- Rayleigh's method, 58-5
- R-chart, 61-22, 61-24
- Reactance, 67-5
- Reactant, 21-5, 21-7
- Reaction, 43-6, 43-8
 - chemical, 21-5
 - combustion, *22-9*
 - endothermic, 21-9
 - enthalpy, 21-9
 - eutectic, 47-3
 - exothermic, 21-9
 - rate constant, 66-25
 - site, 45-15
 - stoichiometric, 21-6, 21-7
 - time, 56-21
 - turbine, 18-22, 18-23, 27-8
- Reactive
 - power, 67-6, 67-7
 - substance, 66-3
- Reactor (*see also type*)
 - boiling water, 30-2
 - nuclear, 30-1
 - pressurized water, 30-1
 - reformer, 31-8
 - tank, 66-25
- Real
 - fluid, 14-2
 - gas, 24-2, 24-19, 24-20
 - machine, 23-6
 - number, 3-1
 - power, 67-6
- Rebound, 56-15
- Rebound test, 46-13
- Receipt, 69-3
- Receivable turnover, 69-35
- Receiver tank, 32-2
- Reciprocating
 - compressor, 32-1, 32-2
 - pump, 18-2
- Reciprocity, 72-2
- Reciprocity theorem for radiation, 37-4
- Recirculating air bypass, 41-3
- Recirculation, flue gas, 66-27
- Recovery, 46-2
 - depreciation, 69-26
 - stage, 47-9
- Recrystallization, 47-8, 47-9
 - temperature, *47-8*
- Rectangular
 - coordinate system, 7-3
 - duct, 20-14
 - form, 3-7
 - hyperbola, 7-12
 - rosette, 62-12
- Rectified sinusoid, 67-5
- Rectifier, 33-7
- Rectilinear system, 55-2
- Rectum, latus, 7-10, 7-11
- Recuperative heater, 27-15
- Recuperative heat exchanger, 36-10 (ftn)
- Recuperator, 33-7
- Recycle air, 38-11
- Red
 - hardness, 45-7 (ftn), 63-4
 - mud, 45-11
- Reduced
 - coke process, 45-7
 - equation, 10-1
 - plan, 61-25
 - variable, 24-19
- Reducing flame, 63-12
- Reduction
 - coefficient, noise, *A-135*
 - in area, 46-6
- Redundancy, 61-9
 - degree of, 44-1
 - reliability, 11-8
- Redundant member, 43-7, 43-13
- Reference value, 60-13
- Refining iron, *45-3*
- Reflectance, 68-3
- Reflect angle, 6-1
- Reflection, light, 68-3
- Reflux pool-boiling receiver, 31-3
- Reformer, 31-8
- Reformulated gasoline, 22-6
- Refracted light, 68-3
- Refractory
 - ash, 22-3
 - material, 37-4
- Refrigerant, 33-2, 33-9
- Refrigerant-12, properties, *A-56-A-60, A-75-A-77*
- Refrigerant-22, properties, *A-61-A-63, A-78-A-80*
- Refrigerant HFC-134a, properties, *A-64, A-81*
- Refrigeration, 33-1
 - capacity, 33-3
 - cycle, air, 33-6
 - cycle, Carnot, 33-3
 - effect, 33-3
 - load, 41-1 (ftn)
 - tons, 33-3
- Refuse, 22-4
- Refuse-derived fuel, 22-4, 66-32
- Regain, static, 20-15, *20-23*
- Regeneration, 21-17
- Regenerative
 - air preheater, 27-15
 - cycle, 28-7
 - heat exchanger, 36-10 (ftn)
- Regenerator, 29-12, 29-18
 - effectiveness, 29-19
 - efficiency, 29-19
- Region
 - elastic, 46-2
 - entrance, 36-5
 - feasible, 61-12
 - proportional, 46-2
 - transition, 16-8
- Register, 20-24
- Registered engineer, 72-1
- Registration, 72-1
- Regression
 - linear, 11-13
 - nonlinear curves, *11-14*
- Regula falsi method, 13-2 (ftn)
- Regular
 - function, 8-1
 - lay, 64-2
- Regulating system, 60-13
- Regulation
 - speed, 67-10
 - voltage, 67-10
- Regulator, 60-13
- Reheat, 41-4
 - control, 42-1
 - factor, 28-6
 - temperature, 27-13
- Rankine cycle, 28-5
- Reheater, 27-13, 30-1
- Reheating turbine, 27-8
- Reid vapor pressure, 66-10
- Reinforcement, opening, 53-11
- Related angle, 6-2
 - functions of, 6-3
- Relative
 - abundance, 21-2
 - atomic weight, 21-1
 - bonus, 61-20
 - earnings, 61-20
 - efficiency, 29-3
 - humidity, 38-2
 - motion, 55-9
 - position, 55-9
 - risk, 69-34
 - roughness, 17-4
 - stability, 60-11
 - time, 34-4
 - velocity difference, 17-29
- Reliability, 11-7, 11-8, 11-13, 61-9
- Reliability (measurement), 62-2
- Relief angle, 63-2
- Reloading curve, 46-6
- Reluctance, 62-4 (ftn)
- Remainder method, 12-1
- Remedial maintenance, 61-10 (ftn)
- Remediation, 66-17
- Removal
 - efficiency, 66-25
 - of heat, ventilation, 39-3
- Renewable energy source, 31-1
- Renewal, 61-11
- Repair, mean time to, 61-9
- Rephosphorized steel, 45-5
- Replacement, 21-6, 61-11
- Replacement study, 69-18
- Repose, angle of, 56-6, 64-4, *64-4*
- Repowering, 27-8 (ftn), 29-22

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Research
and development cost, 69-32
octane number, 22-6
- Reserve, 27-15 (*see also type*)
- Reservoir
heat, 25-10
modeling, 59-7
three-, 17-20
- Residual
fuel oil, 22-6
gas, 32-3
value, 69-16
- Resilience, 46-6, 50-4
- Resin, ion exchange, 21-15
- Resistance, 34-3
bridge, 62-9
contact, 34-6 (ftn)
electrical, 67-2
motion, 14-2
rolling, 56-7
shear, 14-1
temperature detector, 62-5
thermal, 40-2
thermal, coefficient, 62-6
vehicular, 56-19
- Resistivity, , 62-6
electrical, 67-2
- Resistor, 67-2, 67-3, 67-5
- Resolution, 3-6, 9-8
- Resonance, 58-10
- Resource-recovery plant, 66-31
- Response, 59-1 (*see also Steady-state response*)
dynamic, 49-7
equation, 60-14
frequency, 60-10, 60-11
function, 59-1
natural, 60-2
sinusoidal, 60-2
static, 49-7
time, 60-7, 60-9
types, 60-1, 60-2
unit step, 60-2, 60-2
variable, 59-2
- Restitution, coefficient, 56-15
- Resulfurized steel, 45-5
- Resultant
acceleration, 55-8
equivalent, 43-4
vector, 5-2, 5-3
- Resuperheater, 27-13
- Retainer fee, 70-5
- Retentivity, 66-23
- Retort stoking, 27-3
- Retrofitting, 27-16
- Return on investment, 69-11, 69-14, 69-15
- Reverberant
field, 68-6
room, 68-6
- Reverberatory furnace, 45-10
- Reverse
-bias, 62-5 (ftn)
transfer function, 60-4
- Reversible
adiabatic process, 25-8
process, 25-3
- Reverted gear set, 57-4
- Revolution
surface of, 9-5, 48-3
volume of, 9-5, 48-3
- Reyn, 52-19
- Reynolds number, 1-9 (tbl), 16-7, 35-3, 36-2
condensation, 35-9
critical, 36-3
film, 35-9
mixing, 64-12
similarity, 17-38
- Rheopectic fluid, 14-7
- Rheostat, 67-2
- Rich-quench-lean combustion, 29-15
- Right
angle, 6-2
-hand rule, 5-4, 43-3
triangle, 6-2
- Righting moment, 15-16
- Rigid
body, 55-1, 56-8
body motion, 56-2
truss, 43-12
- Rigidity, 49-2, 49-3
- Rigidity, modulus, 46-7
- Rim flywheel, 57-3
- Rimmed steel, 45-4
- Ring
flange, 53-14
gear, 57-5
permutation, 11-2
rotating, 57-2
- Ringelman scale, 22-13
- Riser, 27-4 (fig), 63-8, 65-2, 65-13, 65-14
- Rise time, 60-2
- Risk 61-25 (*see also type*)
analysis, 69-43
assessment, 61-27
-free investment, 69-11
- Rivet, 51-10
- Rms value, 67-5
- Roadway banking, 56-21
- Rocket, 56-17
- Rockwell hardness, 46-12
- Rod, slider, 55-13
- Rohsenow equation, 14-10
- Roll, 56-2
- Roller
lifter, 57-10
support, 43-7
- Roll forming, 63-13
- Rolling
friction, coefficient of, 56-8
resistance, 56-7, 56-19
- Room
clean, 39-5
constant, 68-8
sensible heat ratio, 38-6
- Root, 3-3, 13-1
double, 3-3
finding, 13-1
-locus diagram, 60-12
-mean-square speed, 24-16
-mean-square value, 11-10, 67-5
- Rope, 43-11 (ftn), 64-1
wire, 64-2, 64-3
- Roping, 64-3
- Rosette strain gate, 62-8
- Rotameter, 17-21
- Rotary
action pump, 18-2, 18-3
feeder, 64-6
positive-displacement compressor, 32-1 (ftn)
turboblower, 32-1 (ftn)
- Rotating
compressor, 32-1
disk, 57-2
fluid mass, 57-3
hub, 57-2
machine, electrical, 67-10, 67-13
ring, 57-2
- Rotation, 55-6, 56-2
free, 58-5
of axis, 48-7
of fluid mass, 15-19
pipe bundle, 66-36
- Rotational
symmetry, 7-4
system, modeling, 59-5
- Rotor
flywheel, 57-3
motor, 67-12
wind machine, 31-4
- Rotor concentrator, 66-23
- Roughness
coefficient, 17-7
height index, 2-4
relative, 17-4
specific, 17-4, 17-4, A-31
specific, ducts, 20-11 (ftn)
weight, 2-4
- Rough-pipe flow, 17-5
- Routh criterion, 60-12
- Roving, 45-19 (ftn)
- Row
canonical form, 4-2
equivalent matrix, 4-2
matrix, 4-1
operation, 4-2
rank, 4-5 (ftn)
-reduced echelon form, 4-2
-reduced echelon matrix, 4-1
- Rth-order difference, 3-10
- Rubbish, 22-4
- Rule, 71-1
Amagat-Leduc's, 24-17
Cramer's, 3-7, 4-6
derived from, 66-4
Gibbs, 24-18
Gibbs phase, 47-3
lever, 38-5, 47-2
L'Hôpital's, 3-9
Miner's, 50-7
mixture, 66-4
octave, 58-19
of professional conduct, 71-1

Italicized page numbers represent sources of data in tables, figures, and appendices.

- of signs, Descartes', 3-4
- right-hand, 5-4, 43-3
- Simpson's, 7-2
- trapezoidal, 7-1
- Rules, SI system, 1-5
- Runaway speed, 17-30
- Runner, turbine, 18-21
- Runoff, 66-16
- Run-of-mine coal, 22-4
- Run-of-the-nut method, 51-12
- Rupture
 - angle of, 46-7
 - Mohr's theory, 46-7
 - strength, 46-15
- R-value, 34-3
- S**
- Sabin, 68-9
- Sacrificial anode, 21-12
- Saddle point, 7-2
- Safeguard, machine, 61-30
- Safety
 - factor of, 50-1
 - margin of, 50-1
 - risk assessment, 61-27
- Salary plus fee, 70-5
- Salometer scale, 14-4 (ftn)
- Sal soda, 63-4
- Salt, crevice, 21-11
- Salvage value, 69-18
- Sample, 11-2
 - plan, single-, *A-128*
 - space, 11-3
 - standard deviation, 11-10
 - variance, 11-11
- Sampling
 - emissions, 66-20
 - with replacement, 11-3
 - work, 61-17
- Sand
 - blasting, 63-13
 - green, 63-8
 - molding, 63-8
- Sandwiched plane, 34-6
- SAP alloy, 45-19
- Satisfier, 61-28
- Saturated
 - air, 38-2
 - hydrocarbon, 22-1
 - liquid, 24-2, 24-12
 - liquid line, 24-3
 - polymer, 45-15
 - solution, 21-7
 - steam properties, *A-44, A-47, A-65, A-67*
 - temperature, 24-4
 - vapor, 24-2, 24-12
 - vapor line, 24-3
 - water, *A-98*
- Saturation
 - degree of, 38-2
 - efficiency, 38-7, 38-11
 - pressure, 14-9
 - process, adiabatic, 38-7, 38-10
 - ratio, 38-2
 - table, 24-10
- Saybolt
 - second, 14-6 (ftn)
 - seconds
 - Furol, 14-6 (ftn)
 - universal, 14-6 (ftn)
 - universal, conversions, 18-2 (ftn), 19-1 (ftn)
 - universal viscosity, 52-19
 - viscometer, 14-6 (ftn)
- Scalar, 5-1
 - matrix, 4-1
 - product, triple, 5-4
- Scale
 - API, 14-4
 - Baumé, 14-5
 - model, 17-38
 - Ringelman, 22-13
- Scaling, 27-12, 36-17
- Scavenging, 21-15, 29-2
- s-chart, 61-22
- Schedule-40 pipe, *16-11*
- Schedule (pipe), 16-10
- Schmidt number, 1-9 (tbl)
- Scleroscopic test, 46-13
- Scratch hardness, 46-12
- Screw
 - conveyor, 64-5
 - feeder, 64-5
 - power, 52-22
- Screwed fitting, 17-12 (ftn)
- Scroll compressor, 33-7
- Scrubber, 66-22
- Scrubbing, 66-37
- Seal, 66-35
- Seal material, 19-2 (ftn)
- Seam, 53-2 (ftn), 53-6 (ftn)
- Seamless
 - pipe, 63-13
 - shell, 53-3
- Secant
 - formula, 51-3
 - modulus, 46-4
 - modulus (bulk), 14-13
- Second
 - acceleration, 57-10
 - critical back-pressure ratio, 26-13
 - critical shaft speed, 58-15
 - derivative, 8-1
 - law of thermodynamics, 24-7 (ftn), 25-11
 - moment of a function, 9-6
 - moment of the area, 48-3
- Secondary
 - air, 27-3
 - combustion chamber, 66-30
 - creep, 46-15
- Second-order, linear, 10-3
- Section
 - conic, 7-8, 7-9
 - dangerous, 49-11
 - drawing, 2-3
 - modulus, 49-11
- Sections, method of, 43-15
- Seebeck
 - coefficient, 31-9
 - effect, 62-6
- Seider-Tate correlation, 36-5, 36-6
- Selective
 - catalytic reduction, 66-13, 66-37
 - leaching, 21-11
 - noncatalytic reduction, 66-38
 - surface, 31-2
- Selectivity, classification, 64-11
- Self-energizing brake, 52-16
- Self-locking brake, 52-16
- Self-locking screw, 52-22
- Self-regulating plan, 61-20
- Semidry scrubbing, 66-37
- Semi-infinite solid, 34-13
- Semi-killed steel, 45-5
- Semimajor distance, 7-11
- Semiminor distance, 7-11
- Semivariable cost, 69-31
- Semivertex angle, 26-11
- Sense, 5-1
- Sensible heat, 24-8, 39-3
 - factor, 38-6
 - ratio, 38-6, 41-3
- Sensible heating/cooling, 38-8
- Sensitivity, 11-13, 60-5, 62-2
 - analysis, 61-12, 69-43
 - fatigue notch, 46-10
- Sensitization, 45-9
- Sensor, 42-1, 62-3
- Separable, first-order, 10-3
- Separation
 - cyclone, 64-10
 - factor, 66-26
 - mesh, 64-10
 - of terms, 9-2
- Separator, moisture, 30-1
- Sequence, 3-10
 - arithmetic, 3-11
 - convergent, 3-10
 - divergent, 3-10
 - geometric, 3-11
 - harmonic, 3-11
 - p*-, 3-11
 - standard, 3-11
- Sequential combustion, 29-14
- Serial reliability, 11-8
- Series, 3-11
 - arithmetic, 3-11
 - circuit, electrical, 67-3
 - expansion, 8-8
 - finite, 3-11
 - Fourier, 9-6
 - galvanic, 21-11, *21-12*
 - geometric, 3-11
 - harmonic, 3-11
 - hydrocarbon, 22-2
 - infinite, 3-11
 - Maclaurin, 8-7 (ftn)
 - of alternating sign, 3-12
 - p*-sequence, 3-11
 - pipe, 17-19
 - pumps, 18-17
 - Taylor's, 8-7
- Server, 61-6, 61-7
- Service
 - factor, 40-4, 56-7 (ftn), 61-6, 61-7, 67-11

Italicized page numbers represent sources of data in tables, figures, and appendices.

- gear drive, 52-11
 - V-belt, 52-16
- life, 69-20
 - pressure vessel, 53-3
- Servomechanism, 60-13
- Set, 11-1
 - laws, 11-1
 - null, 11-1
 - permanent, 46-2
 - point, 21-16, 42-2
 - theory, 11-1
 - universal, 11-1
- Setback, thermostat, 40-6
- Setting, 27-4
- Settleable solid, 66-41
- Settling time, 60-2
- Severability, 70-3
- Shading
 - coefficient, 41-2
 - factor, 31-2
- Shaft
 - critical speed, 58-15, 58-17
 - design, 51-13
 - loading, pump, 18-10
 - stepped, 58-5
 - twist, 46-7, 51-13
 - vibration, 58-15
 - work, 25-6, 27-8
- Shaker table, 58-21
- Shape
 - factor, 34-20, 34-21, 37-2, 37-2, 37-4
 - mode, 58-19
 - of a fluid, 14-1
- Shaving wheel fan, 20-4
- Shear, 49-7
 - diagram, 49-8
 - flow, 51-15
 - formation, rate of, 14-6
 - horizontal, 49-10
 - modulus, 46-7, 46-7, 49-2, 51-13
 - one-way, 49-7 (ftn)
 - rate, 14-6, 17-13
 - resistance, 14-1
 - single/double, 51-10
 - strain, 46-7
 - strength, 46-8
 - stress, 49-2
 - beam, 49-9
 - fluid, 14-6, 17-13
 - theory, maximum, 50-3
 - wind, 31-5
- Shearing, 63-7
- Sheave, 43-11, 64-2
- Sheet metal gauge, A-123
- Shelf, 47-2
- Shell, 53-3
 - and-tube heat exchanger, 36-10
 - torsion, 51-14
 - type element, 53-3
- Sheradizing, 63-14
- Sherwood number, 1-9 (tbl)
- Shewhart control chart, 61-22
- Shield, 61-30
- Shielded metal arc welding, 63-12
- Shift, 61-22
- SHM, 58-6
- Shock, 58-19
 - angle, 26-11
 - wedge, 26-11
 - normal, A-85
 - pulse, 58-19
 - transmission, 58-20
 - treatment, 27-12
 - wave, 26-9, 26-11, 26-13
- Shoe brake, 52-17
- Shore hardness, 46-13
- Short
 - circuit, electrical, 67-2
 - term exposure limit, 39-5
- Shotpeen, 47-10, 52-3
- Shotting, 45-10
- Shrink fit, 51-5
- Shutoff
 - head, 18-15
 - pump, 65-3
 - service valve, 16-11
- SI base units, 1-5
- SI-derived units, 1-5, 1-6
- Sick building, 66-5
- Side friction factor, 56-21
- Sidewall sprinkler, 65-4
- Sideways friction, 56-21
- Siemens, 67-2
- Sieving, 64-10
- Sigma
 - chart, 61-22
 - phase (steel), 45-8 (ftn)
- Sign
 - alternating, series of, 3-12
 - convention (thermal), 25-4
 - convention, thermodynamic, 28-1
 - of the function, 6-3, 6-3
- Signal analyzer, 9-7
- Signature analysis, 9-7 (ftn)
- Significant digit, 3-1, 12-1
- Silica, 45-18
- Siliceous-gel zeolite, 21-14
- Silicon
 - bronze, 45-12
 - carbide, 45-19
- Similarity, 17-38
 - fan, 20-9, 20-9
 - law (pump), 18-18
 - partial, 17-40
- Similar triangle, 6-2
- Simple
 - cycle, 29-17
 - harmonic motion, 58-2, 58-6
 - interest, 69-11, 69-39
 - support, 43-7
- Simplex
 - method, 61-12
 - pump, 18-2
- Simplified boiling water reactor, 30-2
- Simpson's rule, 7-2
- Simultaneous
 - equations, matrix, 4-6
 - linear equations, 3-7
- Sine function, integral, 9-8
- Sines, law of, 6-5, 6-6
- Single
 - acceptance plan, 61-25
 - acting engine, 29-2
 - acting pump, 18-2
 - butt, 51-10 (ftn)
 - degree of freedom, 58-2, 59-2
 - duct system, 42-1
 - pass heat exchanger, 36-10
 - payment cash flow, 69-3
 - payment present worth factor, 69-5
 - sampling plan, A-128
 - seal, 66-35
 - shear, 51-10
 - stage pump, 18-4
 - suction pump, 18-4
- Singularity, 4-5
- Singularity function, 59-3
- Singular matrix, 4-1, 4-5
- Singular point, 8-1, 8-3 (ftn)
- Sink, 33-1 (ftn)
 - energy, 17-15
 - reservoir, 25-10
- Sinking fund, 69-7
 - factor, 69-7
 - method, 69-22
 - plus interest, 69-22
- Sintered carbide, 45-19, 63-4
- Sintering, 45-19 (ftn), 63-10, 63-11
- Sinusoidal
 - response, 60-2
 - test, vibration, 58-20
- Siphon, 17-19
- SI system, 1-5, 1-7
- Six nines rule, 66-30
- Size, motor, 18-8
- Sizing, 63-7
- Skelp, 63-13
- Skewness, 11-11
- Skew symmetric matrix, 4-2
- Skidding distance, 56-21
- Skin friction, 17-5 (ftn), 17-34
- Skin friction coefficient, 17-38, 36-4
- Slab, 40-3, 45-10 (ftn)
- Slab edge coefficient, 40-3
- Slack time, 61-3, 61-4
- Slag, 22-3, 29-15, 45-3
- Slagging, 29-20 (ftn)
- Slender column, 51-1
- Slenderness ratio, 51-2
- Slider
 - crank, 55-13
 - rod, 55-13
- Sliding
 - factor of safety, 15-12
 - load unit, 27-16
 - plate viscometer test, 14-6
 - pressure operation, 27-16
 - vector, 5-1 (ftn)
- Sling psychrometer, 38-7
- Slip, 18-9
 - ammonia, 66-37 (ftn)
 - electrical, 67-12
 - pump, 18-3
- Slipping, 56-9
- Slope, 8-1

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Slope form, 7-5
Slow-closing valve, 17-32
Sludge, 66-3 (ftn)
 conditioner, 21-16
 incineration, 66-34
Slug, 1-3
Slurry, friction loss, 17-11
Small angle approximation, 6-3
Smear metal, 63-5
Smelting, 45-11
Smith
 forging, 63-7
 line, 50-7 (ftn)
Smog, 66-17
Smoke, 22-13, 66-17
 damper, 20-18
 spot number, 22-13, 66-17
Smoothing coefficient, 69-22
Snagging, 63-5
Soderberg line, 50-6
Sodium-sulfur battery, 31-10
Softening
 point, Vicat, 46-11
 precipitation, 21-14
Soft material, 46-16
Softwood, 45-16
Soil
 incineration, 66-34
 washing, 66-38
Solar
 cell, 31-4
 collector, 31-2
 constant, 31-1, 37-7
 cooling load, 41-2
 energy, 31-1
 energy generating system, 31-3
 gear set, 57-5
 power cycle, 31-3
 radiation, 37-7
 system, active, 31-2 (ftn)
Soldering, 63-12
Sole proprietorship, 70-1
Solid, 24-2
 angle, 6-6
 height, 52-5
 oxide fuel cell, 31-8
 polymer fuel cell, 31-8
 property, 24-11
 -solution alloy, 47-1
 suspension, 64-12
 waste, 66-3
 municipal, *66-33*
Solids, properties, *A-82*
Solidus line, 47-1
Solubility, 47-3, 66-39
Solute, 14-9, 21-7
Solution, 14-9, 47-3
 buffer, 21-9
 complementary, 10-4, 58-10
 heat treatment, 47-9
 neutral, 21-8
 particular, 10-4
 saturated, 21-7
 trivial, 3-7 (ftn)
Solutions, 14-15, 21-7
Solvency, 69-34
Solvent, 14-9, 21-7
Solvent recovery, 66-23
Sommerfeld number, 52-22
Sone scale, 68-8
Sonic
 boom, 14-14
 velocity, 14-14, 68-4
Sorbent injection, 66-38
Sound, 68-3
 abatment, 68-9
 absorption coefficient, 68-8
 field, 68-5
 intensity, 68-4
 meter, 68-5
 power level, 68-7
 pressure level, 68-6
 speed of, 14-14, 68-4, *68-5*
 transmission class, 68-9
 wave, 68-4
Source, 33-1 (ftn)
 energy, 17-15
 reservoir, 25-10
Space
 heating, 29-21, 33-2
 mechanics, 56-19
Spacing, molecule, 14-2
Span, 17-33
Sparging, 66-38
Spark ignition, 29-2
Special
 damages, 70-7
 triangle, 6-2
Specific
 capacity, battery, 31-10
 collection area, 66-27
 cutting energy, 63-3
 energy, 16-1, 16-9, 23-1
 battery, 31-10
 flywheel, 57-2
 feed characteristic, 66-29
 fuel consumption, 29-3
 gas constant, 24-14
 gravity, 14-4
 hydrocarbon, *A-18*
 heat, 24-7, *24-8*, 34-3
 gas, 24-15
 gases, *22-2*, *24-20*, *A-99*, *A-100*
 liquids, *A-98*
 load, 36-14
 polytropic, 25-2
 ratio of, 15-13, 24-8
 real gas, 24-20
 solids, *A-90*, *A-91*
 humidity, 38-2
 impulse, 26-8
 performance, 70-4, 70-5
 power, 31-10
 power, flywheel, 57-2
 properties, 24-4
 roughness, 17-4, *17-4*, *A-31*
 duct, 20-11 (ftn)
 speed, 18-11, *18-8*, *18-11*
 fan, 20-4
 suction, 18-15
 turbine, 18-20
 volume, 14-4, 24-5
 weight, 14-5
Specification limit, 61-22 (ftn)
Specimen, 46-1
Spectrum analyzer, 9-7
Specular reflection, 68-3
Speed, 55-3
 control
 compressor, 32-2
 constant, 60-13
 motor, 67-15
 turbine, 27-16
 cutting, 63-2, 63-3, *63-3*
 factor, 52-13
 of efflux, 17-16
 of molecule, 24-17
 of sound, 14-14, 68-4
 ratio, 57-5
 regulation, 67-10
 runaway, 17-30
 specific, *18-8*, 18-11, *18-11*
 fan, 20-4
 turbine, 18-20
 synchronous, 18-9, *18-9*, 67-12
Sphere, 7-12
 flow over, 36-10
 unit, 6-6
Spherical
 coordinate system, 7-3 (tbl), 7-4 (fig)
 defect, 6-6
 drop, 10-10
 excess, 6-6
 shell, conduction, 34-10
 tank, 51-5
 triangle, 6-5
 trigonometry, 6-5
Sphericity, 17-36, *17-36*
Spheroidize-annealing, 47-9
Spheroidizing, 47-9
Spider gear, 57-5
Spill, hazardous, 66-17
Spinel, 45-18
Spinning reserve, 27-15
Spitzglass formula, 17-9
Splitter, damper, 20-18
Spool valve, 19-2
Spot humidification, 39-3
Spray
 chamber, 38-2 (ftn), 38-10 (ftn)
 ratio, 38-11
 tower, 66-22, 66-39
Spring
 allowable stress, 52-3, *52-4*
 -back, 63-7
 buckling, 52-7, *52-8*
 clock, 52-9 (ftn)
 compression, 52-6
 constant, 49-2, 52-2
 constant, torsional, 58-5
 design, 52-2
 dynamic response of, 52-8
 end treatment, *52-6*
 energy, 23-3

Italicized page numbers represent sources of data in tables, figures, and appendices.

- extension, 52-8
- fatigue loading, 52-4
- flat, 52-9
- flat coil, 52-9 (ftn)
- index, 52-2 (ftn), 52-4
- leaf, 52-10
- linear, 23-2, 23-3 (ftn)
- material, 52-3, 52-3, 52-4, 52-4
- nested, 52-5
- pitch, 52-5
- power, 52-9 (ftn)
- rate, 52-2
- rate equation, 52-5
- torsion, 52-9
- wire gauge, *A-123*
- work, 23-2
- Sprinkler, 65-4
 - characteristics, 65-5
 - discharge, 65-5
 - head, 65-4
 - protection area, 65-6, 65-6
 - separation, 65-6
 - system, 65-2
 - system design, 65-9
 - worksheet, 65-11, 65-12, *A-132*
- Sprue hole, 63-8
- Spur gear, 52-10
- SQC, *61-22*
- Square matrix, 4-2
- Squirrel
 - cage fan, 20-3
 - case rotor, 67-12
- SSF (*see* Saybolt seconds Furol)
- SSU (*see* Saybolt seconds universal)
- Stability, 11-13, 15-16, 56-2, 60-11, 62-2
- Stabilization, 66-17
- Stable equilibrium, 56-2
- Stack
 - dew point, 66-4
 - effect, 22-16
 - effect head, 22-17
 - friction loss, 22-18
 - gas (*see* Flue gas)
- Stage
 - compression, 32-1
 - gear, 57-4
 - pump, 18-4
- Staged
 - air burner, 66-38
 - combustion, 66-38
 - lean combustion, 29-14
- Staging, optimum, 32-7
- Stagnation
 - energy, 6-4
 - point, 16-4
 - property, 26-2
 - tube, 16-4
- Stagnation energy, 16-4
- Stainless steel, 21-11 (ftn), 45-5, 45-7, 45-9
 - characteristics, 45-8
- Stall
 - angle, 17-33
 - limiting, 31-5
- Standard
 - atmosphere, 24-5, *A-88*
 - atmospheric pressure, *14-3*
 - bonus, 61-20
 - conditions, 14-4 (ftn), *14-4*, 22-2
 - contract, 70-4
 - cost, 61-15, 69-36
 - cubic feet per minute, 20-2
 - data, 61-16
 - deviation, 11-10
 - error of the mean, 11-11
 - gravity, 1-2
 - hour plan, 61-20
 - normal curve, *A-12*
 - normal values, 11-6, *11-12*
 - of care, 70-5 (ftn), 70-6
 - orthographic view, 2-2
 - polynomial form, 3-3
 - sequence, 3-11
 - state, chemical, 21-9
 - temperature and pressure, 14-4, *14-4*, 22-2
 - time, 61-15, 61-19
- Standardized reactor, 30-2
- Stanton number, 1-9 (tbl), 36-2
- Star gear set, 57-5
- Stat, 42-1
- State, 24-4
 - corresponding, 24-19
 - equation, 60-14
 - equation of, 24-13
 - model, 60-14
 - oxidation, 21-3
 - standard, chemical, 21-9
 - thermodynamic, 24-2
 - variable, 59-2
- Static
 - balance, 54-2, 58-18
 - deflection, 58-2
 - discharge head, 18-5
 - efficiency, 20-4
 - energy, 16-2, 23-3
 - equilibrium, 15-16, 43-6 (ftn)
 - friction, 56-6
 - pressure, 20-1
 - probe, 17-21
 - tube, 15-2
 - property, 26-3
 - regain, 20-15, 20-23
 - regain method, 20-21
 - response, 49-7
 - suction head, 18-5
- Statically indeterminate, 43-7, 44-1
- Statical moment, 48-2, 49-10
- Statics, 43-1
- Station, 61-18
- Station rate, 27-5, 28-2
- Statistical
 - error, terms, 62-3
 - process control, 11-12, 61-22
 - quality control, 61-22
- Stator (pump), 18-3
- Statute, 71-1
- Statute of frauds, 70-2 (ftn)
- Steady-
 - flow availability function, 25-12
 - flow energy equation, 25-5, 26-2
 - flow open system, 25-1
 - flow system, 25-5
 - state component, 58-11
 - state response, 60-2, 60-7
- Steam
 - admission valve, 27-16
 - bleed, 27-8
 - drum, 27-4
 - flow through nozzle, 26-20
 - friction loss, 17-9
 - generator, 27-4
 - heat recovery, 29-20
 - nuclear, 30-1
 - humidification, 38-10
 - injection, 29-14
 - process, 29-21
 - properties, *A-44*, *A-47*, *A-65*, *A-67*, *A-100*
 - pump, 18-2
 - rate, 27-15
 - stripping, 66-40
 - superheated, properties, *A-49*, *A-69*
 - table, 24-10
 - tracing, 34-20
 - turbine, 27-8
- Steel, 45-5 47-5 (*see also type*)
 - AISI-SAE designations, 45-6
 - allowable stress vs.-temperature, 53-5
 - alloying ingredients, 45-6
 - boiler tubing, *A-28*
 - grate, 19-3 (ftn)
 - pipe, 16-10
 - pipe, black, 16-10
 - pipe, water flow in, 17-8
 - carbon, 45-5
 - duplexed, 45-4
 - free-machining, 63-4
 - group, 45-7
 - hardened, 47-7
 - hardness, 47-7
 - hardness, maximum, 47-7
 - killed, 45-5
 - pipe dimensions, *16-11*, *A-22-A-25*
 - rimmed, 45-5
 - semi-killed, 45-5
 - stainless, 45-5, 45-7
 - stainless, characteristics, 45-8
 - temperature effect, 53-5
 - tool, 45-7, 63-4 (*see also type*)
- Stefan-Boltzmann law, 37-2
- Step
 - function, 10-6
 - reaction polymerization, 45-15
 - unit, 59-2, 60-2
- Stepped
 - cash flow, 69-10
 - shaft, 58-5
- Stepper motor, 60-13 (ftn)
- Steradian, 6-6
- Stiffener, beam, 49-18
- Stiffness, 49-2, 49-3
 - spring, 52-2
 - transformed, 58-8
- Stirling
 - cycle, 29-12
 - engine, 29-12

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Stochastic
 critical path model, 61-5
 model, 61-2
- Stoichiometric
 combustion, 22-9
 reaction, 21-6, 21-7
- Stoke, 14-8
- Stoker, 27-3
- Stoke's law, 17-35
- Stokes number, 1-9 (tbl)
- Stone wall point, 32-8
- Stopping distance, 56-21
- Storage
 energy, 31-9
 pile, bulk, 64-4
 tank, 66-17, 66-19
- Stove, 45-2
- STP (*see* Standard temperature and pressure)
- Straddles, 13-1
- Straight
 angle, 6-2
 -blade fan, 20-4
 condensing, 27-11 (ftn), 28-2
 extraction, 66-21
 fin, 34-18
 line
 forms, 7-5
 method, 69-21, 69-26
 plus interest, 69-22
 -tube boiler, 27-4
- Strain, 49-2
 axial, 46-4
 circumferential, 51-5
 creep, 46-15
 diametral, 51-5
 elastic, 46-2
 energy, 46-6, 49-2, 49-11, 49-15, 49-17
 energy, torsion, 51-13
 energy theory, 50-4
 engineering, 46-2
 gage, 62-8, 62-9
 gauge, 15-2, 62-13
 hardening, 46-4
 -hardening exponent, 46-5
 inelastic, 46-2
 lateral, 46-4
 physical, 46-5
 plastic, 46-2
 radial, 51-5
 rate of, 14-6
 sensitivity factor, 62-8
 shear, 46-7
 thermal, 49-4
 true, 46-5
 volumetric, 14-13
- Strainer, hydraulic, 19-5
- Stratification, 61-22
- Stratified charge combustion, 29-2
- Stratosphere, 15-12, 15-13 (ftn)
- Stream
 function, 17-3
 potential, 17-3
- Streamline, 16-7
- Streamline flow, 16-7
- Streamtube, 16-7
- Strength
 breaking, 46-3
 coefficient, 46-5
 compressive, 46-7
 creep, 46-15
 design, 49-2 (ftn)
 endurance, 46-9
 fatigue, 46-9
 proof, 51-8, 51-12
 rupture, 46-15
 shear, 46-8
 tensile, 46-3
 ultimate, 46-3
 ultimate, spring, 52-4
 versus factors, 46-16
 yield, 46-2, 46-3
- Stress, 49-2
 allowable, 50-1
 bolt, 53-15
 gear, 52-13
 pressure vessel, 53-5
 spring, 52-4
 alternating, 50-6
 alternating combined, 50-8
 bending, 49-10
 biaxial, 49-5, 50-1
 circumferential, 51-3, 51-4
 combined, 49-5, 51-13
 concentration, 49-4
 concentration factor, A-121
 concentration factor, bolt, 51-12
 concentration factor, fatigue, 46-9, 46-10
 concentration, press-fit, 51-7, 51-8
 corrosion, 21-12
 corrosion cracking, 45-9
 cylinder, thick-wall, 51-5
 effective allowable, pressure vessel, 53-9
 engineering, 46-2
 equivalent, 50-6
 extreme, 49-5
 flexural, 49-10
 longitudinal, 51-4
 mean, 46-8, 50-6
 normal, 49-2
 physical, 46-4
 principal, 49-5
 proof, 46-3 (ftn)
 range, 50-6
 -relaxation, 46-10
 relief, 47-8
 riser, 49-4
 -rupture test, 46-15
 shear, 49-2
 shear, fluid, 14-6
 -strain curve, 46-1, 46-3
 tangential, 51-3
 triaxial, 50-3, 50-5
 true, 46-4
 yield, 46-2
- Stresspeen, 52-3
- Stripping, 66-22 (ftn)
 air, 66-38
 factor, 66-40
 steam, 66-40
- Stroke, 29-2
- Strong material, 46-16
- Strouhal number, 1-9 (tbl)
- Structural
 cell, 43-12
 laminate, 45-20
 rope, 64-2
 steel, 45-5
 strand, 64-2
- Structure
 atomic, 21-1
 composite, 49-19
- Student's *t*-distribution, 61-16 (ftn), A-127
- Subautogenous waste, 66-28 (ftn)
- Subcontract, 70-4
- Subcooled liquid, 24-2, 24-11
- Sub-isokinetic, 66-20
- Sublimation, 24-9
- Submatrix, 4-1
- Submerged
 arc welding, 63-12
 fraction, 15-15
 scraper conveyor, 66-6
- Subset, 11-1
- Subsonic, 14-14
- Substance, lethal, 53-3
- Success, 11-3
- Suction, 18-4
 gas, 33-1
 head, net positive, 18-13
 line, 33-9
 specific speed, 18-15
 throttling, compressor, 32-2
- Sudden failure model, 61-11
- Sulfate sulfur, 22-3
- Sulfur, 22-3
 dioxide, 66-17
 in stack gas, 66-4
 low-, coal, 22-4
 oxides, 66-17
 trioxide, 22-3, 66-4, 66-17
- Sulfurous acid, 66-17
- Summer, 60-4
- Summer degree day, 41-2
- Summing point, 60-14
- Sum-of-the-years' digits method, 69-21, 69-26
- Sun gear, 57-5
- Sunk cost, 69-3
- Superaustenitic stainless steel, 45-8
- Supercharger, 29-10
- Superconductivity, 45-18
- Supercooled liquid, 45-17
- Supercritical
 cycle, 28-7
 -pressure boiler, 27-4
 -pressure turbine, 27-8
- Superelevation, 56-21
- Superferritic stainless steel, 45-8
- Superfinishing, 63-5, 63-14
- Superheat
 table, 24-10
 with Rankine cycle, 28-4
- Superheated
 steam, cooling, 36-20

Italicized page numbers represent sources of data in tables, figures, and appendices.

- steam, properties, *A-49, A-69*
- vapor, 24-2, 24-3, 24-13
- Superheater, 27-12 (*see also type*)
- Superhigh-speed steel, 63-4
- Super-isokinetic, 66-20
- Superposed turbine, 27-8
- Superposition, 49-16
 - loads, 43-16
 - method, 44-4
 - theorem, 10-6
- Supersaturated solution, 21-7 (ftn)
- Supersonic, 14-14
- Supplementary
 - angle, 6-2
 - firing, 29-20
 - unit, 1-5
- Supplier, dealing with, 71-2
- Supplier's risk, 61-25
- Supply
 - duct, 20-18
 - pump, fire fighting, 65-3
- Support type, 43-7
- Surcharge, 15-12
- Surface
 - acting agent, 66-10 (ftn)
 - condenser, 27-11
 - control, 25-1
 - durability, gear, 52-14
 - finish, 2-4, *2-4*, 46-9
 - finish factor, *46-10*
 - free, 16-6
 - frictionless, 43-7
 - hardening, 47-10
 - of revolution, 9-5, 48-3
 - runoff, 66-16
 - selective, 31-2
 - temperature, 10-10
 - tension, 14-10, *14-11*
- Surfactant, 66-10
- Surge
 - chamber, 18-20
 - limit, 32-8
 - tank, 17-32
- Surging, 52-8
- Surroundings, 25-1
- Susceptance, 67-5
- Suspension, 21-7
- Suspension, solids, 64-12
- Suspicious event, 61-22
- Swaging, 63-7
- Sweating, 34-10
- Swept volume, 29-2, 32-3
- Swing
 - temperature, 39-2
 - test, 58-21
 - valve, 16-12
- Symbols, 3-1
 - fluid power, 19-1, *A-38*
 - piping, *A-30*
 - weld, 53-8
- Symmetrical
 - function, 7-4
 - matrix, 4-2
 - waveform, *9-7*
- Symmetry
 - curve, types, 7-4
 - even, 9-7 (tbl)
 - full-wave, 9-7 (tbl)
 - half-wave, 9-7 (tbl)
 - odd, 9-7 (tbl)
 - quarter-wave, 9-7 (tbl)
- Synchronous
 - capacitor, 67-13
 - motor, 67-13
 - speed, 18-9, *18-9*, 67-12
- Syndiotactic polymer, 45-16
- Syngas, 29-14, 66-18
- Synthesis, 21-6
- Synthetic
 - gas, 22-5, 22-8 (ftn), 29-14
 - polymer, 45-14
 - resin, 21-15
 - standard data, 61-16
- System (*see also type*)
 - bin, 27-3
 - binary, 12-1
 - boundary, 25-1
 - bypass factor, 41-4
 - central, 27-3
 - closed, 25-1
 - consistent, 3-7
 - conventional duct, 20-17
 - curve, 20-7
 - diagram, 59-3
 - direct-firing, 27-3
 - effect, 20-7
 - equation, 59-3
 - force-couple, 43-4
 - function, 60-4
 - hexadecimal, 12-2
 - high-velocity, 20-17
 - inconsistent, 3-7
 - isolated, 25-2
 - linear force, 43-4
 - low-velocity, 20-17
 - modeling, 59-1
 - numbering, 3-1
 - octal, 12-2
 - of forces, 43-6
 - of units, 1-2
 - open, 25-1
 - performance curve, 18-15
 - riser, 65-2
 - SI, 1-5
 - steady-flow, 25-5
 - thermodynamic, 25-1
 - type, 60-13 (ftn)
 - unified numbering, 45-1
 - unit, 27-3
 - voltage, 67-5 (ftn)
 - wind energy conversion, 31-4
- Systematic error, 62-2
- T**
- T₂₅₀ temperature, 22-3
- Table
 - divided difference, 13-3
 - fan rating, 20-5
 - multirating, 20-5
- normal shock, 26-9
 - of integrals, 9-1 (ftn)
 - periodic, 21-2, *A-40*
- Tableau, 61-12
- Tachometer control, 60-13
- Tail
 - curve, 11-6
 - race, 18-20
 - water, 18-20
- Take-off, branch, 20-16
- Tall building, infiltration, 39-2
- Tandem
 - flywheel system, 57-4
 - pulley drive, 64-8 (ftn)
 - seal, 66-35
- Tangent, 7-2
 - modulus (bulk), 14-13
 - plane, 8-5
- Tangential
 - acceleration, 55-7
 - force, gear, 52-12
 - pressure angle, 52-12
 - stress, 51-3
 - turbine, 18-21 (ftn)
 - velocity, 18-21, 55-7
- Tangents, law of, 6-5
- Tangible property, 69-20 (ftn)
- Tank
 - above-ground, 66-19
 - compressed air, 32-2
 - discharge, 17-16, 17-17
 - pressurized, 17-17
 - reactor, 66-25
 - spherical, 51-5
 - thick-walled (*see* Cylinder, thick-walled)
 - thin-walled, 51-3 (*see also* Pressure vessel)
 - time to empty, 17-18
 - underground, 66-17
- Tapered-hub flange, 53-14
- Tap hole, 15-2
- Tappet, 57-10
- Target substance, 62-3
- Task, 61-15
- Tax credit, 69-25
- Taylor's
 - equation, 63-5
 - formula, 8-7
 - series, 8-7
- T-delta rosette, 62-12
- t-distribution, Student's, *A-127*
- TDC (*see* Top-dead-center)
- Tedlar bag, 66-20
- Teetering two-blade, 31-6
- Teflon, 45-15
- Telomer, 45-14
- TEMA (*see* Tubular Exchangers Manufacturers Association)
- Temper
 - carbon, 45-10
 - designations, aluminum, 47-10
- Temperature, 24-4, 24-17
 - absolute, 24-4, 24-5
 - approach, 36-13
 - at a point, 34-7

Italicized page numbers represent sources of data in tables, figures, and appendices.

- autoignition, 22-8
- bulk, 34-4, 35-3, 36-2, 36-3
- change, airflow, 36-24
- chip, 63-4
- coarsening, 47-8
- combustion, 22-15
- critical, 47-7
- cross, 36-14
- deflection, 46-10
- dew-point, 38-2
- difference, 36-13
 - equivalent, 41-2
 - logarithmic mean, 36-14
 - terminal, 27-11, 27-14
- dry-bulb, 38-1
- effect on output, 62-12
- effect, pipe, *53-16*
- effect, steel, *53-5*
- eutectic, 47-3
- fictive, 45-17
- film, 35-3, 36-3
- flame, 22-15
- flue gas, 22-13
- forging, *63-7*
- free-stream, 36-2
- glass transition, 45-17
- gradient, 34-5
- ignition, 22-8
- increase in pressurized liquid, 27-7
- inversion, 25-3, *25-3*
- net stack, 22-13
- profile, 34-5
- ratio, 36-20 (ftn)
- recrystallization, 47-8, *47-8*
- reheat, 27-13
- saturation, 24-4
- scales, *24-5*
- surface, 10-10
- swing, 39-2
- time diagram, 47-2
- transition, 46-14
 - ductile, *46-14*
- wet-bulb, 38-2
- Tempered martensite, 47-7
- Tempering, 47-7, 47-9
- Temporary hardness, 21-14
- Tendency, central, 11-10
- Tens complement, 12-3
- Tensile
 - strength, 46-3
 - test, 46-1
- Tension
 - cable, 56-11
 - effective belt, 64-8
 - surface, 14-10, *14-11*
- Tensor, 5-1
- Teratogen, 61-27
- Term
 - general, 3-10
 - in a sequence, 3-10
- Terminal
 - point, 5-1
 - temperature difference, 27-11, 27-14
 - value, 69-16
 - velocity, 17-35, 20-24, 56-17
- Terminator, 45-15
- Terms
 - harmonic, 9-6
 - separation of, 9-2
- Tertiary
 - air, 27-3
 - creep, 46-15
- Test (*see also type*)
 - comparison, 3-12
 - fatigue, 46-8
 - financial, 69-34, 69-35
 - for convergence, 3-11
 - hardness, 46-12, *46-13*
 - Hurwitz, 60-12
 - hydrostatic pressure, 53-17
 - Jominy, 47-7
 - on plastic, 46-10
 - ratio, 3-12
 - sliding plate viscometer, 14-6
 - tensile, 46-1
 - torsion, 46-7
- Testing (*see also type*)
 - boiler feedwater, 21-11
 - isokinetic, 66-20
 - nondestructive, 46-11
- Tetrafunctionality, 45-15
- Theorem
 - binomial, 3-3
 - buoyancy, 15-14
 - Cauchy-Schwartz, 5-3
 - central limit, 11-11
 - de Moivre's, 3-8
 - final value, 60-7
 - Gibbs, 24-18
 - initial value, 60-7
 - Kalman's, 60-14 (ftn)
 - Kutta-Joukowski, 17-34
 - linearity, 10-6
 - Nemst, 24-6
 - of calculus, fundamental, 9-4
 - of Fourier, 9-6
 - of Pappus, 9-5
 - of Pappus-Guldinus, 48-3
 - parallel axis, 48-4, 54-2
 - perpendicular axis, 48-5
 - Pythagorean, 6-2
 - reciprocity, for radiation, 37-4
 - superposition, 10-6
 - time-shifting, 10-6
 - transfer axis, 48-4
 - Varignon's, 43-3
- Theoretical
 - maximum velocity, 26-2
 - yield, 21-7
- Theory
 - Coulomb-Mohr, 50-2
 - distortion energy, 46-8, 50-5
 - failure, 50-1
 - maximum
 - normal stress, 50-1
 - shear stress, 46-8, 50-3
 - strain, 50-3
 - net transport, 34-2
 - octahedral shear-stress, 50-5
 - of constant energy distortion, 50-5
 - of influence, 61-28
 - Prandtl's layer, 17-37
 - queuing, 61-6
 - set, 11-1
 - strain energy, 50-4
 - von Mises, 46-8, 50-5
 - X, 61-28
 - Y, 61-28
- Therm, 40-1 (ftn)
- Thermal
 - arrest, 47-2
 - backflushing, 27-12
 - ballast, 66-30
 - capacitance, 34-12
 - capacity rate, 36-20
 - coefficient of expansion, 14-12 (ftn)
 - conductance, 34-2
 - conductance, air space, *40-3*
 - conductivity, 34-2, *34-3, 36-16, A-89*
 - cracking, 22-2
 - deflection temperature, 46-11
 - deformation, 49-3
 - desorption, 66-40
 - diffusivity, 34-4, *34-4*
 - efficiency, 22-16, 25-10, 28-1, 29-3
 - energy, 23-3 (ftn)
 - entry length, 36-5
 - equilibrium, 24-4, 25-5, 37-1, 37-6
 - expansion, 49-3
 - expansion, coefficient of, *49-4, 66-36*
 - flywheel effect, 40-5
 - gradient, 34-5
 - inertia, 40-5
 - lag, 40-5
 - NOx, 66-13
 - properties, insulation, *34-10*
 - radiation, 37-1
 - rating, power, 27-1
 - resistance, 34-3, 40-2
 - resistance, coefficient of, *62-6*
 - strain, 49-4
 - treatment, aluminum, *45-12*
- Thermionic generator, 31-9
- Thermistor, 62-5
- Thermocouple, 62-6
 - constant, *A-124*
 - material, *62-7*
- Thermodynamic
 - relation, 25-6
 - state, 24-2
 - system, 25-1
- Thermodynamics
 - first law of, closed system, 25-4
 - first law of, open system, 25-5
 - second law of, 25-11
 - third law of, 24-6
 - zeroth law of, 24-4
- Thermoelectric
 - constant, 62-7, *A-130*
 - generator, 31-9
- Thermopile, 62-7
- Thermoplastic, 45-16, 63-13
- polymer, *45-17*
- properties, *A-116*

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Thermosetting, 45-16, 63-13
 polymer, 45-17
- Thermosiphon, 33-6 (ftn), 34-20
- Thermostat, 42-1
 mixing, 42-2
 setback, 40-6
- Thickness
 insulation, 34-10
 pressure vessel, 53-3, 53-9, 53-9,
 53-10, 53-15
 tooth, 52-11
- Thick-walled cylinder, 51-4, 51-5
- Thin-walled tank, 51-3
- Third
 critical back-pressure ratio, 26-13
 derivative of motion, 57-10
 law, thermodynamics, 24-6
- Thixotropic fluid, 14-7
- Thompson effect, 62-6 (ftn)
- Thread
 Acme, 52-22
 angle, 52-22
 angle, helix, 51-13
 stress concentration, 51-12
- Threaded fitting, 17-12 (ftn)
- Three
 -dimensional areas, A-9
 -force member, 43-6
 -moment equation, 44-5
 -phase electricity, 67-8
 -reservoir problem, 17-20
- Threshold
 audibility, 68-4
 hearing, 68-6
 limit value, 39-5
 pain, 68-4
- Throat
 effective weld, 51-13
 of nozzle, 26-5
- Throttle
 control, 27-16
 temperature, 27-13
 valve, 27-16 (ftn)
- Throttling
 process, 25-2, 25-3, 25-9
 range, 42-5
 service valve, 16-11
 valve, 27-12, 27-16 (ftn), 33-1
- Through-variable, 59-3
- Throw, 20-24
- Thrust, coefficient, 26-8
- Tidal power, 31-7
- Tightened plan, 61-25
- TIG welding, 63-12
- Time (*see also type*)
 allowance, 61-16
 bed residence, 66-25
 constant, 34-12, 60-2, 60-9
 cycle, 61-18
 delay, 60-2
 effective, 26-9
 relative, 34-4
 response, 60-2 (ftn), 60-7, 60-9
 -series analysis, 9-7 (ftn)
 -shifting theorem, 10-6
 study, 61-15
 -temperature chart, 34-13
 -temperature diagram, 47-2
 -temperature-transformation curve, 47-6
 to double, 69-8, 69-8
 to empty tank, 17-18
 to triple, 69-8, 69-8
 value of money, 69-5
 -weighted average, 39-5
- Timed two-position control, 42-2
- Tip, adiabatic, 34-17
- Tire, 45-13 (ftn)
 -derived fuel, 22-4
 discarded, 66-18
- Titania, 22-3 (ftn)
- Toe (dam), 15-11
- Tolerance, 2-4
- Tone, pure, 68-3
- Tonnage, 63-6
- Tonne, 1-7
- Tons, refrigeration, 33-3
- Tool
 life, 63-5
 steel, 45-7
 group, 45-7
 type, 63-4
 wear, 63-5
- Tooth thickness, 52-11
- Top-dead-center, 29-2, 32-3
- Topping
 cycle, 29-21
 turbine, 27-8
- Torispherical head, 53-4
- Torque, 43-2
 bolt, 51-12
 brake, 29-4
 braking, 52-19
 coefficient, 51-12
 electrical motor, 67-10
 hydrostatic, 15-11
 meter, 62-14 on a gate, 15-11
 pump shaft, 18-10
 shaft, 51-13
 versus power, 52-10
- Toricelli's equation, 17-16, 18-21
- Torsion
 angle, 46-7, 51-13
 balance, 14-10
 noncircular shape, 51-15
 shell, 51-14
 solid member, 51-15
 spring, helical, 52-9
 test, 46-7
- Torsional
 pendulum, 58-5
 spring constant, 58-5
 strain energy, 51-13
- Tort, 70-5
- Tortuous-path valve, 27-12
- Total
 dynamic head, 18-6
 efficiency, fan, 20-4
 energy, 16-2, 16-4
 energy line, 17-15
 equivalent temperature difference, 41-2
 film coefficient, 35-11
 hardness, 21-14
 head, 16-3
 heat, 24-5
 impulse, 26-8
 pressure, 16-3, 20-2, 24-17
 pressure method, 20-24
 property, 26-2
 residual chlorine, 66-26
 response, 60-2
- Toughened ceramic, 45-19
- Tough material, 46-6, 46-16
- Toughness, 46-6, 46-13
 modulus, 46-6
 notch, 46-13, 47-9, 53-5
 test, 46-13
- Tow, 45-20 (ftn)
- Tower
 cooling, 38-11
 forced draft, 38-11
 load, 38-12
 losses, 38-13
 packed, 66-22, 66-39
 shadow, 31-4
 spray, 66-39
 tray, 66-39
 unit, 38-12
- Town gas, 22-7 (ftn)
- Toxicity
 dilution, 39-5
 leaching characteristic, 66-3
- Tracheid, 45-16
- Tracing, heat, 34-20
- Traction effort, 56-20
- Tractive force, 56-20
- Trade-in allowance, 69-18
- Train
 ratio, 57-5
 value, 57-5
- Transcendental function
 circular, 6-2
 derivative, 8-2
 integral of, 9-1
- Transducer, 15-2, 42-1, 58-21, 62-3
- Transfer
 axis theorem, 48-4
 fluid, 31-3
 function, 60-3, 60-4
 function method, 41-2
 molding, 63-10
 unit, 66-40
 units, number of, 36-20
- Transferred duty, 29-21
- Transform
 fast Fourier, 9-7
 Laplace, 10-5, A-11
- Transformation
 coefficient of, 5-2
 matrix, 5-3
- Transformed stiffness, 58-8
- Transformer, 67-6
- Transgranular, 21-12
- Transient
 component, 58-11
 heat flow, 34-11, A-92-A-97
 modulus, 34-4
 response, 60-2

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Transition
 element, 21-2, 21-3
 metal, 21-3
 region, 16-8
 temperature, 46-14
 temperature, ductile, *46-14*
 temperature, glass, 45-17
- Translation, 56-2
- Translucent material, 68-3
- Trans mer, 45-16
- Transmissibility, 58-12, *58-12*
- Transmissible vector, 5-1 (ftn)
- Transmission
 coefficient, 68-9
 dynamometer, 62-12
 factor, 26-18
 gear ratio, 56-20
 loss, 40-1, 68-9, *A-136*
 rope, 64-1
- Transmittance, 31-2, 66-17
- Transmitted
 load, gear, 52-12
 power versus torque, 52-10
 shock, 58-20
- Transonic, 14-14
- Transparent material, 68-3
- Transportation problem, 61-12, 61-14
- Transpose, 4-4
- Transverse
 axis, 7-11
 circular pitch, 52-12
 fin, 34-18
 load, truss, 43-16
 pressure, 17-22
 sensitivity factor, 62-8
 velocity, 55-9
 wave, 68-4
- Trapezoidal
 cam profile, 57-10 (ftn)
 rule, 7-1
- Trash, 22-4
- Traverse point, 66-20
- Tray tower, 66-39
- Treatment
 all-volatile, 21-16
 caustic phosphate, 21-16
 zero-solids, 21-16
- Tree system, 65-1
- Trestle, 43-12
- Triad, Cartesian, 5-2
- Trial, 11-2
- Triangle, 6-2
 general, 6-5
 oblique, 6-5
 Pascal's, 3-3
 right, 6-2
 similar, 6-2
 special, 6-2
 spherical, 6-5
- Triangular matrix, 4-2
- Triaxial stress, 50-3, 50-5
- Tridymite, 45-18
- Trifunctionality, 45-15
- Trigonometric
 identity, *6-2-6-5*, 6-3
 form, 3-7
 function, 6-2
- Trigonometry, spherical, 6-5
- Trihalomethane, 66-18
- Trihedral angle, 6-5
- Trimetric view, 2-3
- Trimmer die, 63-8, 63-9
- Triple
 integral, 9-3
 junction cell, 31-4
 point, 24-8, *24-8*, 47-4
 product, mixed, 5-4
 product, vector, 5-5
 scalar product, 5-4
- Triplex pump, 18-2
- Tripling time, 69-8, *69-8*
- Tripod, 43-22
- Tritium, 21-2
- Trivial solution, 3-7 (ftn)
- Tropopause, 15-13 (ftn)
- Troposphere, 15-13
- Trough-electric system, 31-3
- True
 strain, 46-5
 stress, 46-4
- Truss, 43-12
 deflection, 49-17
 indeterminate, 44-6
 transverse load, 43-16
 types, *43-11*
- TTT curve, 47-6
- Tube
 bundle, 36-9
 condensation, 35-9, 35-10
 impact, 16-4
 -in-tube heat exchanger, 36-10
 length required, 36-15
 piezometer, 15-2
 pitot, 16-4, 26-21
 stagnation, 16-4
 static pressure, 15-2
- Tubeaxial fan, 20-3
- Tubesheet feedwater heater, 27-14
- Tubing
 brass, dimensions, *A-27*
 copper, 16-10
 copper, dimensions, *A-26*, *A-27*
 hydraulic, 19-2
 steel boiler, *A-28*
- Tubular Exchangers Manufacturers Association (TEMA), 36-11
 designations, *36-11*
- Tumbling, 63-14
- Tuned system, 58-13
- Turbine, 17-14
 aeroderivative, 29-14
 axial-flow, 18-23
 combustion, 29-14
 control, 27-16
 efficiency, 27-8, 27-9
 gas, 29-14
 high-head, 18-21
 impulse, 17-29, 18-21
 meter, 17-21
 power, 17-29, 18-21
 radial flow, 18-23
 reaction, 18-22
 runner, 18-21
 specific speed, 18-20
 steam, 27-8 (*see also type*)
 throttle valve, 27-16
 type, 18-20, 18-22
- Turboblower, 32-1 (ftn)
- Turbocharger, 29-10, 32-1 (ftn)
- Turbocompressor, 32-1 (ftn)
- Turbulent flow, 16-8, 17-5
- Turndown ratio, 27-3, 27-13
- Turns ratio, 67-6
- Tuyères, 27-3, 45-2
- Twaddell scale, 14-4 (ftn)
- Twist, angle of, 51-13
- Two
 -angle formula, 6-4
 -dimensional areas, *A-7*
 -force member, 43-6, 43-12
 -metal corrosion, 21-11
 -point form, 7-5
 points, distance, 7-7
 -position control, 42-2
 -stage expansion, 27-8
 -stroke cycle, 29-2
 -stroke, diesel, 29-10
 tail limit, 11-12
- Twos complement, 12-3
- Type
 I error, 61-25
 II error, 61-25
 n system, 60-13 (ftn)
 number, 3-1
- Types of views, 2-1
- U**
- Ultimate
 analysis, 21-4, 21-5, 22-2
 CO₂, 22-12
 strength, 46-3
 strength design, 49-2 (ftn)
 strength, spring, *52-4*
- Ultrafinishing, 63-5
- Ultrahigh-strength steel, 45-5
- Ultralow
 NOx burner, 66-35
 particle arrester, 39-6
- Ultrasonic
 flowmeter, 17-22
 machining, 63-6
 test, 46-13
- Ultrasound testing, 46-11
- Unavailability, 61-9
- Unbalanced force, 43-1
- Unbiased estimator, 11-10
- Unburned fuel loss, 22-15
- Uncertainty analysis, 69-43
- Unconstrained motion, 56-9
- Undamped, forced vibration, 58-10
- Underdamped, 58-9
- Under-expansion, 26-13
- Underfeed stoking, 27-3
- Underflow, 64-10
- Underground storage tank, 66-17

Italicized page numbers represent sources of data in tables, figures, and appendices.

- Undetermined coefficients, method of, 3-6, 10-4
- Unicouple, 31-9
- Unified numbering system, 45-1
- Uniform
- acceleration, 55-3, *55-3*
 - attack corrosion, 21-10
 - cost, annual, 69-7
 - exam, 72-2
 - flow, 16-9
 - gradient factor, 69-9
 - motion, 55-3
 - pressure, clutch, 52-19
 - series cash flow, 69-3
 - wear, clutch, 52-19
- Union of sets, 11-1
- Unit
- air conditioner, 33-2
 - circle, 6-1
 - conductance, 34-6
 - impulse, 59-2
 - impulse function, 10-6
 - load method, 49-17
 - matrix, 4-2
 - operation, 27-1
 - primary, 1-7
 - ramp, 59-2
 - sphere, 6-6
 - step, 59-2, *60-2*
 - function, 10-6
 - response, 60-2
 - system, 27-3
 - tower, 38-12
 - transfer, 66-40
 - vector, 5-2, 43-2
 - vector, Cartesian, 5-2
- Unitary
- air conditioner, 33-2
 - equipment, 42-1
- Units
- consistent system of, 1-2
 - non-SI, *1-6*
 - of pressure, 14-2
 - SI base, *1-5*
 - SI-derived, *1-5, 1-6*
- Universal
- gas constant, 24-13, *24-14*
 - gravitation, Newton's, 56-18
 - sets, 11-1
 - standard data, 61-16
- Universe, 11-3
- Unloading curve, 46-6
- Unsaturated
- air, 38-2
 - hydrocarbon, 22-1
 - position, 45-16
- Unstable equilibrium, 56-2
- Unsteady heat transfer, 34-11
- Upgrade, coal, 22-5
- Upper
- bound, 9-4
 - control limit, 61-23
 - critical point, 47-4
- Upright sprinkler, 65-4
- Upset forming, 63-8
- Uptime, 61-9
- Upwind machine, 31-4
- Urea, 66-13 (ftn), 66-38 (ftn)
- Usage, electrical, 67-7
- Use factor, 27-16
- Utilization
- factor, queue, *61-7*
 - fuel, 29-22
- U-tube
- heat exchanger, 36-12
 - manometer (*see* manometer)
- U-value, thermal, *40-2*
- U-waste, 66-3
- V**
- Vacuum, 14-3, 15-2
- extraction, 66-40
 - forming, 63-10
- Valence, *21-3*
- Value
- analysis, 69-43
 - average (by integration), 9-4
 - book, 69-23
 - boundary, 10-2
 - effective, 67-5
 - engineering, 61-27, 69-43
 - expected, 69-30
 - face, 69-29
 - heating, 22-14
 - initial, 9-3, 10-1
 - limiting, 3-9
 - market, 69-23
 - Pace, 30-2
 - R*-, 34-3
 - residual, 69-16
 - salvage, 69-18
 - standard normal, 11-6
 - threshold limit, 39-5
- Valve, *16-12 (see also type)*
- angle, 16-11
 - ball, 16-11
 - butterfly, 16-11
 - check, 16-12
 - flow coefficient, 17-13
 - gate, 16-11
 - globe, 16-11
 - hydraulic control, 19-2
 - lift, 16-12
 - needle, 16-11
 - nonreverse-flow, 16-12
 - plug, 16-11
 - poppet, 29-2
 - pressure-relief, 17-32
 - spool, 19-2
 - steam throttle, 27-16
 - swing, 16-12
 - throttling, 27-12
 - types, 16-11
- Vaneaxial fan, 20-3
- van der Waal's
- equation, 24-19
 - force, 24-19
- Vane, inlet, 20-3
- Vapor
- compression cycle, 33-3
 - condensing, 66-40
 - condensing, film, 35-7
 - dominated reservoir, 31-7
 - incinerator, 66-34
 - power cycle, 28-1
 - pressure, 14-9, *14-9, A-17*
 - head, 18-5 (ftn)
 - moist air, 38-2
 - Reid, 66-10
 - saturated, 24-2
 - superheated, 24-2, 24-3
- Variable, 3-2
- area meter, 17-21
 - capacitance transducer, 62-4
 - chart, 61-22
 - cost, 69-31
 - dimensions of, 1-8 (tbl)
 - flow rate, 20-3
 - inductance transducer, 62-4
 - matrix, 4-6
 - pitch pulley, 20-3
 - reduced, 24-19
 - reluctance transducer, 62-4
 - resistor, 62-3
 - throttle pressure operation, 27-16
- Variance, 11-11, 69-36
- Variation
- coefficient of, 11-1, 61-16
 - of parameters, 10-4
- Varignon's theorem, 43-3
- Varying mass, 56-17
- V-belt, 52-16, 56-7 (ftn)
- Vector, 5-1
- addition, 5-3
 - bound, 5-1 (ftn)
 - Cartesian unit, 5-2
 - cross product, 5-4
 - dot product, 5-3
 - equivalent, 5-1 (ftn)
 - field, curl, 8-7
 - field, divergence, 8-6
 - fixed, 5-1 (ftn)
 - function, 5-5
 - gradient, 8-5
 - multiplication, 5-3
 - normal line, 8-6
 - normal to plane, 7-6
 - resultant, 5-3
 - sliding, 5-1 (ftn)
 - transmissible, 5-1 (ftn)
 - triple product, 5-5
 - unit, 5-2, 43-2
- Vectors
- equal, 5-1
 - orthogonal, 5-3
- Vehicle
- dynamics, 56-19
 - electric, 31-10
- Veil, 45-20
- Velocity, 55-3
- acoustical, 14-14
 - average, 16-8
 - bulk, 16-8
 - burnout, 56-17
 - burst, 57-3
 - centerline, 16-8

Italicized page numbers represent sources of data in tables, figures, and appendices.

- characteristic exhaust, 26-9
 - coefficient, 17-16, 17-23
 - coefficient, nozzle, 26-8
 - control, 39-4
 - control, hood, 39-4
 - dependent force, 56-17
 - distribution, 16-8
 - drift, 66-27
 - duct, 20-19
 - energy, 16-2 (ftn)
 - escape, 56-19
 - flooding, 66-22
 - gradient, 14-6, 17-13
 - head, 18-5
 - maximum fluid, 17-3
 - of approach, 16-4, 17-16, 17-23
 - of whirl, 18-10 (ftn)
 - pitch circle, 52-10
 - pressure, 20-2
 - pressure, sprinkler, 65-7
 - propagation, 68-4
 - ratio, 57-5
 - ratio, gear, 52-11, 52-15, 57-5
 - reduction method, 20-19
 - sonic, 14-14, 68-4
 - tangential, 18-21, 55-7
 - terminal, 17-35, 56-17
 - terminal duct, 20-24
 - theoretical maximum, 26-2
 - transducer, 58-21
 - Velocity ratio, pump, 18-3
 - Vena contracta, 17-16, 17-24
 - Ventilation, 39-1
 - dilution, 39-5
 - energy to warm, 40-4
 - for heat removal, 39-3
 - Venturi
 - meter, 17-23
 - nozzle, 26-5
 - ratio, pump, 18-3
 - Vertex, parabola, 7-10
 - Vertical
 - angle, 6-2
 - axis machine, 31-4
 - buckling, 49-18
 - submersible turbine pump, 65-3
 - Vessel, pressure, 53-1, 53-3
 - thickness, 53-9, 53-10
 - Vibration, 58-2, 58-6
 - beam, 58-19
 - damped, forced, 58-11
 - damped, free, 58-9
 - forced, 58-2
 - free, 58-2
 - isolation, 58-12
 - natural, 58-2
 - pick-up, 58-21
 - plate, 58-17
 - sensor, 58-21
 - shaft, 58-15
 - thin plate, 58-17
 - Vibratory feeder, 64-6
 - Vibrometer, 58-21
 - Vicat softening point, 46-11
 - Vickers hardness, 46-12
 - View
 - auxiliary, 2-2
 - axonometric, 2-3
 - central, 2-2
 - dimetric, 2-3
 - factor, 37-2
 - isometric, 2-3
 - normal, 2-1
 - oblique, 2-2
 - orthogonal, 2-2
 - orthographic, 2-2
 - orthographic oblique, 2-3
 - perspective, 2-2, 2-3
 - planar, 2-2
 - principal, 2-2
 - profile auxiliary, 2-2
 - trimetric, 2-3
 - types, 2-1
 - Virial
 - coefficient, 24-19
 - equation of state, 24-19
 - Virtual work, 49-17
 - Viscometer
 - concentric cylinder, 14-6 (ftn)
 - cup-and-bob, 14-6 (ftn)
 - Saybolt, 14-6 (ftn)
 - test, 14-6
 - Viscosity, 14-6
 - coefficient of, 14-6
 - conversion, 14-8 (tbl), A-19
 - dynamic, 14-6 (ftn)
 - effect on head loss, 17-10
 - grade, 52-19
 - index, 14-9, 19-2 (ftn), A-20
 - kinematic, 14-8, 16-7
 - limit, 52-20
 - oil, 52-20
 - power law, 17-11
 - Saybolt universal, 52-19
 - Viscous
 - coefficient, 56-17
 - damping, 58-9
 - flow, 16-7
 - Vision, center of, 2-3
 - Vitrification, 45-17, 66-24, 66-40
 - Vitrified clay (pipe), 16-10
 - VOC (*see* Volatile organic compounds)
 - Void region, 7-3
 - Volatile
 - inorganic compounds, 66-19
 - liquid, 14-9, 21-7 (ftn)
 - matter, 22-4
 - organic compounds, 66-19, 66-25
 - Volatility, 22-6
 - Voltage, 67-2
 - divider, 67-4
 - drop, 67-3
 - line, 19-5 (ftn)
 - motor, 67-15
 - phase, 19-5 (ftn)
 - regulation, 67-10
 - Voltammetric sensor, 62-3
 - Volume
 - clearance, 32-3
 - control, 25-1
 - cut-off, 29-11
 - molar, 21-4
 - of a fluid, 14-1
 - of revolution, 9-5, 48-3
 - partial, 24-17
 - ratio, 24-10
 - specific, 14-4, 24-5
 - splitter, 20-18
 - swept, 32-3
 - Volumetric
 - analysis, 22-2
 - efficiency, 29-3, 32-4
 - efficiency pump, 18-3
 - expansion, coefficient, 49-3
 - fraction, 22-2, 24-17
 - strain, 14-13
 - von Mises-Hencky theory, 50-5
 - von Mises theory, 46-8, 50-5
 - Vortex, 64-10
 - Vorticity, 8-7
 - Vulcanization, 45-13
- W**
- Wage incentive plan, 61-20
 - Wahl correction factor, 52-5
 - Wake drag, 17-34
 - Wall
 - complex, 34-7
 - composite, 34-6
 - heat transfer, 40-2
 - shear stress factor, 17-5 (ftn)
 - thermal coefficient, 40-2
 - thickness, pipe, 19-3
 - thickness, pressure vessel, 53-3, 53-9, 53-15
 - Warming, global, 66-11
 - Warning limit, 61-22
 - Wash, 31-4
 - Washer, air, 38-10, 38-11
 - Washing, soil, 66-38
 - Waste, 66-3 (*see also type*)
 - fuel, 22-4
 - heat boiler, 29-20
 - to-energy facility, 66-31
 - Wastewater, 66-41
 - Wasting, 21-16
 - Water
 - bulk modulus, 14-13
 - chemistry equivalent, A-41, A-42
 - compressed, A-51, A-70
 - cooling, 36-14
 - deionized, 21-16
 - demineralized, 21-16
 - evaporization, film coefficient, 35-11
 - film coefficient, 35-3
 - flow, steel pipes, 17-8
 - flow through schedule-40 pipe, A-36
 - gas, 22-7 (ftn)
 - hammer, 17-31
 - hammer factor, 19-3
 - hardness, 21-13
 - horsepower, 17-14, 18-6, 18-7
 - latent heat, 24-9
 - make-up, 21-15
 - moderated reactor, 30-1

Italicized page numbers represent sources of data in tables, figures, and appendices.

- of crystallization, 21-4
 - of hydration, 21-4
 - power, 18-6
 - properties, *A-13, A-14*
 - range, 38-12
 - rate, 27-15
 - reactor, boiling, 30-2
 - reactor, pressure, 30-1
 - saturated, *A-98*
 - softening equivalent, *A-41, A-42*
 - spray humidification, 39-3
 - supply chemistry, 21-13
 - tube boiler, 27-4
 - tubing, copper, 16-10
 - vapor, 66-19
 - vapor pressure, *A-17*
 - Watt, 1-5
 - Watt density, 40-4 (ftn)
 - Wave
 - Mach, 26-11 (ftn)
 - normal shock, 26-9
 - oblique shock, 26-11
 - power, 31-7
 - sound, 68-4
 - weak shock, 26-11
 - Waveform
 - Fourier, 9-7
 - frequency, 9-6
 - period, 9-6
 - symmetrical, 9-7 (tbl)
 - Wavelength, sound, 68-4
 - Waviness height, 2-4
 - Weak
 - material, 46-16
 - shock wave, 26-11
 - Wear, tool, 63-5
 - Web, 48-4
 - crippling, 49-18
 - stiffener, 49-18
 - Weber number, 1-9 (tbl), 17-40
 - Wedge, 56-7
 - angle, 63-2
 - shock angle, *26-11*
 - Weibull distribution, 61-9 (ftn)
 - Weight, 1-1, 1-3, 54-1
 - and proportion problem, 21-6
 - atomic, 21-1, *A-39*
 - combining, 21-5
 - density, 1-3
 - equivalent, 21-4
 - formula, 21-4
 - molecular, 21-4
 - roughness, 2-4
 - specific, 14-5
 - Weisbach equation, 17-7
 - Weld
 - bead crack, 45-9
 - decay, 21-10, 45-9
 - examination, 53-9
 - fillet, 51-13
 - group, properties, *A-122*
 - joint, efficiency, *53-9*
 - pressure vessel, *53-8*
 - symbols, 53-8
 - throat, effective, 51-13
 - type, 63-11 (fig)
 - Welded
 - plate exchanger, 36-12
 - seam, 53-2 (ftn)
 - Welding, 63-11
 - bell, 63-13
 - neck flange, 53-14
 - pressure vessel, 53-7
 - Well, injection, 66-28
 - Western coal, 22-4
 - Wet
 - bulb depression, 38-2
 - bulb temperature, 38-2
 - compression, 33-4
 - scrubber, 66-22
 - scrubbing, 66-37
 - Wetted perimeter, 16-6
 - Weymouth
 - equation, 26-17
 - formula, 17-9
 - Wheatstone bridge, 62-9
 - Whirl, velocity of, 18-10 (ftn)
 - Whisker, 45-19
 - Whistle-blowing, 71-3 (ftn)
 - White
 - cast iron, 45-9, 47-8
 - noise, 68-4
 - Whole
 - air sample, 66-20
 - depth, 52-10
 - Width, 2-2
 - Wide beams, 49-16, 52-9
 - Wind
 - axis machine, 31-4
 - energy conversion system, 31-4
 - farm, 31-6
 - power, 31-4
 - power coefficient, *31-6*
 - shear, 31-5
 - velocity, effective, 39-2
 - Windage loss, 38-13, 67-15
 - Windbox, 29-23
 - Winfrey method, 69-16 (ftn)
 - Winter degree day, 40-5
 - Wire, *64-2*
 - film coefficient, 35-7
 - gauge, *A-123*
 - length, 52-5
 - rope, 64-1, *64-2, 64-3*
 - tube correlation, *35-7*
 - Wood, 22-3, 45-16, *45-17*
 - Work, 23-1
 - compressor, 32-4
 - done by force, 23-2
 - done by linear spring, 23-2
 - done by torque, 23-2
 - energy principle, 23-3, 23-4, 52-2
 - external, 23-1
 - factor, 61-16 (ftn)
 - flow, 23-3, 25-6
 - graphically finding, 25-4
 - internal, 23-1, 46-6
 - measurement, 61-15
 - methods, 61-27
 - performed by a force, 9-4
 - p-V*, 23-3, 25-6
 - sampling, 61-17
 - shaft, 25-6, 27-8
 - virtual, 49-17
 - Working
 - cold, 47-9, *63-7*
 - depth, 52-10
 - hot, 47-9, *63-7*
 - pressure, pressure vessel, 53-6
 - Worksheet, sprinkler, 65-11, *65-12, A-132*
 - Worm
 - drive, 52-14
 - gear, 52-14
 - Worth
 - future, 69-5
 - present, 69-5
 - Wrap, cable, 64-3
 - Wrought iron, 45-10
 - Wye-connection, 67-9
- X**
- x*-bar chart, 61-22, 61-23
 - X-ray testing, 46-12
- Y**
- Yaw, 56-2
 - Year-end convention, 69-3
 - Yield, 21-7, 69-28
 - bond, 69-30
 - classification, 64-11
 - mass, 66-33
 - point, 46-2
 - strength, *46-3*
 - stress, 46-2
 - Young's modulus, 46-2, *46-2, 49-2*
- Z**
- Zebra mussel, 27-12
 - Zeolite, 21-14
 - Zeolite process, 21-14
 - Zero, 3-3, 13-1, 60-8
 - defect program, 61-28
 - discharge facility, 66-9
 - force member, 43-14
 - length loss, 20-15
 - matrix, 4-2
 - solids treatment, 21-16
 - Zeroth law of thermodynamics, 24-4
 - Zone test, 61-22
 - Zuber equation, 14-10
 - z*-values for confidence levels, *11-12*